

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

SECTION 1. IDENTIFICATION

Product name : Bismuth Subnitrate Formulation

Manufacturer or supplier's details

Company : MSD

Address : Talcahuano 750, 6th floor, Ciudad Autonoma
Buenos Aires, Argentina C1013AAP

Telephone : 908-740-4000

Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@msd.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Skin sensitization : Category 1

Specific target organ toxicity - repeated exposure : Category 1 (Central nervous system)

Short-term (acute) aquatic hazard : Category 2

Long-term (chronic) aquatic hazard : Category 2

GHS label elements

Hazard pictograms



Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**

Bismuth Subnitrate Formulation

Version 7.0 Revision Date: 14.04.2025 SDS Number: 657117-00022 Date of last issue: 28.09.2024
Date of first issue: 02.05.2016

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P314 Get medical advice/ attention if you feel unwell.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Bismuth hydroxide nitrate oxide	1304-85-4	≥ 50 -< 70
Petrolatum	8009-03-8	≥ 20 -< 30
Zinc oxide	1314-13-2	≥ 5 -< 10
Benzyl alcohol	100-51-6	≥ 1 -< 5
2,6-Di-tert-butyl-p-cresol	128-37-0	$\geq 0,1$ -< 0,25

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

Most important symptoms and effects, both acute and delayed	: Rinse mouth thoroughly with water. May cause an allergic skin reaction. Causes damage to organs through prolonged or repeated exposure.
Protection of first-aiders	: First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
Notes to physician	: Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Water spray Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	: Exposure to combustion products may be a hazard to health.
Hazardous combustion products	: Nitrogen oxides (NO _x) Metal oxides Carbon oxides
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
Environmental precautions	: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- | | | |
|-----------------------------|---|---|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | Use only with adequate ventilation. |
| Advice on safe handling | : | Do not get on skin or clothing.
Avoid breathing dust, fume, gas, mist, vapors or spray.
Do not swallow.
Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment. |
| Conditions for safe storage | : | Keep in properly labeled containers.
Store in accordance with the particular national regulations. |
| Materials to avoid | : | Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Explosives
Gases |

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Petrolatum	8009-03-8	CMP (Mist)	5 mg/m ³	AR OEL
		CMP - CPT (Mist)	10 mg/m ³	AR OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Zinc oxide	1314-13-2	CMP (Fumes)	5 mg/m ³	AR OEL
		CMP (Dust)	10 mg/m ³	AR OEL
		CMP - CPT (Fumes)	10 mg/m ³	AR OEL

Bismuth Subnitrate Formulation

Version 7.0 Revision Date: 14.04.2025 SDS Number: 657117-00022 Date of last issue: 28.09.2024
 Date of first issue: 02.05.2016

		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
		STEL (Respirable particulate matter)	10 mg/m ³	ACGIH
2,6-Di-tert-butyl-p-cresol	128-37-0	CMP (Vapour and aerosol, inhalable fraction)	2 mg/m ³	AR OEL
Further information: A4 - Not classifiable as a human carcinogen				
		TWA (Inhalable fraction and vapor)	2 mg/m ³	ACGIH

Engineering measures : Ensure adequate ventilation, especially in confined areas.
 Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often!
 For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
 Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
 Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
 When using do not eat, drink or smoke.
 Contaminated work clothing should not be allowed out of the workplace.
 Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

Appearance	:	paste
Color	:	white
Odor	:	Petroleum
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not classified as a flammability hazard
Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	No data available
Solubility(ies)		
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle characteristics		

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Can react with strong oxidizing agents.
Conditions to avoid	: None known.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5.000 mg/kg
Method: Calculation method

Components:**Bismuth hydroxide nitrate oxide:**

Acute oral toxicity	: LD50 (Rat): > 2.000 mg/kg Method: OECD Test Guideline 423 Remarks: Based on data from similar materials
Acute inhalation toxicity	: LC50 (Rat): > 5,07 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 436 Remarks: Based on data from similar materials

Petrolatum:

Acute oral toxicity	: LD50 (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401 Remarks: Based on data from similar materials
Acute dermal toxicity	: LD50 (Rat): > 2.000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity Remarks: Based on data from similar materials

Zinc oxide:

Acute oral toxicity	: LD50 (Rat): > 5.000 mg/kg
---------------------	-----------------------------

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

Acute inhalation toxicity : LC50 (Rat): > 5,7 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Benzyl alcohol:

Acute oral toxicity : LD50 (Rat): 1.200 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,4 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

2,6-Di-tert-butyl-p-cresol:

Acute oral toxicity : LD50 (Rat): > 6.000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439

Result : No skin irritation

Petrolatum:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Zinc oxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

Benzyl alcohol:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation

2,6-Di-tert-butyl-p-cresol:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation
Remarks	: Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

Petrolatum:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405
Remarks	: Based on data from similar materials

Zinc oxide:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405

Benzyl alcohol:

Species	: Rabbit
Result	: Irritation to eyes, reversing within 21 days
Method	: OECD Test Guideline 405

2,6-Di-tert-butyl-p-cresol:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405
Remarks	: Based on data from similar materials

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

Respiratory sensitization

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative

Petrolatum:

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: negative
Remarks	: Based on data from similar materials

Zinc oxide:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Benzyl alcohol:

Test Type	: Human repeat insult patch test (HRIPT)
Routes of exposure	: Skin contact
Species	: Humans
Result	: positive

Assessment	: Probability or evidence of low to moderate skin sensitization rate in humans
------------	--

2,6-Di-tert-butyl-p-cresol:

Test Type	: Human repeat insult patch test (HRIPT)
Routes of exposure	: Skin contact
Species	: Humans
Result	: negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative Remarks: Based on data from similar materials
	Test Type: In vitro mammalian cell gene mutation test

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Petrolatum:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Zinc oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: equivocal

Test Type: Chromosome aberration test in vitro

Result: equivocal

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (dust/mist/fume)
Method: OECD Test Guideline 474
Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: inhalation (dust/mist/fume)

Result: positive

Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)

Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

Benzyl alcohol:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative

2,6-Di-tert-butyl-p-cresol:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative Test Type: In vitro mammalian cell gene mutation test Result: negative Test Type: Chromosome aberration test in vitro Result: negative
Genotoxicity in vivo	: Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Rat Application Route: Ingestion Result: negative

Carcinogenicity

Not classified based on available information.

Components:**Petrolatum:**

Species	: Rat
Application Route	: Ingestion
Exposure time	: 2 Years
Result	: negative

Zinc oxide:

Species	: Mouse
Application Route	: Ingestion
Exposure time	: 1 Years
Result	: negative
Remarks	: Based on data from similar materials

Benzyl alcohol:

Species	: Mouse
Application Route	: Ingestion
Exposure time	: 103 weeks
Method	: OECD Test Guideline 451
Result	: negative

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

2,6-Di-tert-butyl-p-cresol:

Species	: Rat
Application Route	: Ingestion
Exposure time	: 22 Months
Result	: negative

Reproductive toxicity

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Effects on fertility	: Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Result: negative
Effects on fetal development	: Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Method: OECD Test Guideline 414 Result: negative

Petrolatum:

Effects on fertility	: Test Type: Reproduction/Developmental toxicity screening test Species: Rat Application Route: Ingestion Result: negative Remarks: Based on data from similar materials
Effects on fetal development	: Test Type: Embryo-fetal development Species: Rat Application Route: Skin contact Result: negative Remarks: Based on data from similar materials

Zinc oxide:

Effects on fertility	: Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: Ingestion Result: negative Remarks: Based on data from similar materials
Effects on fetal development	: Test Type: Embryo-fetal development Species: Rat Application Route: inhalation (dust/mist/fume) Method: OECD Test Guideline 414 Result: negative Remarks: Based on data from similar materials

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

Benzyl alcohol:

Effects on fertility	: Test Type: Fertility/early embryonic development Species: Rat Application Route: Ingestion Result: negative Remarks: Based on data from similar materials
Effects on fetal development	: Test Type: Embryo-fetal development Species: Mouse Application Route: Ingestion Result: negative

2,6-Di-tert-butyl-p-cresol:

Effects on fertility	: Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: Ingestion Result: negative
Effects on fetal development	: Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Components:**Bismuth hydroxide nitrate oxide:**

Target Organs	: Central nervous system
Assessment	: Causes damage to organs through prolonged or repeated exposure.

Zinc oxide:

Assessment	: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.
------------	---

2,6-Di-tert-butyl-p-cresol:

Assessment	: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.
------------	--

Repeated dose toxicity**Components:****Petrolatum:**

Species	: Rat
NOAEL	: 5.000 mg/kg
Application Route	: Ingestion

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

Exposure time : 2 y

Zinc oxide:

Species : Rat, male
NOAEL : 0,0015 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 3 Months
Method : OECD Test Guideline 413

Benzyl alcohol:

Species : Rat
NOAEL : 1,072 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 28 Days
Method : OECD Test Guideline 412

2,6-Di-tert-butyl-p-cresol:

Species : Rat
NOAEL : 25 mg/kg
Application Route : Ingestion
Exposure time : 22 Months

Aspiration toxicity

Not classified based on available information.

Experience with human exposure**Product:**

Ingestion : Symptoms: The absorption of this product into the body may lead to the formation of methaemoglobine that, in sufficient concentration, causes cyanosis., May cause, Neurological disorders, Blood disorders, blood effects, central nervous system effects, Methaemoglobinemia

Components:**Bismuth hydroxide nitrate oxide:**

Ingestion : Target Organs: Blood
Symptoms: Methaemoglobinemia
Target Organs: Central nervous system
Symptoms: Neurological disorders

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Bismuth hydroxide nitrate oxide:**

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 137 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 137 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	EL50 (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201
		NOELR (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201

Petrolatum:

Toxicity to fish	:	LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10.000 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	:	NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 10 mg/l Exposure time: 21 d Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Zinc oxide:

Toxicity to fish	:	LC50 : > 0,1 - 1 mg/l Exposure time: 96 h Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 0,136 mg/l Exposure time: 72 h
		NOEC (Pseudokirchneriella subcapitata (green algae)): > 0,01 - 0,1 mg/l Exposure time: 72 h

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

Remarks: Based on data from similar materials

M-Factor (Acute aquatic toxicity)	:	1
Toxicity to fish (Chronic toxicity)	:	NOEC (Jordanella floridae (flagfish)): > 0,01 - 0,1 mg/l Exposure time: 14 Weeks Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Ceriodaphnia dubia (water flea)): > 0,01 - 0,1 mg/l Exposure time: 7 d Remarks: Based on data from similar materials
M-Factor (Chronic aquatic toxicity)	:	1

Benzyl alcohol:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 460 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 230 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 770 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
		NOEC (Pseudokirchneriella subcapitata (green algae)): 310 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 51 mg/l Exposure time: 21 d Method: OECD Test Guideline 211

2,6-Di-tert-butyl-p-cresol:

Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): > 0,57 mg/l Exposure time: 96 h Method: Directive 67/548/EEC, Annex V, C.1.
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 0,48 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0,24 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
		NOEC (Pseudokirchneriella subcapitata (green algae)): 0,24 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

M-Factor (Acute aquatic toxicity)	:	1
Toxicity to fish (Chronic toxicity)	:	NOEC (Oryzias latipes (Japanese medaka)): 0,053 mg/l Exposure time: 30 d Method: OECD Test Guideline 210
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 0,316 mg/l Exposure time: 21 d
M-Factor (Chronic aquatic toxicity)	:	1
Toxicity to microorganisms	:	EC50: > 10.000 mg/l Exposure time: 3 h Method: OECD Test Guideline 209

Persistence and degradability**Components:****Petrolatum:**

Biodegradability	:	Result: Not readily biodegradable. Biodegradation: 31 % Exposure time: 28 d Method: OECD Test Guideline 301F Remarks: Based on data from similar materials
------------------	---	--

Benzyl alcohol:

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 92 - 96 % Exposure time: 14 d
------------------	---	--

2,6-Di-tert-butyl-p-cresol:

Biodegradability	:	Result: Not readily biodegradable. Biodegradation: 4,5 % Exposure time: 28 d Method: OECD Test Guideline 301C
------------------	---	--

Bioaccumulative potential**Components:****Zinc oxide:**

Bioaccumulation	:	Species: Oncorhynchus mykiss (rainbow trout) Bioconcentration factor (BCF): 78 - 2.060
-----------------	---	---

Benzyl alcohol:

Partition coefficient: n-octanol/water	:	log Pow: 1,05
--	---	---------------

2,6-Di-tert-butyl-p-cresol:

Bioaccumulation	:	Species: Cyprinus carpio (Carp)
-----------------	---	---------------------------------

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

Bioconcentration factor (BCF): 330 - 1.800

Partition coefficient: n-octanol/water : log Pow: 5,1

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues	: Do not dispose of waste into sewer. Dispose of in accordance with local regulations.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number	: UN 3077
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc oxide, 2,6-Di-tert-butyl-p-cresol)
Class	: 9
Packing group	: III
Labels	: 9
Environmentally hazardous	: yes

IATA-DGR

UN/ID No.	: UN 3077
Proper shipping name	: Environmentally hazardous substance, solid, n.o.s. (Zinc oxide, 2,6-Di-tert-butyl-p-cresol)
Class	: 9
Packing group	: III
Labels	: Miscellaneous
Packing instruction (cargo aircraft)	: 956
Packing instruction (passenger aircraft)	: 956
Environmentally hazardous	: yes

IMDG-Code

UN number	: UN 3077
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc oxide, 2,6-Di-tert-butyl-p-cresol)
Class	: 9
Packing group	: III
Labels	: 9
EmS Code	: F-A, S-F

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Argentina. Carcinogenic Substances and Agents Registry. : Not applicable

Control of precursors and essential chemicals for the preparation of drugs. : Not applicable

The ingredients of this product are reported in the following inventories:

AICS : not determined
DSL : not determined
IECSC : not determined

SECTION 16. OTHER INFORMATION

Revision Date : 14.04.2025
Date format : dd.mm.yyyy

Further information

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
AR OEL : Argentina. Occupational Exposure Limits

ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
AR OEL / CMP : TLV (Threshold Limit Value)
AR OEL / CMP - CPT : STEL (Short Term Limit Value)

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 28.09.2024
7.0	14.04.2025	657117-00022	Date of first issue: 02.05.2016

Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AR / Z8