

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0 Revision Date: 13.12.2025 SDS Number: 2972623-00021 Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

SECTION 1. IDENTIFICATION

Product name : Deltamethrin (with Xylene) Formulation

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc
Address : 126 E. Lincoln Avenue
Rahway, New Jersey U.S.A. 07065
Telephone : 908-740-4000
Emergency telephone : 1-908-423-6000
E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Flammable liquids : Category 3
Acute toxicity (Oral) : Category 4
Acute toxicity (Inhalation) : Category 4
Skin irritation : Category 2
Eye irritation : Category 2A
Skin sensitization : Category 1
Germ cell mutagenicity : Category 1B
Carcinogenicity : Category 1B
Reproductive toxicity : Category 2
Specific target organ toxicity - single exposure : Category 3
Specific target organ toxicity - repeated exposure (Oral) : Category 1 (Central nervous system, Immune system)
Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Central nervous system)
Specific target organ toxicity - repeated exposure : Category 2 (Auditory system)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version
8.0

Revision Date:
13.12.2025

SDS Number:
2972623-00021

Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

Aspiration hazard : Category 1

Other hazards

Cutaneous sensations may occur, such as burning or stinging on the face and mucosae. However, these sensations cause no lesions and are of a transitory nature (max. 24 hours). Vapors may form explosive mixture with air.

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.
H302 + H332 Harmful if swallowed or if inhaled.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H340 May cause genetic defects.
H350 May cause cancer.
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
H372 Causes damage to organs (Central nervous system, Immune system) through prolonged or repeated exposure if swallowed.
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.
H373 May cause damage to organs (Auditory system) through prolonged or repeated exposure.

Precautionary Statements :

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking.
P233 Keep container tightly closed.
P241 Use explosion-proof electrical, ventilating and lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version
8.0

Revision Date:
13.12.2025

SDS Number:
2972623-00021

Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical attention.

P331 Do NOT induce vomiting.

P333 + P313 If skin irritation or rash occurs: Get medical attention.

P337 + P313 If eye irritation persists: Get medical attention.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Ethylbenzene	100-41-4*	>= 30 - <= 60	TSC
Xylene	1330-20-7*	>= 30 - <= 60	TSC
Deltamethrin (ISO)	52918-63-5*	>= 3 - <= 7	TSC
2,6-Di-tert-butyl-p-cresol	128-37-0*	>= 3 - <= 7	TSC
Solvent naphtha (petroleum), light aromatic	64742-95-6*	>= 0,1 - <= 1	TSC
Methanol	67-56-1*	>= 0,1 - <= 1	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0	Revision Date: 13.12.2025	SDS Number: 2972623-00021	Date of last issue: 06.12.2025 Date of first issue: 02.07.2018
General advice		<ul style="list-style-type: none">: In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.	
If inhaled		<ul style="list-style-type: none">: If inhaled, remove to fresh air.: If not breathing, give artificial respiration.: If breathing is difficult, give oxygen.: Get medical attention.	
In case of skin contact		<ul style="list-style-type: none">: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.: Get medical attention.: Wash clothing before reuse.: Thoroughly clean shoes before reuse.	
In case of eye contact		<ul style="list-style-type: none">: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.: If easy to do, remove contact lens, if worn.: Get medical attention.	
If swallowed		<ul style="list-style-type: none">: If swallowed, DO NOT induce vomiting.: If vomiting occurs have person lean forward.: Call a physician or poison control center immediately.: Rinse mouth thoroughly with water.: Never give anything by mouth to an unconscious person.	
Most important symptoms and effects, both acute and delayed		<ul style="list-style-type: none">: Harmful if swallowed or if inhaled.: May be fatal if swallowed and enters airways.: Causes skin irritation.: May cause an allergic skin reaction.: Causes serious eye irritation.: May cause respiratory irritation.: May cause genetic defects.: May cause cancer.: Suspected of damaging fertility. Suspected of damaging the unborn child.: Causes damage to organs through prolonged or repeated exposure if swallowed.: Causes damage to organs through prolonged or repeated exposure if inhaled.: May cause damage to organs through prolonged or repeated exposure.: This product contains a pyrethroid.: Pyrethroid poisoning should not be confused with carbamate or organophosphate poisoning.: No information available.	
Protection of first-aiders		<ul style="list-style-type: none">: First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).	
Notes to physician		<ul style="list-style-type: none">: Treat symptomatically and supportively.	

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	<ul style="list-style-type: none">: Water spray: Alcohol-resistant foam: Carbon dioxide (CO₂): Dry chemical
------------------------------	---

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0 Revision Date: 13.12.2025 SDS Number: 2972623-00021 Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NOx)
Bromine compounds

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0	Revision Date: 13.12.2025	SDS Number: 2972623-00021	Date of last issue: 06.12.2025 Date of first issue: 02.07.2018
----------------	------------------------------	------------------------------	---

determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Advice on safe handling : Do not get on skin or clothing.
Do not breathe mist or vapors.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Already sensitized individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives
Gases
Very acutely toxic substances and mixtures

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0 Revision Date: 13.12.2025 SDS Number: 2972623-00021 Date of last issue: 06.12.2025 Date of first issue: 02.07.2018

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m ³	NIOSH REL
		ST	125 ppm 545 mg/m ³	NIOSH REL
		TWA	100 ppm 435 mg/m ³	OSHA Z-1
Xylene	1330-20-7	TWA	100 ppm 435 mg/m ³	OSHA Z-1
		TWA	20 ppm	ACGIH
Deltamethrin (ISO)	52918-63-5	TWA	15 µg/m ³ (OEB 3)	Internal
			Further information: DSEN, Skin	
		Wipe limit	100 µg/100 cm ²	Internal
2,6-Di-tert-butyl-p-cresol	128-37-0	TWA (Inhalable fraction and vapor)	2 mg/m ³	ACGIH
		TWA	10 mg/m ³	NIOSH REL
	64742-95-6	TWA	500 ppm 2.000 mg/m ³	OSHA Z-1
		STEL	250 ppm	ACGIH
Methanol	67-56-1	TWA	250 ppm 325 mg/m ³	NIOSH REL
		ST	200 ppm 260 mg/m ³	NIOSH REL
		TWA	200 ppm 260 mg/m ³	NIOSH REL
		TWA	200 ppm 260 mg/m ³	OSHA Z-1

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	150 mg/g creatinine	ACGIH BEI
Xylene	1330-20-7	Methylhippuric acids	Urine	End of shift (As soon as possible after exposure)	0.3 g/g creatinine	ACGIH BEI

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version
8.0

Revision Date:
13.12.2025

SDS Number:
2972623-00021

Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI
----------	---------	----------	-------	--	---------	-----------

Engineering measures

- Use appropriate engineering controls and manufacturing technologies to control airborne concentrations (e.g., drip-less quick connections). All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment. Containment technologies suitable for controlling compounds are required to control at source and to prevent migration of the compound to uncontrolled areas (e.g., open-face containment devices). Minimize open handling.
- Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Respiratory protection

- General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material

- Chemical-resistant gloves

Remarks

- Consider double gloving. Take note that the product is flammable, which may impact the selection of hand protection.

Eye protection

- Wear safety glasses with side shields or goggles. If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles. Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or aerosols.

Skin and body protection

- Work uniform or laboratory coat. Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces. Use appropriate degowning techniques to remove potentially

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0 Revision Date: 13.12.2025 SDS Number: 2972623-00021 Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

contaminated clothing.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.
The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : clear
yellow

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : 100 °F / 38 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Not applicable

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0 Revision Date: 13.12.2025 SDS Number: 2972623-00021 Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

Density	: No data available
Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: Not applicable
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, kinematic	: No data available
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: No data available
Particle characteristics	
Particle size	: Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Harmful if swallowed or if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: 978,52 mg/kg
Method: Calculation method

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0 Revision Date: 13.12.2025 SDS Number: 2972623-00021 Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5.000 mg/kg
Method: Calculation method

Components:

Ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3.500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 17,8 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Xylene:

Acute oral toxicity : LD50 (Rat): 3.523 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : LC50 (Rat): 27,571 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 4.200 mg/kg

Deltamethrin (ISO):

Acute oral toxicity : LD50 (Rat): 66,7 mg/kg
LD50 (Rat): 9 - 139 mg/kg
LD50 (Mouse): 19 - 34 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,8 mg/l
Exposure time: 2 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): 2.000 mg/kg
LD50 (Rat): > 800 mg/kg

Acute toxicity (other routes of administration) : LD50 (Rat): 2,5 mg/kg
Application Route: Intravenous
LD50 (Mouse): 10 mg/kg
Application Route: Intraperitoneal

2,6-Di-tert-butyl-p-cresol:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0 Revision Date: 13.12.2025 SDS Number: 2972623-00021 Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

Acute oral toxicity	:	LD50 (Rat): > 6.000 mg/kg Method: OECD Test Guideline 401
Acute dermal toxicity	:	LD50 (Rat): > 2.000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

Solvent naphtha (petroleum), light aromatic:

Acute oral toxicity	:	LD50 (Rat): > 5.000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5,61 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	:	LD50 (Rabbit): > 2.000 mg/kg

Methanol:

Acute oral toxicity	:	Acute toxicity estimate (Humans): 300 mg/kg Method: Expert judgment
Acute inhalation toxicity	:	Acute toxicity estimate: 3 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Expert judgment Remarks: Based on national or regional regulation.
Acute dermal toxicity	:	Acute toxicity estimate: 300 mg/kg Method: Expert judgment Remarks: Based on national or regional regulation.

Skin corrosion/irritation

Causes skin irritation.

Components:

Xylene:

Species	:	Rabbit
Result	:	Skin irritation

Deltamethrin (ISO):

Species	:	Rabbit
Result	:	No skin irritation

2,6-Di-tert-butyl-p-cresol:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation
Remarks	:	Based on data from similar materials

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0 Revision Date: 13.12.2025 SDS Number: 2972623-00021 Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

Solvent naphtha (petroleum), light aromatic:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	Skin irritation

Methanol:

Species	:	Rabbit
Result	:	No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Xylene:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days

Deltamethrin (ISO):

Species	:	Rabbit
Result	:	Moderate eye irritation

2,6-Di-tert-butyl-p-cresol:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

Solvent naphtha (petroleum), light aromatic:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

Methanol:

Species	:	Rabbit
Result	:	No eye irritation

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Xylene:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0 Revision Date: 13.12.2025 SDS Number: 2972623-00021 Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

Species : Mouse
Result : negative

Deltamethrin (ISO):

Test Type : Maximization Test
Routes of exposure : Dermal
Species : Guinea pig
Result : negative

Test Type : Human repeat insult patch test (HRIPT)
Routes of exposure : Dermal
Species : Humans
Result : positive

2,6-Di-tert-butyl-p-cresol:

Test Type : Human repeat insult patch test (HRIPT)
Routes of exposure : Skin contact
Species : Humans
Result : negative

Solvent naphtha (petroleum), light aromatic:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Methanol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Germ cell mutagenicity

May cause genetic defects.

Components:

Ethylbenzene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with
mammalian liver cells in vivo
Species: Mouse

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version
8.0

Revision Date:
13.12.2025

SDS Number:
2972623-00021

Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

Application Route: Inhalation
Method: OECD Test Guideline 486
Result: negative

Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mammalian cells
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Skin contact
Result: negative

Deltamethrin (ISO):

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: DNA Repair
Test system: Escherichia coli
Result: negative

Test Type: Chromosomal aberration
Test system: Chinese hamster ovary cells
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Test system: Chinese hamster lung cells
Concentration: LOAEL: 20 mg/kg
Result: positive

Genotoxicity in vivo : Test Type: Micronucleus test
Species: Mouse
Application Route: Oral
Result: negative

Test Type: dominant lethal test
Species: Mouse
Application Route: Oral
Result: negative

Test Type: sister chromatid exchange assay
Species: Mouse

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0	Revision Date: 13.12.2025	SDS Number: 2972623-00021	Date of last issue: 06.12.2025 Date of first issue: 02.07.2018
----------------	------------------------------	------------------------------	---

Cell type: Bone marrow
Application Route: Oral
Result: negative

2,6-Di-tert-butyl-p-cresol:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
	Test Type: In vitro mammalian cell gene mutation test Result: negative
	Test Type: Chromosome aberration test in vitro Result: negative
Genotoxicity in vivo	: Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Rat Application Route: Ingestion Result: negative

Solvent naphtha (petroleum), light aromatic:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
	Test Type: In vitro mammalian cell gene mutation test Result: positive
Genotoxicity in vivo	: Test Type: Sister chromatid exchange analysis in spermatogonia Species: Mouse Application Route: Intraperitoneal injection Result: positive
Germ cell mutagenicity - Assessment	: Positive result(s) from in vivo heritable germ cell mutagenicity tests in mammals

Methanol:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
	Test Type: In vitro mammalian cell gene mutation test Result: negative
	Test Type: in vitro micronucleus test Result: negative
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version
8.0

Revision Date:
13.12.2025

SDS Number:
2972623-00021

Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

II

Carcinogenicity

May cause cancer.

Components:

Ethylbenzene:

Species	:	Rat
Application Route	:	inhalation (vapor)
Exposure time	:	104 weeks
Result	:	positive
Remarks	:	The mechanism or mode of action may not be relevant in humans.

Xylene:

Species	:	Rat
Application Route	:	Ingestion
Exposure time	:	103 weeks
Result	:	negative

Deltamethrin (ISO):

Species	:	Mouse, male and female
Application Route	:	oral (feed)
Exposure time	:	104 weeks
NOAEL	:	8 mg/kg body weight
LOAEL	:	4 mg/kg body weight
Result	:	positive
Target Organs	:	Lymph nodes

Species	:	Rat, male and female
Application Route	:	oral (feed)
Exposure time	:	2 Years
Result	:	negative

Species	:	Dog, male and female
Application Route	:	oral (feed)
Exposure time	:	2 Years
NOAEL	:	1 mg/kg body weight
Result	:	negative

2,6-Di-tert-butyl-p-cresol:

Species	:	Rat
Application Route	:	Ingestion
Exposure time	:	22 Months
Result	:	negative

Solvent naphtha (petroleum), light aromatic:

Species	:	Mouse
Application Route	:	Skin contact
Exposure time	:	2 Years
Result	:	positive

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0 Revision Date: 13.12.2025 SDS Number: 2972623-00021 Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

Carcinogenicity - Assessment : Sufficient evidence of carcinogenicity in animal experiments

Methanol:

Species : Monkey
Application Route : inhalation (vapor)
Exposure time : 7 Months
Result : negative

IARC Group 2B: Possibly carcinogenic to humans
Ethylbenzene

100-41-4

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging fertility. Suspected of damaging the unborn child.

Components:

Ethylbenzene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 416
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 414
Result: negative

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Deltamethrin (ISO):

Effects on fertility : Test Type: Three-generation reproduction toxicity study
Species: Rat
Application Route: oral (feed)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version
8.0

Revision Date:
13.12.2025

SDS Number:
2972623-00021

Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

Early Embryonic Development: NOAEL: 50 mg/kg body weight

Symptoms: No effects on fertility., Embryo-fetal toxicity.

Remarks: Significant toxicity observed in testing

Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Oral

Early Embryonic Development: LOAEL: 84 - 149 mg/kg body weight

Symptoms: No effects on fertility., Embryo-fetal toxicity.

Test Type: Fertility

Species: Rat, male

Application Route: Oral

Fertility: LOAEL: 1 mg/kg body weight

Symptoms: Effects on fertility.

Target Organs: Testes

Effects on fetal development : Test Type: Development
Species: Mouse
Application Route: oral (gavage)
Developmental Toxicity: LOAEL: 1 mg/kg body weight
Result: Skeletal malformations.
Remarks: Maternal toxicity observed.

Test Type: Development
Species: Rat, female
Developmental Toxicity: NOAEL: 10 mg/kg body weight
Symptoms: No effects on fetal development.

Test Type: Development
Species: Rabbit, female
Application Route: oral (gavage)
Developmental Toxicity: NOAEL: 16 mg/kg body weight
Symptoms: No effects on fetal development.

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

2,6-Di-tert-butyl-p-cresol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Solvent naphtha (petroleum), light aromatic:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0 Revision Date: 13.12.2025 SDS Number: 2972623-00021 Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (vapor)
Result: negative

Methanol:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Monkey
Application Route: inhalation (vapor)
Result: negative

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test
Species: Monkey
Application Route: inhalation (vapor)
Result: negative

STOT-single exposure

May cause respiratory irritation.

Components:

Xylene:

Assessment : May cause respiratory irritation.

Deltamethrin (ISO):

Assessment : May cause respiratory irritation.

Solvent naphtha (petroleum), light aromatic:

Assessment : May cause drowsiness or dizziness.

Methanol:

Target Organs : optic nerve, Central nervous system
Assessment : Causes damage to organs.

STOT-repeated exposure

Causes damage to organs (Central nervous system, Immune system) through prolonged or repeated exposure if swallowed.

Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

May cause damage to organs (Auditory system) through prolonged or repeated exposure.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version
8.0

Revision Date:
13.12.2025

SDS Number:
2972623-00021

Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

Components:

Ethylbenzene:

Routes of exposure	:	inhalation (vapor)
Target Organs	:	Auditory system
Assessment	:	Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Xylene:

Routes of exposure	:	inhalation (vapor)
Target Organs	:	Auditory system
Assessment	:	Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Deltamethrin (ISO):

Routes of exposure	:	Ingestion
Target Organs	:	Central nervous system, Immune system
Assessment	:	Causes damage to organs through prolonged or repeated exposure.

Routes of exposure	:	inhalation (dust/mist/fume)
Target Organs	:	Central nervous system
Assessment	:	Causes damage to organs through prolonged or repeated exposure.

2,6-Di-tert-butyl-p-cresol:

Assessment	:	No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.
------------	---	--

Repeated dose toxicity

Components:

Ethylbenzene:

Species	:	Rat
LOAEL	:	0,868 mg/l
Application Route	:	inhalation (vapor)
Exposure time	:	13 Weeks

Species	:	Rat
NOAEL	:	75 mg/kg
LOAEL	:	250 mg/kg
Application Route	:	Ingestion
Method	:	OECD Test Guideline 408

Xylene:

Species	:	Rat
LOAEL	:	> 0,2 - 1 mg/l
Application Route	:	inhalation (vapor)
Exposure time	:	13 Weeks

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0 Revision Date: 13.12.2025 SDS Number: 2972623-00021 Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

||| Remarks : Based on data from similar materials

||| Species : Rat
LOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Deltamethrin (ISO):

Species	: Rat, male and female
NOAEL	: 1 mg/kg
LOAEL	: 2,5 mg/kg
Application Route	: Oral
Exposure time	: 13 Weeks
Target Organs	: Nervous system
Symptoms	: hyperexcitability
Species	: Rat
LOAEL	: 3 mg/m ³
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 2 wk / 5 d/wk / 6 h/d
Symptoms	: Local irritation, respiratory tract irritation
Species	: Dog
NOAEL	: 0,1 mg/kg
LOAEL	: 1 mg/kg
Application Route	: Oral
Exposure time	: 13 Weeks
Target Organs	: Nervous system
Symptoms	: Dilatation of the pupil, Vomiting, Tremors, Diarrhea, Salivation
Species	: Rat
NOAEL	: 14 mg/kg
LOAEL	: 54 mg/kg
Application Route	: Oral
Exposure time	: 91 d
Target Organs	: Nervous system
Species	: Mouse
LOAEL	: 6 mg/kg
Application Route	: Oral
Exposure time	: 12 Weeks
Target Organs	: Immune system
Symptoms	: immune system effects

2,6-Di-tert-butyl-p-cresol:

||| Species : Rat
NOAEL : 25 mg/kg
Application Route : Ingestion
Exposure time : 22 Months

Solvent naphtha (petroleum), light aromatic:

||| Species : Rat

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0 Revision Date: 13.12.2025 SDS Number: 2972623-00021 Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

LOAEL	:	500 mg/kg
Application Route	:	Ingestion
Exposure time	:	28 Days

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Ethylbenzene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Solvent naphtha (petroleum), light aromatic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure

Components:

Deltamethrin (ISO):

Inhalation	:	Symptoms: respiratory tract irritation, Dizziness, Sweating, Headache, Nausea, Vomiting, anorexia, Fatigue, tingling, Palpitation, Blurred vision, muscle twitching
Skin contact	:	Symptoms: Skin irritation, Erythema, pruritis, Headache, Nausea, Vomiting, Dizziness, tingling, Sweating, muscle twitching, Blurred vision, Fatigue, anorexia, Allergic reactions
Ingestion	:	Symptoms: muscle pain, Small pupils

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Ethylbenzene:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 4,2 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,8 - 2,4 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 3,6 mg/l Exposure time: 96 h

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0	Revision Date: 13.12.2025	SDS Number: 2972623-00021	Date of last issue: 06.12.2025 Date of first issue: 02.07.2018
----------------	------------------------------	------------------------------	---

NOEC (Pseudokirchneriella subcapitata (green algae)): 3,4 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): 0,96 mg/l
Exposure time: 7 d

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 96 mg/l
Exposure time: 24 h

Xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13,5 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): > 0,1 - < 1 mg/l
Exposure time: 35 d
Method: OECD Test Guideline 210
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Deltamethrin (ISO):

Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): 0,00048 mg/l
Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): 0,00039 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Mysidopsis bahia (opossum shrimp)): 0,0037 µg/l
Exposure time: 48 h

EC50 (Daphnia magna (Water flea)): 0,0035 mg/l
Exposure time: 48 h

LC50 (Gammarus fasciatus (freshwater shrimp)): 0,0003 µg/l

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0	Revision Date: 13.12.2025	SDS Number: 2972623-00021	Date of last issue: 06.12.2025 Date of first issue: 02.07.2018
----------------	------------------------------	------------------------------	---

		Exposure time: 96 h
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): > 9,1 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: No toxicity at the limit of solubility.
Toxicity to fish (Chronic toxicity)	:	NOEC (Pimephales promelas (fathead minnow)): 0,000022 mg/l Exposure time: 36 d NOEC (Pimephales promelas (fathead minnow)): 0,000017 mg/l Exposure time: 260 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 0,0041 µg/l Exposure time: 21 d
2,6-Di-tert-butyl-p-cresol:		
Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): > 0,57 mg/l Exposure time: 96 h Method: Directive 67/548/EEC, Annex V, C.1.
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 0,48 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0,24 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 NOEC (Pseudokirchneriella subcapitata (green algae)): 0,24 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	:	NOEC (Oryzias latipes (Japanese medaka)): 0,053 mg/l Exposure time: 30 d Method: OECD Test Guideline 210
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 0,316 mg/l Exposure time: 21 d
Toxicity to microorganisms	:	EC50: > 10.000 mg/l Exposure time: 3 h Method: OECD Test Guideline 209

Solvent naphtha (petroleum), light aromatic:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 8,2 mg/l Exposure time: 96 h
------------------	---	--

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version
8.0

Revision Date:
13.12.2025

SDS Number:
2972623-00021

Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

Test substance: Water Accommodated Fraction

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 4,5 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (microalgae)): 3,1 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (microalgae)): 0,5 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 2,6 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 211

Methanol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 15.400 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10.000 mg/l
Exposure time: 48 h
Method: DIN 38412

Toxicity to algae/aquatic plants : ErC50 (Raphidocelis subcapitata (freshwater green alga)): 22.000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): > 1.000 mg/l
Exposure time: 3 h
Test substance: Neutralized product
Method: OECD Test Guideline 209

Persistence and degradability

Components:

Ethylbenzene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 - 80 %
Exposure time: 28 d

Xylene:

Biodegradability : Result: Readily biodegradable.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version
8.0

Revision Date:
13.12.2025

SDS Number:
2972623-00021

Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Deltamethrin (ISO):

Stability in water : Hydrolysis: 0 %(30 d)

2,6-Di-tert-butyl-p-cresol:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 4,5 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Solvent naphtha (petroleum), light aromatic:

Biodegradability : Result: Inherently biodegradable.
Biodegradation: 94 %
Exposure time: 25 d

Methanol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 95 %
Exposure time: 20 d

Bioaccumulative potential

Components:

Ethylbenzene:

Partition coefficient: n-octanol/water : log Pow: 3,6

Xylene:

Partition coefficient: n-octanol/water : log Pow: 3,16
Remarks: Calculation

Deltamethrin (ISO):

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)
Bioconcentration factor (BCF): 1.800

Partition coefficient: n-octanol/water : log Pow: 4,6

2,6-Di-tert-butyl-p-cresol:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 330 - 1.800

Partition coefficient: n-octanol/water : log Pow: 5,1

Methanol:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0 Revision Date: 13.12.2025 SDS Number: 2972623-00021 Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): < 10

Partition coefficient: n-octanol/water : log Pow: -0,77

Mobility in soil

Components:

Deltamethrin (ISO):

Distribution among environmental compartments : log Koc: 7,2

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1992
Proper shipping name : FLAMMABLE LIQUID, TOXIC, N.O.S.
(Ethylbenzene, Xylene)

Class : 3
Subsidiary risk : 6.1
Packing group : III
Labels : 3 (6.1)
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1992
Proper shipping name : Flammable liquid, toxic, n.o.s.
(Ethylbenzene, Xylene)

Class : 3
Subsidiary risk : 6.1
Packing group : III
Labels : Flammable Liquids, Toxic
Packing instruction (cargo aircraft) : 366

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0 Revision Date: 13.12.2025 SDS Number: 2972623-00021 Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1992
Proper shipping name : FLAMMABLE LIQUID, TOXIC, N.O.S.
(Ethylbenzene, Xylene, Deltamethrin (ISO))
Class : 3
Subsidiary risk : 6.1
Packing group : III
Labels : 3 (6.1)
EmS Code : F-E, S-D
Marine pollutant : yes

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1992
Proper shipping name : Flammable liquids, toxic, n.o.s.
(Ethylbenzene, Xylene)
Class : 3
Subsidiary risk : 6.1
Packing group : III
Labels : FLAMMABLE LIQUID, TOXIC
ERG Code : 131
Marine pollutant : yes(Deltamethrin (ISO))

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	271
Ethylbenzene	100-41-4	1000	2583

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Acute toxicity (any route of exposure)
Respiratory or skin sensitization
Germ cell mutagenicity
Carcinogenicity

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version 8.0 Revision Date: 13.12.2025 SDS Number: 2972623-00021 Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Ethylbenzene	100-41-4	>= 30 - < 50 %
Xylene	1330-20-7	>= 30 - < 50 %
4-Nonylphenol, branched, ethoxylated	127087-87-0	>= 10 - < 20 %

US State Regulations

Pennsylvania Right To Know

Ethylbenzene	100-41-4
Xylene	1330-20-7
4-Nonylphenol, branched, ethoxylated	127087-87-0
Deltamethrin (ISO)	52918-63-5
2,6-Di-tert-butyl-p-cresol	128-37-0
Methanol	67-56-1
Acetic acid	64-19-7

California Prop. 65

WARNING: This product can expose you to chemicals including Ethylbenzene, which is/are known to the State of California to cause cancer, and Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Ethylbenzene	100-41-4
Xylene	1330-20-7
2,6-Di-tert-butyl-p-cresol	128-37-0

California Permissible Exposure Limits for Chemical Contaminants

Ethylbenzene	100-41-4
Xylene	1330-20-7
2,6-Di-tert-butyl-p-cresol	128-37-0

The ingredients of this product are reported in the following inventories:

AICS	: not determined
CA. DSL	: not determined
IECSC	: not determined

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version
8.0

Revision Date:
13.12.2025


SDS Number:
2972623-00021

Date of last issue: 06.12.2025
Date of first issue: 02.07.2018

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemi-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Deltamethrin (with Xylene) Formulation

Version Revision Date: SDS Number: Date of last issue: 06.12.2025
8.0 13.12.2025 2972623-00021 Date of first issue: 02.07.2018

cals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 13.12.2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8