

Bismuth Subnitrate (with Mineral Oil) Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 06.12.2023
3.0	14.04.2025	5060463-00012	Date of first issue: 17.10.2019

SECTION 1. IDENTIFICATION

Product name : Bismuth Subnitrate (with Mineral Oil) Formulation

Other means of identification : Shutout (A011866)
CEPRALOCK (89964)

Manufacturer or supplier's details

Company : MSD

Address : Talcahuano 750, 6th floor, Ciudad Autonoma
Buenos Aires, Argentina C1013AAP

Telephone : 908-740-4000

Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@msd.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Specific target organ toxicity - repeated exposure : Category 1 (Central nervous system)

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
Response:
P314 Get medical advice/ attention if you feel unwell.

**Bismuth Subnitrate (with Mineral Oil) Formula-
tion**

Version 3.0 Revision Date: 14.04.2025 SDS Number: 5060463-00012 Date of last issue: 06.12.2023
Date of first issue: 17.10.2019

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Bismuth hydroxide nitrate oxide	1304-85-4	>= 50 -< 70
White mineral oil (petroleum)	8042-47-5	>= 20 -< 30
Fatty acids, C14-26, aluminum salts	97404-28-9	>= 1 -< 5

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.

**Bismuth Subnitrate (with Mineral Oil) Formula-
tion**

Version	Revision Date:	SDS Number:	Date of last issue: 06.12.2023
3.0	14.04.2025	5060463-00012	Date of first issue: 17.10.2019

- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Nitrogen oxides (NO_x)
Metal oxides
Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not swallow.
Avoid contact with eyes.
Avoid prolonged or repeated contact with skin.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Do not eat, drink or smoke when using this product.

Bismuth Subnitrate (with Mineral Oil) Formula- tion

Version 3.0 Revision Date: 14.04.2025 SDS Number: 5060463-00012 Date of last issue: 06.12.2023
Date of first issue: 17.10.2019

- || Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Explosives
Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	CMP (Mist)	5 mg/m ³	AR OEL
		CMP - CPT (Mist)	10 mg/m ³	AR OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Fatty acids, C14-26, aluminum salts	97404-28-9	TWA (Respirable particulate matter)	1 mg/m ³ (Aluminum)	ACGIH

- Engineering measures** : Use feasible engineering controls to minimize exposure to compound.
All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment.

Personal protective equipment

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Combined particulates and organic vapor type
- Hand protection : Chemical-resistant gloves
- Eye protection : Wear safety glasses with side shields or goggles.
If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles.
Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or aerosols.
- Skin and body protection : Work uniform or laboratory coat.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the

**Bismuth Subnitrate (with Mineral Oil) Formula-
tion**

Version 3.0	Revision Date: 14.04.2025	SDS Number: 5060463-00012	Date of last issue: 06.12.2023 Date of first issue: 17.10.2019
----------------	------------------------------	------------------------------	---

working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: ointment
Color	: White to light yellow
Odor	: No data available
Odor Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: No data available
Evaporation rate	: Not applicable
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: Not applicable
Relative vapor density	: Not applicable
Relative density	: No data available
Density	: No data available
Solubility(ies) Water solubility	: No data available
Partition coefficient: n-octanol/water	: Not applicable
Autoignition temperature	: No data available
Decomposition temperature	: No data available

**Bismuth Subnitrate (with Mineral Oil) Formula-
tion**

Version	Revision Date:	SDS Number:	Date of last issue: 06.12.2023
3.0	14.04.2025	5060463-00012	Date of first issue: 17.10.2019

Viscosity		
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available
Particle characteristics		
Particle size	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	None known.
Conditions to avoid	:	None known.
Incompatible materials	:	None.
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	:	Skin contact Ingestion Eye contact
--	---	--

Acute toxicity

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Acute oral toxicity	:	LD50 (Rat): > 2.000 mg/kg Method: OECD Test Guideline 423 Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 5,07 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 436 Remarks: Based on data from similar materials

White mineral oil (petroleum):

Acute oral toxicity	:	LD50 (Rat): > 5.000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l Exposure time: 4 h

**Bismuth Subnitrate (with Mineral Oil) Formula-
tion**

Version	Revision Date:	SDS Number:	Date of last issue: 06.12.2023
3.0	14.04.2025	5060463-00012	Date of first issue: 17.10.2019

	Test atmosphere: dust/mist
	Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	: LD50 (Rabbit): > 2.000 mg/kg
	Assessment: The substance or mixture has no acute dermal toxicity

Fatty acids, C14-26, aluminum salts:

Acute oral toxicity	: LD50 (Rat, female): > 2.000 mg/kg
	Method: OECD Test Guideline 423
	Remarks: Based on data from similar materials
Acute inhalation toxicity	: LC50 (Rat): > 5,15 mg/l
	Exposure time: 4 h
	Test atmosphere: dust/mist
	Method: OECD Test Guideline 403
	Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Species	: reconstructed human epidermis (RhE)
Method	: OECD Test Guideline 439

Result	: No skin irritation
--------	----------------------

White mineral oil (petroleum):

Species	: Rabbit
Result	: No skin irritation

Fatty acids, C14-26, aluminum salts:

Species	: reconstructed human epidermis (RhE)
Method	: OECD Test Guideline 431
Remarks	: Based on data from similar materials

Species	: reconstructed human epidermis (RhE)
Method	: OECD Test Guideline 439
Remarks	: Based on data from similar materials

Result	: No skin irritation
--------	----------------------

Serious eye damage/eye irritation

Not classified based on available information.

**Bismuth Subnitrate (with Mineral Oil) Formula-
tion**

Version	Revision Date:	SDS Number:	Date of last issue: 06.12.2023
3.0	14.04.2025	5060463-00012	Date of first issue: 17.10.2019

Components:**Bismuth hydroxide nitrate oxide:**

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

White mineral oil (petroleum):

Species	:	Rabbit
Result	:	No eye irritation

Fatty acids, C14-26, aluminum salts:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	negative

White mineral oil (petroleum):

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative

Fatty acids, C14-26, aluminum salts:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	negative
Remarks	:	Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

**Bismuth Subnitrate (with Mineral Oil) Formula-
tion**

Version	Revision Date:	SDS Number:	Date of last issue: 06.12.2023
3.0	14.04.2025	5060463-00012	Date of first issue: 17.10.2019

Components:**Bismuth hydroxide nitrate oxide:**

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative Remarks: Based on data from similar materials Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
-----------------------	---	--

White mineral oil (petroleum):

Genotoxicity in vitro	:	Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials

Fatty acids, C14-26, aluminum salts:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative Remarks: Based on data from similar materials Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative Remarks: Based on data from similar materials
-----------------------	---	---

Carcinogenicity

Not classified based on available information.

Components:**White mineral oil (petroleum):**

Species	:	Rat
Application Route	:	Ingestion
Exposure time	:	24 Months
Result	:	negative

Reproductive toxicity

Not classified based on available information.

**Bismuth Subnitrate (with Mineral Oil) Formula-
tion**

Version	Revision Date:	SDS Number:	Date of last issue: 06.12.2023
3.0	14.04.2025	5060463-00012	Date of first issue: 17.10.2019

Components:**Bismuth hydroxide nitrate oxide:**

Effects on fertility	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Result: negative
Effects on fetal development	:	Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Method: OECD Test Guideline 414 Result: negative

White mineral oil (petroleum):

Effects on fertility	:	Test Type: One-generation reproduction toxicity study Species: Rat Application Route: Skin contact Result: negative
Effects on fetal development	:	Test Type: Embryo-fetal development Species: Rat Application Route: Ingestion Result: negative

Fatty acids, C14-26, aluminum salts:

Effects on fertility	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 422 Result: negative Remarks: Based on data from similar materials
Effects on fetal development	:	Test Type: Reproduction/Developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 414 Result: negative Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

**Bismuth Subnitrate (with Mineral Oil) Formula-
tion**

Version	Revision Date:	SDS Number:	Date of last issue: 06.12.2023
3.0	14.04.2025	5060463-00012	Date of first issue: 17.10.2019

Components:**Bismuth hydroxide nitrate oxide:**

Target Organs	: Central nervous system
Assessment	: Causes damage to organs through prolonged or repeated exposure.

Repeated dose toxicity**Components:****White mineral oil (petroleum):**

Species	: Rat
LOAEL	: 160 mg/kg
Application Route	: Ingestion
Exposure time	: 90 Days

Species	: Rat
LOAEL	: ≥ 1 mg/l
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 4 Weeks
Method	: OECD Test Guideline 412

Fatty acids, C14-26, aluminum salts:

Species	: Rat
	: ≥ 1000 mg/kg
Application Route	: Ingestion
Exposure time	: 42 Days
Remarks	: Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Experience with human exposure**Components:****Bismuth hydroxide nitrate oxide:**

Ingestion	: Target Organs: Blood Symptoms: Methaemoglobinemia Target Organs: Central nervous system Symptoms: Neurological disorders
-----------	---

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Bismuth hydroxide nitrate oxide:**

Toxicity to fish	: LL50 (Danio rerio (zebra fish)): > 137 mg/l Exposure time: 96 h
------------------	--

**Bismuth Subnitrate (with Mineral Oil) Formula-
tion**

Version	Revision Date:	SDS Number:	Date of last issue: 06.12.2023
3.0	14.04.2025	5060463-00012	Date of first issue: 17.10.2019

	Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 137 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: EL50 (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201
	NOELR (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201

White mineral oil (petroleum):

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOEC (Oncorhynchus mykiss (rainbow trout)): 1.000 mg/l Exposure time: 28 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 1.000 mg/l Exposure time: 21 d

Persistence and degradability**Components:****White mineral oil (petroleum):**

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 31 % Exposure time: 28 d
------------------	---

Fatty acids, C14-26, aluminum salts:

Biodegradability	: Result: Readily biodegradable. Biodegradation: 81,2 %
------------------	--

**Bismuth Subnitrate (with Mineral Oil) Formula-
tion**

Version 3.0	Revision Date: 14.04.2025	SDS Number: 5060463-00012	Date of last issue: 06.12.2023 Date of first issue: 17.10.2019
----------------	------------------------------	------------------------------	---

Exposure time: 28 d
Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

Bioaccumulative potential**Components:****Fatty acids, C14-26, aluminum salts:**

Partition coefficient: n-
octanol/water : log Pow: > 7
Remarks: Calculation

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.
Contaminated packaging : Empty containers should be taken to an approved waste
handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Argentina. Carcinogenic Substances and Agents : Not applicable
Registry.

**Bismuth Subnitrate (with Mineral Oil) Formula-
tion**

Version	Revision Date:	SDS Number:	Date of last issue: 06.12.2023
3.0	14.04.2025	5060463-00012	Date of first issue: 17.10.2019

Control of precursors and essential chemicals for the : Not applicable
preparation of drugs.

The ingredients of this product are reported in the following inventories:

AICS : not determined

DSL : not determined

IECSC : not determined

SECTION 16. OTHER INFORMATION

Revision Date : 14.04.2025
Date format : dd.mm.yyyy

Further information

Sources of key data used to : Internal technical data, data from raw material SDSs, OECD
compile the Material Safety eChem Portal search results and European Chemicals Agen-
Data Sheet cy, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
AR OEL : Argentina. Occupational Exposure Limits

ACGIH / TWA : 8-hour, time-weighted average
AR OEL / CMP : TLV (Threshold Limit Value)
AR OEL / CMP - CPT : STEL (Short Term Limit Value)

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Develop-

**Bismuth Subnitrate (with Mineral Oil) Formula-
tion**

Version	Revision Date:	SDS Number:	Date of last issue: 06.12.2023
3.0	14.04.2025	5060463-00012	Date of first issue: 17.10.2019

ment; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AR / Z8