

SAFETY DATA SHEET



Bismuth Subnitrate (with Mineral Oil) Formulation

Version
3.0

Revision Date:
14.04.2025

SDS Number:
5060469-00011

Date of last issue: 06.12.2023
Date of first issue: 17.10.2019

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Bismuth Subnitrate (with Mineral Oil) Formulation
Other means of identification : Shutout (A011866)
CEPRALOCK (89964)

Manufacturer or supplier's details

Company name of supplier : MSD
Address : 126 E. Lincoln Avenue
Rahway, New Jersey U.S.A. 07065
Telephone : 908-740-4000
Emergency telephone : 1-908-423-6000
E-mail address : EHSDATASTEWARD@msd.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Specific target organ toxicity : Category 1 (Central nervous system)
- repeated exposure

GHS label elements

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
Response:
P314 Get medical advice/ attention if you feel unwell.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Bismuth Subnitrate (with Mineral Oil) Formula-tionVersion
3.0Revision Date:
14.04.2025SDS Number:
5060469-00011Date of last issue: 06.12.2023
Date of first issue: 17.10.2019

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Bismuth hydroxide nitrate oxide	1304-85-4	>= 50 -< 70
White mineral oil (petroleum)	8042-47-5	>= 20 -< 30
Fatty acids, C14-26, aluminum salts	97404-28-9	>= 1 -< 5

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : Causes damage to organs through prolonged or repeated exposure.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Nitrogen oxides (NO_x)
Metal oxides
Carbon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do

Bismuth Subnitrate (with Mineral Oil) Formula-tionVersion
3.0Revision Date:
14.04.2025SDS Number:
5060469-00011Date of last issue: 06.12.2023
Date of first issue: 17.10.2019

so.
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not swallow. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wash skin thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment. Do not eat, drink or smoke when using this product. Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the

SAFETY DATA SHEET



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version
3.0

Revision Date:
14.04.2025

SDS Number:
5060469-00011

Date of last issue: 06.12.2023
Date of first issue: 17.10.2019

Conditions for safe storage	: Keep in properly labeled containers. Store in accordance with the particular national regulations.
Materials to avoid	: Do not store with the following product types: Self-reactive substances and mixtures Organic peroxides Explosives Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	VLE-PPT (Mist)	5 mg/m ³	NOM-010- STPS-2014
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Fatty acids, C14-26, aluminum salts	97404-28-9	VLE-PPT (Respirable fraction)	1 mg/m ³ (Aluminum)	NOM-010- STPS-2014
		TWA (Respirable particulate matter)	1 mg/m ³ (Aluminum)	ACGIH

Engineering measures : Use feasible engineering controls to minimize exposure to compound.
All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment.

Personal protective equipment

Respiratory protection	: If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Filter type	: Combined particulates and organic vapor type
Hand protection	
Material	: Chemical-resistant gloves
Eye protection	: Wear safety glasses with side shields or goggles. If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles. Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or aerosols.
Skin and body protection	: Work uniform or laboratory coat.

SAFETY DATA SHEET



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version
3.0

Revision Date:
14.04.2025

SDS Number:
5060469-00011

Date of last issue: 06.12.2023
Date of first issue: 17.10.2019

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	ointment
Color	:	White to light yellow
Odor	:	No data available
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	No data available
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Relative density	:	No data available
Density	:	No data available
Solubility(ies)		
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

SAFETY DATA SHEET



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version
3.0

Revision Date:
14.04.2025

SDS Number:
5060469-00011

Date of last issue: 06.12.2023
Date of first issue: 17.10.2019

Molecular weight : No data available

Particle characteristics
Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reac-tions : None known.
Conditions to avoid : None known.
Incompatible materials : None.
Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 423
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.07 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436
Remarks: Based on data from similar materials

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhala-tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal

Bismuth Subnitrate (with Mineral Oil) Formula-tionVersion
3.0Revision Date:
14.04.2025SDS Number:
5060469-00011Date of last issue: 06.12.2023
Date of first issue: 17.10.2019**toxicity****Fatty acids, C14-26, aluminum salts:**

Acute oral toxicity	:	LD50 (Rat, female): > 2,000 mg/kg Method: OECD Test Guideline 423 Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 5.15 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Species	:	reconstructed human epidermis (RhE)
Method	:	OECD Test Guideline 439
Result	:	No skin irritation

White mineral oil (petroleum):

Species	:	Rabbit
Result	:	No skin irritation

Fatty acids, C14-26, aluminum salts:

Species	:	reconstructed human epidermis (RhE)
Method	:	OECD Test Guideline 431
Remarks	:	Based on data from similar materials
Species	:	reconstructed human epidermis (RhE)
Method	:	OECD Test Guideline 439
Remarks	:	Based on data from similar materials
Result	:	No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

SAFETY DATA SHEET



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version
3.0

Revision Date:
14.04.2025

SDS Number:
5060469-00011

Date of last issue: 06.12.2023
Date of first issue: 17.10.2019

White mineral oil (petroleum):

Species	:	Rabbit
Result	:	No eye irritation

Fatty acids, C14-26, aluminum salts:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	negative

White mineral oil (petroleum):

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative

Fatty acids, C14-26, aluminum salts:

Test Type	:	Local lymph node assay (LLNA)
Routes of exposure	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	negative
Remarks	:	Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES)
	:	Result: negative
	:	Remarks: Based on data from similar materials

SAFETY DATA SHEET



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version
3.0

Revision Date:
14.04.2025

SDS Number:
5060469-00011

Date of last issue: 06.12.2023
Date of first issue: 17.10.2019

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

White mineral oil (petroleum):

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Fatty acids, C14-26, aluminum salts:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

Species : Rat
Application Route : Ingestion
Exposure time : 24 Months
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat

SAFETY DATA SHEET



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version
3.0

Revision Date:
14.04.2025

SDS Number:
5060469-00011

Date of last issue: 06.12.2023
Date of first issue: 17.10.2019

Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

White mineral oil (petroleum):

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Skin contact
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Fatty acids, C14-26, aluminum salts:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Components:

Bismuth hydroxide nitrate oxide:

Target Organs
Assessment : Central nervous system
: Causes damage to organs through prolonged or repeated exposure.

SAFETY DATA SHEET



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version
3.0

Revision Date:
14.04.2025

SDS Number:
5060469-00011

Date of last issue: 06.12.2023
Date of first issue: 17.10.2019

Repeated dose toxicity

Components:

White mineral oil (petroleum):

Species	:	Rat
LOAEL	:	160 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days
Species	:	Rat
LOAEL	:	>= 1 mg/l
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	4 Weeks
Method	:	OECD Test Guideline 412

Fatty acids, C14-26, aluminum salts:

Species	:	Rat
	:	>= 1000 mg/kg
Application Route	:	Ingestion
Exposure time	:	42 Days
Remarks	:	Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

Bismuth hydroxide nitrate oxide:

Ingestion	:	Target Organs: Blood Symptoms: Methaemoglobinemia Target Organs: Central nervous system Symptoms: Neurological disorders
-----------	---	-----------------------------------------------------------------------------------------------------------------------------------

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Bismuth hydroxide nitrate oxide:

Toxicity to fish	:	LL50 (Danio rerio (zebra fish)): > 137 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 137 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202

Bismuth Subnitrate (with Mineral Oil) Formula-tionVersion
3.0Revision Date:
14.04.2025SDS Number:
5060469-00011Date of last issue: 06.12.2023
Date of first issue: 17.10.2019

Toxicity to algae/aquatic plants	: EL50 (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201
	NOELR (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201

White mineral oil (petroleum):

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l Exposure time: 28 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia magna (Water flea)): 1,000 mg/l Exposure time: 21 d

Persistence and degradability**Components:****White mineral oil (petroleum):**

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 31 % Exposure time: 28 d
------------------	-------------------------------------------------------------------------------------

Fatty acids, C14-26, aluminum salts:

Biodegradability	: Result: Readily biodegradable. Biodegradation: 81.2 % Exposure time: 28 d Method: OECD Test Guideline 301B Remarks: Based on data from similar materials
------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SAFETY DATA SHEET



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version
3.0

Revision Date:
14.04.2025

SDS Number:
5060469-00011

Date of last issue: 06.12.2023
Date of first issue: 17.10.2019

Bioaccumulative potential

Components:

Fatty acids, C14-26, aluminum salts:

Partition coefficient: n-octanol/water : log Pow: > 7
Remarks: Calculation

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

NOM-002-SCT

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Federal Law for the control of chemical precursors, : Not applicable
essential chemical products and machinery for
producing capsules, tablets and pills.

SAFETY DATA SHEET



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version
3.0

Revision Date:
14.04.2025

SDS Number:
5060469-00011

Date of last issue: 06.12.2023
Date of first issue: 17.10.2019

The ingredients of this product are reported in the following inventories:

AICS : not determined

DSL : not determined

IECSC : not determined

SECTION 16. OTHER INFORMATION

Revision Date : 14.04.2025
Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NOM-010-STPS-2014 : Mexico. Norm NOM-010-STPS-2014 on Chemicals Polluting the Work Environment - Identification, Assessment and Control - Appendix 1 Occupational Exposure Limits
ACGIH / TWA : 8-hour, time-weighted average
NOM-010-STPS-2014 / VLE- : Time weighted average limit value
PPT

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recom-

SAFETY DATA SHEET



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version
3.0

Revision Date:
14.04.2025

SDS Number:
5060469-00011

Date of last issue: 06.12.2023
Date of first issue: 17.10.2019

mendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumu-lative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

MX / Z8