

# SAFETY DATA SHEET



## Bismuth Subnitrate (with Mineral Oil) Formulation

Version  
3.0

Revision Date:  
14.04.2025

SDS Number:  
5060472-00013

Date of last issue: 06.04.2024  
Date of first issue: 17.10.2019

---

### Section 1: Identification

**Product identifier** : Bismuth Subnitrate (with Mineral Oil) Formulation

**Other means of identification** : Shutout (A011866)  
CEPRALOCK (89964)

#### Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product  
Restrictions on use : Not applicable

#### Manufacturer or supplier's details

Company : MSD

Address : 50 Tuas West Drive  
Singapore - Singapore 638408

Telephone : +1-908-740-4000

Emergency telephone number : 65 6697 2111 (24/7/365)

E-mail address : EHSDATASTEWARD@msd.com

---

### Section 2: Hazard identification

#### Classification of the substance or mixture

Specific target organ toxicity - : Category 1 (Central nervous system)  
repeated exposure

#### GHS Label elements, including precautionary statements

Hazard pictograms :



Signal word : Danger

Hazard statements : H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary statements : **Prevention:**

P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.

**Response:**

**Bismuth Subnitrate (with Mineral Oil) Formula-tion**Version  
3.0Revision Date:  
14.04.2025SDS Number:  
5060472-00013Date of last issue: 06.04.2024  
Date of first issue: 17.10.2019

P314 Get medical advice/ attention if you feel unwell.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards which do not result in classification**

None known.

**Section 3: Composition/information on ingredients**

Substance / Mixture : Mixture

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Bismuth hydroxide nitrate oxide	1304-85-4	>= 50 -< 70
White mineral oil (petroleum)	8042-47-5	>= 20 -< 30
Fatty acids, C14-26, aluminum salts	97404-28-9	>= 1 -< 10

**Section 4: First-aid measures****Description of necessary first-aid measures**

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.  
Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.

**Most important symptoms and effects, both acute and delayed**

Risks : Causes damage to organs through prolonged or repeated exposure.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

**Indication of any immediate medical attention and special treatment needed**

Treatment : Treat symptomatically and supportively.

**Bismuth Subnitrate (with Mineral Oil) Formula-tion**Version  
3.0Revision Date:  
14.04.2025SDS Number:  
5060472-00013Date of last issue: 06.04.2024  
Date of first issue: 17.10.2019**Section 5: Fire-fighting measures****Extinguishing media**

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

**Special hazards arising from the substance or mixture**

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Nitrogen oxides (NO<sub>x</sub>)  
Metal oxides  
Carbon oxides

**Special protective actions for fire-fighters**

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

**Section 6: Accidental release measures****Personal precautions, protective equipment and emergency procedures**

Personal precautions : Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

**Environmental precautions**

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

**Methods and materials for containment and cleaning up**

Methods for cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.

**Bismuth Subnitrate (with Mineral Oil) Formula-tion**Version  
3.0Revision Date:  
14.04.2025SDS Number:  
5060472-00013Date of last issue: 06.04.2024  
Date of first issue: 17.10.2019

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

**Section 7: Handling and storage****Precautions for safe handling**

Technical measures	: See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	: Use only with adequate ventilation.
Advice on safe handling	: Do not swallow. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wash skin thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment Do not eat, drink or smoke when using this product. Take care to prevent spills, waste and minimize release to the environment.
Hygiene measures	: If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

**Conditions for safe storage, including any incompatibilities**

Conditions for safe storage	: Keep in properly labelled containers. Store in accordance with the particular national regulations.
Materials to avoid	: Do not store with the following product types: Strong oxidizing agents

---

**Section 8: Exposure controls/personal protection****Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of	Control parame- ters / Permissible	Basis
------------	---------	------------------------	---------------------------------------	-------

# SAFETY DATA SHEET



## Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version  
3.0

Revision Date:  
14.04.2025

SDS Number:  
5060472-00013

Date of last issue: 06.04.2024  
Date of first issue: 17.10.2019

		exposure)	concentration	
White mineral oil (petroleum)	8042-47-5	PEL (long term) (Mist)	5 mg/m3	SG OEL
		PEL (short term) (Mist)	10 mg/m3	SG OEL
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
Fatty acids, C14-26, aluminum salts	97404-28-9	TWA (Respirable particulate matter)	1 mg/m3 (Aluminium)	ACGIH

### Appropriate engineering control measures

- : Use feasible engineering controls to minimize exposure to compound.  
All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment.

### Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection	: Wear safety glasses with side shields or goggles. If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles. Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or aerosols.
Skin protection	: Work uniform or laboratory coat.
Respiratory protection	: If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Filter type	: Combined particulates and organic vapour type
Hand protection	
Material	: Chemical-resistant gloves

### Section 9: Physical and chemical properties

Appearance	: ointment
Colour	: White to light yellow
Odour	: No data available
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling	: No data available

**Bismuth Subnitrate (with Mineral Oil) Formula-tion**Version  
3.0Revision Date:  
14.04.2025SDS Number:  
5060472-00013Date of last issue: 06.04.2024  
Date of first issue: 17.10.2019

range

Flash point	: No data available
Evaporation rate	: Not applicable
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: Not applicable
Relative vapour density	: Not applicable
Relative density	: No data available
Density	: No data available
Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: Not applicable
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, kinematic	: Not applicable
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: No data available
Particle characteristics	
Particle size	: No data available

**Section 10: Stability and reactivity**

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reac-	: None known.

**Bismuth Subnitrate (with Mineral Oil) Formula-tion**Version  
3.0Revision Date:  
14.04.2025SDS Number:  
5060472-00013Date of last issue: 06.04.2024  
Date of first issue: 17.10.2019

tions

Conditions to avoid : None known.

Incompatible materials : None.

Hazardous decomposition products : No hazardous decomposition products are known.

**Section 11: Toxicological information**Information on likely routes of exposure : Skin contact  
Ingestion  
Eye contact**Acute toxicity**

Not classified based on available information.

**Components:****Bismuth hydroxide nitrate oxide:**Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 423  
Remarks: Based on data from similar materialsAcute inhalation toxicity : LC50 (Rat): > 5.07 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 436  
Remarks: Based on data from similar materials**White mineral oil (petroleum):**

Acute oral toxicity : LD50 (Rat): &gt; 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicityAcute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity**Fatty acids, C14-26, aluminum salts:**Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg  
Method: OECD Test Guideline 423  
Remarks: Based on data from similar materialsAcute inhalation toxicity : LC50 (Rat): > 5.15 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

**Bismuth Subnitrate (with Mineral Oil) Formula-tion**Version  
3.0Revision Date:  
14.04.2025SDS Number:  
5060472-00013Date of last issue: 06.04.2024  
Date of first issue: 17.10.2019

||| Remarks: Based on data from similar materials

**Skin corrosion/irritation**

Not classified based on available information.

**Components:****Bismuth hydroxide nitrate oxide:**

Species	:	reconstructed human epidermis (RhE)
Method	:	OECD Test Guideline 439
Result	:	No skin irritation

**White mineral oil (petroleum):**

Species	:	Rabbit
Result	:	No skin irritation

**Fatty acids, C14-26, aluminum salts:**

Species	:	reconstructed human epidermis (RhE)
Method	:	OECD Test Guideline 431
Remarks	:	Based on data from similar materials
Species	:	reconstructed human epidermis (RhE)
Method	:	OECD Test Guideline 439
Remarks	:	Based on data from similar materials
Result	:	No skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:****Bismuth hydroxide nitrate oxide:**

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

**White mineral oil (petroleum):**

Species	:	Rabbit
Result	:	No eye irritation

**Fatty acids, C14-26, aluminum salts:**

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

**Bismuth Subnitrate (with Mineral Oil) Formula-tion**Version  
3.0Revision Date:  
14.04.2025SDS Number:  
5060472-00013Date of last issue: 06.04.2024  
Date of first issue: 17.10.2019**Respiratory or skin sensitisation****Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:****Bismuth hydroxide nitrate oxide:**

Test Type	:	Local lymph node assay (LLNA)
Exposure routes	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	negative

**White mineral oil (petroleum):**

Test Type	:	Buehler Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Result	:	negative

**Fatty acids, C14-26, aluminum salts:**

Test Type	:	Local lymph node assay (LLNA)
Exposure routes	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	negative
Remarks	:	Based on data from similar materials

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Bismuth hydroxide nitrate oxide:**

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative Remarks: Based on data from similar materials
		Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
		Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative

**Bismuth Subnitrate (with Mineral Oil) Formula-tion**Version  
3.0Revision Date:  
14.04.2025SDS Number:  
5060472-00013Date of last issue: 06.04.2024  
Date of first issue: 17.10.2019

II

**White mineral oil (petroleum):**

Genotoxicity in vitro	:	Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials

**Fatty acids, C14-26, aluminum salts:**

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative Remarks: Based on data from similar materials
		Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative Remarks: Based on data from similar materials

**Carcinogenicity**

Not classified based on available information.

**Components:****White mineral oil (petroleum):**

Species	:	Rat
Application Route	:	Ingestion
Exposure time	:	24 Months
Result	:	negative

**Reproductive toxicity**

Not classified based on available information.

**Components:****Bismuth hydroxide nitrate oxide:**

Effects on fertility	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Result: negative
Effects on foetal development	:	Test Type: Embryo-foetal development Species: Rat

**Bismuth Subnitrate (with Mineral Oil) Formula-tion**Version  
3.0Revision Date:  
14.04.2025SDS Number:  
5060472-00013Date of last issue: 06.04.2024  
Date of first issue: 17.10.2019

Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

**White mineral oil (petroleum):**

Effects on fertility	: Test Type: One-generation reproduction toxicity study Species: Rat Application Route: Skin contact Result: negative
Effects on foetal development	: Test Type: Embryo-foetal development Species: Rat Application Route: Ingestion Result: negative

**Fatty acids, C14-26, aluminum salts:**

Effects on fertility	: Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 422 Result: negative Remarks: Based on data from similar materials
Effects on foetal development	: Test Type: Reproduction/Developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 414 Result: negative Remarks: Based on data from similar materials

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

**Components:****Bismuth hydroxide nitrate oxide:**

Target Organs Assessment	: Central nervous system : Causes damage to organs through prolonged or repeated exposure.
-----------------------------	---

**Bismuth Subnitrate (with Mineral Oil) Formula-tion**Version  
3.0Revision Date:  
14.04.2025SDS Number:  
5060472-00013Date of last issue: 06.04.2024  
Date of first issue: 17.10.2019**Repeated dose toxicity****Components:****White mineral oil (petroleum):**

Species	:	Rat
LOAEL	:	160 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days
Species	:	Rat
LOAEL	:	>= 1 mg/l
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	4 Weeks
Method	:	OECD Test Guideline 412

**Fatty acids, C14-26, aluminum salts:**

Species	:	Rat
	:	>= 1000 mg/kg
Application Route	:	Ingestion
Exposure time	:	42 Days
Remarks	:	Based on data from similar materials

**Aspiration toxicity**

Not classified based on available information.

**Experience with human exposure****Components:****Bismuth hydroxide nitrate oxide:**

Ingestion	:	Target Organs: Blood
	:	Symptoms: Methaemoglobinemia
Application Route	:	Target Organs: Central nervous system
Exposure time	:	Symptoms: Neurological disorders

**Section 12: Ecological information****Toxicity****Components:****Bismuth hydroxide nitrate oxide:**

Toxicity to fish	:	LL50 (Danio rerio (zebra fish)): > 137 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): > 137 mg/l Exposure time: 48 h

**Bismuth Subnitrate (with Mineral Oil) Formula-tion**Version  
3.0Revision Date:  
14.04.2025SDS Number:  
5060472-00013Date of last issue: 06.04.2024  
Date of first issue: 17.10.2019

Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

**White mineral oil (petroleum):**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l  
Exposure time: 28 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1,000 mg/l  
Exposure time: 21 d

**Persistence and degradability****Components:****White mineral oil (petroleum):**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 31 %  
Exposure time: 28 d

**Fatty acids, C14-26, aluminum salts:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 81.2 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

**Bismuth Subnitrate (with Mineral Oil) Formula-tion**Version  
3.0Revision Date:  
14.04.2025SDS Number:  
5060472-00013Date of last issue: 06.04.2024  
Date of first issue: 17.10.2019

||| Remarks: Based on data from similar materials

**Bioaccumulative potential****Components:****Fatty acids, C14-26, aluminum salts:**

||| Partition coefficient: n-octanol/water : log Pow: > 7  
||| Remarks: Calculation

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**Section 13: Disposal considerations****Disposal methods**

Waste from residues : Do not dispose of waste into sewer.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

**Section 14: Transport information****International Regulations****UNRTDG**

UN number : Not applicable  
UN proper shipping name : Not applicable  
Transport hazard class(es) : Not applicable  
Subsidiary risk : Not applicable  
Packing group : Not applicable  
Labels : Not applicable  
Environmentally hazardous : no

**IATA-DGR**

UN/ID No. : Not applicable  
UN proper shipping name : Not applicable  
Transport hazard class(es) : Not applicable  
Subsidiary risk : Not applicable  
Packing group : Not applicable  
Labels : Not applicable  
Packing instruction (cargo aircraft) : Not applicable  
Packing instruction (passenger aircraft) : Not applicable

# SAFETY DATA SHEET



## Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version  
3.0

Revision Date:  
14.04.2025

SDS Number:  
5060472-00013

Date of last issue: 06.04.2024  
Date of first issue: 17.10.2019

---

### IMDG-Code

UN number	:	Not applicable
UN proper shipping name	:	Not applicable
Transport hazard class(es)	:	Not applicable
Subsidiary risk	:	Not applicable
Packing group	:	Not applicable
Labels	:	Not applicable
EmS Code	:	Not applicable
Marine pollutant	:	Not applicable

### Transport in bulk according to IMO instruments

Not applicable for product as supplied.

### Special precautions for user

Not applicable

---

## Section 15: Regulatory information

### Safety, health and environmental regulations specific for the product in question

Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subject to the requirements in the Act/Regulations.

Environmental Protection and Management Act and : Not applicable

Environmental Protection and Management (Hazardous Substances) Regulations

Fire Safety (Petroleum and Flammable Materials) : Not applicable  
Regulations

### The components of this product are reported in the following inventories:

AICS : not determined

DSL : not determined

IECSC : not determined

---

## Section 16: Other information

Revision Date : 14.04.2025

### Further information

Sources of key data used to : Internal technical data, data from raw material SDSs, OECD  
compile the Safety Data eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>  
Sheet

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

### Full text of other abbreviations

**Bismuth Subnitrate (with Mineral Oil) Formula-tion**Version  
3.0Revision Date:  
14.04.2025SDS Number:  
5060472-00013Date of last issue: 06.04.2024  
Date of first issue: 17.10.2019

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
SG OEL	:	Singapore. Workplace Safety and Health (General Provisions) Regulations - First Schedule Permissible Exposure Limits of Toxic Substances.
ACGIH / TWA	:	8-hour, time-weighted average
SG OEL / PEL (long term)	:	Permissible Exposure Level (PEL) Long Term
SG OEL / PEL (short term)	:	Permissible Exposure Level (PEL) Short Term

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

SG / EN