

SAFETY DATA SHEET



MineralFix Formulation

Version 2.0 Revision Date: 14.04.2025 SDS Number: 11504104-00002 Date of last issue: 22.01.2025 Date of first issue: 22.01.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MineralFix Formulation
Product code : ProteAQ MineralFix

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Veterinary product
Recommended restrictions on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : MSD
20 Spartan Road
1619 Spartan, South Africa
Telephone : +27119239300
E-mail address of person responsible for the SDS : EHSDATASTEWARD@msd.com

1.4 Emergency telephone number

+1-908-423-6000

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Serious eye damage, Category 1 H318: Causes serious eye damage.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H318 Causes serious eye damage.

Precautionary statements : **Prevention:**

SAFETY DATA SHEET



MineralFix Formulation

Version
2.0

Revision Date:
14.04.2025

SDS Number:
11504104-00002

Date of last issue: 22.01.2025
Date of first issue: 22.01.2025

P280 Wear eye protection/ face protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

Hazardous components which must be listed on the label:

Calcium chloride

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Contact with dust can cause mechanical irritation or drying of the skin.

May form explosive dust-air mixture during processing, handling or other means.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Calcium chloride	10043-52-4 233-140-8 017-013-00-2	Eye Dam. 1; H318	>= 10 - < 20
Substances with a workplace exposure limit :			
Magnesium chloride	7786-30-3 232-094-6		>= 10 - < 20

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.

MineralFix Formulation

Version 2.0	Revision Date: 14.04.2025	SDS Number: 11504104-00002	Date of last issue: 22.01.2025 Date of first issue: 22.01.2025
----------------	------------------------------	-------------------------------	---

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap.
Get medical attention if symptoms occur.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately.

If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Contact with dust can cause mechanical irritation or drying of the skin.
Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Metal oxides
Chlorine compounds
Sulphur oxides
Silicon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local cir-

MineralFix Formulation

Version 2.0	Revision Date: 14.04.2025	SDS Number: 11504104-00002	Date of last issue: 22.01.2025 Date of first issue: 22.01.2025
----------------	------------------------------	-------------------------------	---

ods	cumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
-----	---

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).
Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Technical measures : Static electricity may accumulate and ignite suspended dust causing an explosion.
Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not breathe dust.
Do not swallow.
Do not get in eyes.
Avoid prolonged or repeated contact with skin.
Handle in accordance with good industrial hygiene and safety

SAFETY DATA SHEET



MineralFix Formulation

Version
2.0

Revision Date:
14.04.2025

SDS Number:
11504104-00002

Date of last issue: 22.01.2025
Date of first issue: 22.01.2025

Hygiene measures

practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Minimize dust generation and accumulation.
Keep container closed when not in use.
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
: If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.
The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Keep tightly closed. Store in accordance with the particular national regulations.
Advice on common storage : Do not store with the following product types:
Strong oxidizing agents

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Magnesium chloride	7786-30-3	TWA	OEB 2 (>= 100 < 1000 µg/m ³)	Internal

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

Substance name	End Use	Exposure routes	Potential health effects	Value
Sodium chloride	Workers	Inhalation	Long-term systemic effects	2068,62 mg/m ³
	Workers	Inhalation	Acute systemic effects	2068,62 mg/m ³
	Workers	Skin contact	Long-term systemic effects	295,52 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	295,52 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	443,28 mg/m ³

SAFETY DATA SHEET



MineralFix Formulation

Version
2.0

Revision Date:
14.04.2025

SDS Number:
11504104-00002

Date of last issue: 22.01.2025
Date of first issue: 22.01.2025

	Consumers	Inhalation	Acute systemic effects	443,28 mg/m3
	Consumers	Skin contact	Long-term systemic effects	126,65 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	126,65 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	126,65 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	126,65 mg/kg bw/day
Potassium chloride	Workers	Inhalation	Long-term systemic effects	1064 mg/m3
	Workers	Inhalation	Acute systemic effects	5320 mg/m3
	Workers	Skin contact	Long-term systemic effects	303 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	910 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	273 mg/m3
	Consumers	Inhalation	Acute systemic effects	1365 mg/m3
	Consumers	Skin contact	Long-term systemic effects	182 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	910 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	91 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	455 mg/kg bw/day
Magnesium sulphate	Workers	Inhalation	Long-term systemic effects	37,6 mg/m3
	Workers	Skin contact	Long-term systemic effects	21,3 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	11,1 mg/m3
	Consumers	Skin contact	Long-term systemic effects	12,8 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	12,8 mg/kg bw/day
Magnesium chloride	Consumers	Ingestion	Long-term systemic effects	7 mg/kg bw/day
Calcium chloride	Workers	Inhalation	Acute local effects	10 mg/m3
	Workers	Inhalation	Long-term local effects	5 mg/m3
	Consumers	Inhalation	Acute local effects	5 mg/m3
	Consumers	Inhalation	Long-term local effects	2,5 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Sodium chloride	Fresh water	5 mg/l
	Sewage treatment plant	500 mg/l
	Soil	4,86 mg/kg dry

MineralFix Formulation

Version 2.0	Revision Date: 14.04.2025	SDS Number: 11504104-00002	Date of last issue: 22.01.2025 Date of first issue: 22.01.2025
----------------	------------------------------	-------------------------------	---

		weight (d.w.)
Potassium chloride	Fresh water	0,1 mg/l
	Marine water	0,1 mg/l
	Intermittent use/release	1 mg/l
	Sewage treatment plant	10 mg/l
Magnesium sulphate	Fresh water	0,68 mg/l
	Freshwater - intermittent	6,8 mg/l
	Marine water	0,068 mg/l
	Sewage treatment plant	10 mg/l
Magnesium chloride	Fresh water	1,6 mg/l
	Freshwater - intermittent	5,48 mg/l
	Marine water	0,16 mg/l
	Sewage treatment plant	42 mg/l
	Fresh water sediment	1050 mg/kg dry weight (d.w.)
	Marine sediment	105 mg/kg dry weight (d.w.)
	Soil	1045 mg/kg dry weight (d.w.)

8.2 Exposure controls**Engineering measures**

All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment.

Containment technologies suitable for controlling compounds are required to control at source and to prevent migration of the compound to uncontrolled areas (e.g., open-face containment devices).

Minimize open handling.

Personal protective equipment

Eye/face protection	: Wear safety glasses with side shields or goggles. If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles. Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or aerosols.
Hand protection	
Material	: Chemical-resistant gloves
Remarks	: Consider double gloving.
Skin and body protection	: Work uniform or laboratory coat. Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces. Use appropriate degowning techniques to remove potentially contaminated clothing.
Respiratory protection	: If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Filter type	: Particulates type (P)

SAFETY DATA SHEET



MineralFix Formulation

Version 2.0 Revision Date: 14.04.2025 SDS Number: 11504104-00002 Date of last issue: 22.01.2025
Date of first issue: 22.01.2025

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	powder
Colour	:	white, beige
Odour	:	No data available
Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	May form explosive dust-air mixture during processing, handling or other means.
Flammability (liquids)	:	Not applicable
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	Not applicable
Relative vapour density	:	Not applicable
Relative density	:	No data available
Density	:	No data available
Solubility(ies)		
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

SAFETY DATA SHEET



MineralFix Formulation

Version 2.0 Revision Date: 14.04.2025 SDS Number: 11504104-00002 Date of last issue: 22.01.2025 Date of first issue: 22.01.2025

Molecular weight : No data available

Particle size : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : May form explosive dust-air mixture during processing, handling or other means.
Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Avoid dust formation.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

||| Not classified based on available information.

Components:

Calcium chloride:

||| Acute oral toxicity : LD50 (Rat): 2.120 mg/kg
Method: OECD Test Guideline 401

||| Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Magnesium chloride:

||| Acute oral toxicity : LD50 (Rat, female): > 2.000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity

MineralFix Formulation

Version 2.0	Revision Date: 14.04.2025	SDS Number: 11504104-00002	Date of last issue: 22.01.2025 Date of first issue: 22.01.2025
----------------	------------------------------	-------------------------------	---

		Remarks: The test was conducted according to guideline Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rat): > 2.000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity Remarks: The test was conducted according to guideline Based on data from similar materials

Skin corrosion/irritation

||| Not classified based on available information.

Components:**Calcium chloride:**

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation

Magnesium chloride:

Species	:	reconstructed human epidermis (RhE)
Method	:	Regulation (EC) No. 440/2008, Annex, B.46
Remarks	:	The test was conducted equivalent or similar to guideline Based on data from similar materials
Result	:	No skin irritation

Serious eye damage/eye irritation

||| Causes serious eye damage.

Components:**Calcium chloride:**

Species	:	Rabbit
Method	:	OECD Test Guideline 405
Result	:	Irreversible effects on the eye

Magnesium chloride:

Species	:	Rabbit
Method	:	OECD Test Guideline 405
Result	:	No eye irritation
Remarks	:	The test was conducted according to guideline Based on data from similar materials

Respiratory or skin sensitisation**Skin sensitisation**

||| Not classified based on available information.

Respiratory sensitisation

||| Not classified based on available information.

SAFETY DATA SHEET



MineralFix Formulation

Version 2.0

Revision Date: 14.04.2025

SDS Number: 11504104-00002

Date of last issue: 22.01.2025
Date of first issue: 22.01.2025

Components:

Magnesium chloride:

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative
Remarks	:	The test was conducted according to guideline Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Calcium chloride:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
		Test Type: Chromosome aberration test in vitro Result: negative
		Test Type: In vitro mammalian cell gene mutation test Result: negative Remarks: Based on data from similar materials

Magnesium chloride:

Genotoxicity in vitro	:	Test Type: In vitro mammalian cell gene mutation test Result: negative
		Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative Remarks: Based on data from similar materials
		Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative Remarks: The test was conducted according to guideline

Carcinogenicity

Not classified based on available information.

Components:

Calcium chloride:

Species	:	Mouse
---------	---	-------

SAFETY DATA SHEET



MineralFix Formulation

Version 2.0 Revision Date: 14.04.2025 SDS Number: 11504104-00002 Date of last issue: 22.01.2025 Date of first issue: 22.01.2025

Application Route	:	Ingestion
Exposure time	:	96 weeks
Result	:	negative
Remarks	:	Based on data from similar materials

Magnesium chloride:

Species	:	Mouse
Application Route	:	Ingestion
Exposure time	:	96 weeks
Method	:	OECD Test Guideline 453
Result	:	negative
Remarks	:	The test was conducted equivalent or similar to guideline Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

Calcium chloride:

Effects on foetal development	:	Test Type: Embryo-foetal development Species: Rat Application Route: Ingestion Result: negative
-------------------------------	---	--

Magnesium chloride:

Effects on fertility	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 422 Result: negative Remarks: The test was conducted according to guideline Based on data from similar materials
----------------------	---	---

Effects on foetal development	:	Test Type: Embryo-foetal development Species: Rat Application Route: Ingestion Method: OECD Test Guideline 414 Result: negative Remarks: The test was conducted equivalent or similar to guideline Based on data from similar materials
-------------------------------	---	---

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

MineralFix FormulationVersion
2.0Revision Date:
14.04.2025SDS Number:
11504104-00002Date of last issue: 22.01.2025
Date of first issue: 22.01.2025**Repeated dose toxicity****Components:****Magnesium chloride:**

Species	:	Rat
NOAEL	:	308 mg/kg
LOAEL	:	1.600 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days
Remarks	:	Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information**12.1 Toxicity****Components:****Calcium chloride:**

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials

Magnesium chloride:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 2.119,3 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 548,4 mg/l Exposure time: 48 h Remarks: No test guideline followed
Toxicity to algae/aquatic plants	:	ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: The test was conducted according to guideline NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

MineralFix Formulation

Version 2.0	Revision Date: 14.04.2025	SDS Number: 11504104-00002	Date of last issue: 22.01.2025 Date of first issue: 22.01.2025
----------------	------------------------------	-------------------------------	---

		Remarks: The test was conducted according to guideline
Toxicity to microorganisms	:	NOEC (activated sludge): > 900 mg/l Exposure time: 3 h Method: OECD Test Guideline 209 Remarks: The test was conducted according to guideline
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	EC10: 321 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects**Product:**

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

MineralFix FormulationVersion
2.0Revision Date:
14.04.2025SDS Number:
11504104-00002Date of last issue: 22.01.2025
Date of first issue: 22.01.2025

SECTION 14: Transport information**14.1 UN number**

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.2 UN proper shipping name

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.4 Packing group

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA (Passenger)	:	Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

MineralFix FormulationVersion
2.0Revision Date:
14.04.2025SDS Number:
11504104-00002Date of last issue: 22.01.2025
Date of first issue: 22.01.2025**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****The components of this product are reported in the following inventories:**

AICS : not determined
DSL : not determined
IECSC : not determined

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H318 : Causes serious eye damage.

Full text of other abbreviations

Eye Dam. : Serious eye damage

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European

SAFETY DATA SHEET



MineralFix Formulation

Version Revision Date: SDS Number: Date of last issue: 22.01.2025
2.0 14.04.2025 11504104-00002 Date of first issue: 22.01.2025

Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Eye Dam. 1 H318

Classification procedure:

Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

ZA/EN