

Bismuth Subnitrate (with Mineral Oil) Formulation

Date of last issue: 04.12.2023 Version Revision Date: SDS Number: 5.1 06.12.2023 5060471-00011 Date of first issue: 17.10.2019

Section 1: Identification

Product name Bismuth Subnitrate (with Mineral Oil) Formulation

Other means of identification Shutout (A011866)

CEPRALOCK (89964)

Manufacturer or supplier's details

MSD Company

Address 33 Whakatiki Street - Private Bag 908

Upper Hutt - New Zealand

Telephone 0800 800 543

Emergency telephone number: 0800 764 766 (0800 POISON) 0800 243 622 (0800

CHEMCALL)

E-mail address EHSDATASTEWARD@msd.com

Recommended use of the chemical and restrictions on use

Recommended use Veterinary product Restrictions on use Not applicable

Section 2: Hazard identification

GHS Classification

repeated exposure

Specific target organ toxicity - : Category 1 (Central nervous system)

GHS label elements

Hazard pictograms

Signal word Danger

H372 Causes damage to organs (Central nervous system) Hazard statements

through prolonged or repeated exposure.

Precautionary statements Prevention:

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.



Bismuth Subnitrate (with Mineral Oil) Formulation

Version Revision Date: SDS Number: Date of last issue: 04.12.2023 5.1 06.12.2023 5060471-00011 Date of first issue: 17.10.2019

Response:

P314 Get medical advice/ attention if you feel unwell.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

Section 3: Composition/information on ingredients

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)	
Bismuth hydroxide nitrate oxide	1304-85-4	>= 50 -< 70	
White mineral oil (petroleum)	8042-47-5	>= 20 -< 30	
Fatty acids, C14-26, aluminum salts	97404-28-9	>= 1 -< 10	

Section 4: First-aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty

of water.

Get medical attention if symptoms occur. Flush eyes with water as a precaution.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur.

Rinse mouth thoroughly with water.

Most important symptoms : Cause

and effects, both acute and

delayed

Causes damage to organs through prolonged or repeated

exposure.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

Section 5: Fire-fighting measures

Suitable extinguishing media : Water spray

Alcohol-resistant foam



Bismuth Subnitrate (with Mineral Oil) Formulation

Version Revision Date: SDS Number: Date of last issue: 04.12.2023 5.1 06.12.2023 5060471-00011 Date of first issue: 17.10.2019

Carbon dioxide (CO2)

Dry chemical None known.

Unsuitable extinguishing

media

Specific hazards during fire-

fighting

ucts

Hazardous combustion prod-

Nitrogen oxides (NOx) Metal oxides

Carbon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

Exposure to combustion products may be a hazard to health.

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO

Evacuate area.

Special protective equipment

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Section 6: Accidental release measures

Personal precautions, protec: : tive equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions Avoid release to the environment.

> Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up Sweep up or vacuum up spillage and collect in suitable con-

tainer for disposal.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

Section 7: Handling and storage

Technical measures See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation Use only with adequate ventilation.

Do not breathe dust, fume, gas, mist, vapours or spray. Advice on safe handling

Do not swallow.

Avoid contact with eyes.

Avoid prolonged or repeated contact with skin.

Wash skin thoroughly after handling.



Bismuth Subnitrate (with Mineral Oil) Formulation

Version Revision Date: SDS Number: Date of last issue: 04.12.2023 5.1 06.12.2023 5060471-00011 Date of first issue: 17.10.2019

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working

place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the

use of administrative controls.

Conditions for safe storage : Keep in properly labelled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Section 8: Exposure controls/personal protection

Components with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	
White mineral oil (petroleum)	8042-47-5	WES-TWA	5 mg/m3	NZ OEL
		(Mist)		
		WES-STEL	10 mg/m3	NZ OEL
		(Mist)		
		TWA (Inhal-	5 mg/m3	ACGIH
		able particu-		
		late matter)		
Fatty acids, C14-26, aluminum	97404-28-9	TWA (Res-	1 mg/m3	ACGIH
salts		pirable par-	(Aluminium)	
		ticulate mat-	,	
		ter)		

Engineering measures : Use feasible engineering controls to minimize exposure to

compound.

All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection.



Bismuth Subnitrate (with Mineral Oil) Formulation

Version Revision Date: SDS Number: Date of last issue: 04.12.2023 5.1 06.12.2023 5060471-00011 Date of first issue: 17.10.2019

Filter type
Hand protection

: Combined particulates and organic vapour type

Material : Chemical-resistant gloves

Eye protection : Wear safety glasses with side shields or goggles.

If the work environment or activity involves dusty conditions,

mists or aerosols, wear the appropriate goggles.

Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or

aerosols.

Skin and body protection : Work uniform or laboratory coat.

Section 9: Physical and chemical properties

Appearance : ointment

Colour : White to light yellow

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : No data available

Evaporation rate : Not applicable

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : Not applicable

Relative vapour density : Not applicable

Relative density : No data available

Density : No data available

Solubility(ies)

Water solubility : No data available



Bismuth Subnitrate (with Mineral Oil) Formulation

Version Revision Date: SDS Number: Date of last issue: 04.12.2023 5.1 06.12.2023 5060471-00011 Date of first issue: 17.10.2019

Partition coefficient: n-

octanol/water

Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : No data available

Section 10: Stability and reactivity

Reactivity : Not classified as a reactivity hazard. Chemical stability : Stable under normal conditions.

Possibility of hazardous reac- :

tions

: None known.

None known.

Conditions to avoid : None Incompatible materials : None.

Hazardous decomposition

products

: No hazardous decomposition products are known.

Section 11: Toxicological information

Exposure routes : Skin contact

Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 423

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.07 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 436



Bismuth Subnitrate (with Mineral Oil) Formulation

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.12.2023

 5.1
 06.12.2023
 5060471-00011
 Date of first issue: 17.10.2019

Remarks: Based on data from similar materials

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Fatty acids, C14-26, aluminum salts:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg

Method: OECD Test Guideline 423

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.15 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 439

Result : No skin irritation

White mineral oil (petroleum):

Species : Rabbit

Result : No skin irritation

Fatty acids, C14-26, aluminum salts:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 431

Remarks : Based on data from similar materials

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 439



Bismuth Subnitrate (with Mineral Oil) Formulation

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.12.2023

 5.1
 06.12.2023
 5060471-00011
 Date of first issue: 17.10.2019

Remarks : Based on data from similar materials

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

White mineral oil (petroleum):

Species : Rabbit

Result : No eye irritation

Fatty acids, C14-26, aluminum salts:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

White mineral oil (petroleum):

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative



Bismuth Subnitrate (with Mineral Oil) Formulation

Version Revision Date: SDS Number: Date of last issue: 04.12.2023 5.1 06.12.2023 5060471-00011 Date of first issue: 17.10.2019

Fatty acids, C14-26, aluminum salts:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Remarks : Based on data from similar materials

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

White mineral oil (petroleum):

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Fatty acids, C14-26, aluminum salts:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative



Bismuth Subnitrate (with Mineral Oil) Formulation

Version Revision Date: SDS Number: Date of last issue: 04.12.2023 5.1 06.12.2023 5060471-00011 Date of first issue: 17.10.2019

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

Species : Rat
Application Route : Ingestion
Exposure time : 24 Months
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

White mineral oil (petroleum):

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: Skin contact

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion

Result: negative

Fatty acids, C14-26, aluminum salts:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative



Bismuth Subnitrate (with Mineral Oil) Formulation

Version Revision Date: SDS Number: Date of last issue: 04.12.2023 5.1 06.12.2023 5060471-00011 Date of first issue: 17.10.2019

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Components:

Bismuth hydroxide nitrate oxide:

Target Organs : Central nervous system

Assessment : Causes damage to organs through prolonged or repeated

exposure.

Repeated dose toxicity

Components:

White mineral oil (petroleum):

Species: RatLOAEL: 160 mg/kgApplication Route: IngestionExposure time: 90 Days

Species : Rat LOAEL : >= 1 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 4 Weeks

Method : OECD Test Guideline 412

Fatty acids, C14-26, aluminum salts:

Species : Rat

: >= 1000 mg/kg

Application Route : Ingestion Exposure time : 42 Days

Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.



Bismuth Subnitrate (with Mineral Oil) Formulation

Version Revision Date: SDS Number: Date of last issue: 04.12.2023 5.1 06.12.2023 5060471-00011 Date of first issue: 17.10.2019

Experience with human exposure

Components:

Bismuth hydroxide nitrate oxide:

Ingestion : Target Organs: Blood

Symptoms: Methaemoglobinemia Target Organs: Central nervous system Symptoms: Neurological disorders

Section 12: Ecological information

Ecotoxicity

Components:

Bismuth hydroxide nitrate oxide:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 137 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 137 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 137

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): >

137 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

White mineral oil (petroleum):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (green algae)): 100

mg/l



Bismuth Subnitrate (with Mineral Oil) Formulation

Date of last issue: 04.12.2023 Version Revision Date: SDS Number: 5.1 06.12.2023 5060471-00011 Date of first issue: 17.10.2019

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l

Exposure time: 28 d

Toxicity to daphnia and other : aquatic invertebrates (Chron-

NOEC (Daphnia magna (Water flea)): 1,000 mg/l Exposure time: 21 d

ic toxicity)

Persistence and degradability

Components:

White mineral oil (petroleum):

Biodegradability Result: Not readily biodegradable.

Biodegradation: 31 % Exposure time: 28 d

Fatty acids, C14-26, aluminum salts:

Biodegradability Result: Readily biodegradable.

> Biodegradation: 81.2 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

Fatty acids, C14-26, aluminum salts:

Partition coefficient: nlog Pow: > 7

octanol/water Remarks: Calculation

Mobility in soil

No data available

Other adverse effects

No data available

Section 13: Disposal considerations

Disposal methods

Waste from residues Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Empty containers should be taken to an approved waste han-Contaminated packaging

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.



Bismuth Subnitrate (with Mineral Oil) Formulation

Version Revision Date: SDS Number: Date of last issue: 04.12.2023 5.1 06.12.2023 5060471-00011 Date of first issue: 17.10.2019

Section 14: Transport information

International Regulations

UNRTDG

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo : Not applicable

aircraft)

Packing instruction (passen- : Not applicable

ger aircraft)

IMDG-Code

UN number Not applicable Proper shipping name Not applicable Class Not applicable Subsidiary risk Not applicable Packing group Not applicable Labels Not applicable Not applicable **EmS Code** Not applicable Marine pollutant

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

NZS 5433

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Hazchem Code : Not applicable

Special precautions for user

Not applicable



Bismuth Subnitrate (with Mineral Oil) Formulation

Version Revision Date: SDS Number: Date of last issue: 04.12.2023 06.12.2023 5060471-00011 Date of first issue: 17.10.2019 5.1

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number

HSR100758 Veterinary Medicines Non dispersive Closed System Application Group Standard

HSW Controls

Certified handler certificate not required.

Tracking hazardous substance not required.

Refer to the Health and Safety at Work (Hazardous Substances) Regulations 2017, for further information.

The components of this product are reported in the following inventories:

AICS not determined

DSL not determined

IECSC not determined

Section 16: Other information

Revision Date 06.12.2023

Further information

Sources of key data used to

compile the Safety Data

Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Date format dd.mm.yyyy

Full text of other abbreviations

ACGIH USA. ACGIH Threshold Limit Values (TLV)

NZ OEL New Zealand. Workplace Exposure Standards for Atmospher-

ic Contaminants

ACGIH / TWA 8-hour, time-weighted average

NZ OEL / WES-TWA Workplace Exposure Standard - Time Weighted average NZ OEL / WES-STEL Workplace Exposure Standard - Short-Term Exposure Limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA



Bismuth Subnitrate (with Mineral Oil) Formulation

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 04.12.2023

 5.1
 06.12.2023
 5060471-00011
 Date of first issue: 17.10.2019

- International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

NZ / EN