

Bismuth Subnitrate Formulation

Version 5.6 Revision Date: 30.09.2023 SDS Number: 657117-00020 Date of last issue: 04.04.2023
Date of first issue: 02.05.2016

SECTION 1. IDENTIFICATION

Product name : Bismuth Subnitrate Formulation

Manufacturer or supplier's details

Company : MSD

Address : Talcahuano 750, 6th floor, Ciudad Autonoma
Buenos Aires, Argentina C1013AAP

Telephone : 908-740-4000

Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@msd.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Specific target organ toxicity - repeated exposure : Category 1 (Central nervous system)

Short-term (acute) aquatic hazard : Category 2

Long-term (chronic) aquatic hazard : Category 2

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.

Bismuth Subnitrate Formulation

Version 5.6 Revision Date: 30.09.2023 SDS Number: 657117-00020 Date of last issue: 04.04.2023
Date of first issue: 02.05.2016

P273 Avoid release to the environment.

Response:

P314 Get medical advice/ attention if you feel unwell.

P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Bismuth hydroxide nitrate oxide	1304-85-4	>= 50 -< 70
Petrolatum	8009-03-8	>= 20 -< 30
Zinc oxide	1314-13-2	>= 5 -< 10
Benzyl alcohol	100-51-6	>= 1 -< 5
2,6-Di-tert-butyl-p-cresol	128-37-0	>= 0,1 -< 0,25

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04.04.2023
5.6	30.09.2023	657117-00020	Date of first issue: 02.05.2016

		Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	:	None known.
Specific hazards during fire fighting	:	Exposure to combustion products may be a hazard to health.
Hazardous combustion products	:	Nitrogen oxides (NO _x) Metal oxides Carbon oxides
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
Environmental precautions	:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures	:	See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	:	Use only with adequate ventilation.
Advice on safe handling	:	Do not breathe dust, fume, gas, mist, vapors or spray. Do not swallow. Avoid contact with eyes. Avoid prolonged or repeated contact with skin.

Bismuth Subnitrate Formulation

Version 5.6 Revision Date: 30.09.2023 SDS Number: 657117-00020 Date of last issue: 04.04.2023
 Date of first issue: 02.05.2016

- Wash skin thoroughly after handling.
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
 Do not eat, drink or smoke when using this product.
 Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
 Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
 Strong oxidizing agents
 Self-reactive substances and mixtures
 Organic peroxides
 Explosives
 Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Petrolatum	8009-03-8	CMP (Mist)	5 mg/m ³	AR OEL
		CMP - CPT (Mist)	10 mg/m ³	AR OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Zinc oxide	1314-13-2	CMP (Fumes)	5 mg/m ³	AR OEL
		CMP (Dust)	10 mg/m ³	AR OEL
		CMP - CPT (Fumes)	10 mg/m ³	AR OEL
		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
		STEL (Respirable particulate matter)	10 mg/m ³	ACGIH
2,6-Di-tert-butyl-p-cresol	128-37-0	CMP (Vapour and aerosol, inhalable fraction)	2 mg/m ³	AR OEL
Further information: A4 - Not classifiable as a human carcinogen				
		TWA (Inhalable fraction and vapor)	2 mg/m ³	ACGIH

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04.04.2023
5.6	30.09.2023	657117-00020	Date of first issue: 02.05.2016

- Engineering measures** : Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.
- Personal protective equipment**
- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Combined particulates and organic vapor type
- Hand protection
- Material : Chemical-resistant gloves
- Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
- Eye protection : Wear the following personal protective equipment:
Safety glasses
- Skin and body protection : Skin should be washed after contact.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : paste
- Color : white
- Odor : Petroleum
- Odor Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : No data available
- Flash point : Not applicable
- Evaporation rate : No data available
- Flammability (solid, gas) : Not classified as a flammability hazard
- Flammability (liquids) : No data available
- Upper explosion limit / Upper flammability limit : No data available

Bismuth Subnitrate Formulation

Version 5.6 Revision Date: 30.09.2023 SDS Number: 657117-00020 Date of last issue: 04.04.2023
 Date of first issue: 02.05.2016

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : No data available

Solubility(ies)
 Water solubility : No data available

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity
 Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Skin contact
 Ingestion
 Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5.000 mg/kg
 Method: Calculation method

Bismuth Subnitrate Formulation

Version 5.6 Revision Date: 30.09.2023 SDS Number: 657117-00020 Date of last issue: 04.04.2023
Date of first issue: 02.05.2016

Acute inhalation toxicity : Acute toxicity estimate: > 10 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Components:**Bismuth hydroxide nitrate oxide:**

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 423
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5,07 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436
Remarks: Based on data from similar materials

Petrolatum:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Zinc oxide:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,7 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Benzyl alcohol:

Acute oral toxicity : LD50 (Rat): 1.620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4,178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Bismuth Subnitrate Formulation

Version 5.6 Revision Date: 30.09.2023 SDS Number: 657117-00020 Date of last issue: 04.04.2023
Date of first issue: 02.05.2016

2,6-Di-tert-butyl-p-cresol:

Acute oral toxicity : LD50 (Rat): > 6.000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439

Result : No skin irritation

Petrolatum:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Zinc oxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Benzyl alcohol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

2,6-Di-tert-butyl-p-cresol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Bismuth Subnitrate Formulation

Version 5.6 Revision Date: 30.09.2023 SDS Number: 657117-00020 Date of last issue: 04.04.2023
Date of first issue: 02.05.2016

Petrolatum:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Zinc oxide:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

Benzyl alcohol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

2,6-Di-tert-butyl-p-cresol:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

Petrolatum:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Zinc oxide:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04.04.2023
5.6	30.09.2023	657117-00020	Date of first issue: 02.05.2016

Method : OECD Test Guideline 406
Result : negative

Benzyl alcohol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

2,6-Di-tert-butyl-p-cresol:

Test Type : Human repeat insult patch test (HRIPT)
Routes of exposure : Skin contact
Species : Humans
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Petrolatum:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Zinc oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04.04.2023
5.6	30.09.2023	657117-00020	Date of first issue: 02.05.2016

- Method: OECD Test Guideline 476
Result: equivocal
- Test Type: Chromosome aberration test in vitro
Result: equivocal
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (dust/mist/fume)
Method: OECD Test Guideline 474
Result: negative
- Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: inhalation (dust/mist/fume)
Result: positive
- Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
- Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.
- Benzyl alcohol:**
- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative
- 2,6-Di-tert-butyl-p-cresol:**
- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
- Test Type: In vitro mammalian cell gene mutation test
Result: negative
- Test Type: Chromosome aberration test in vitro
Result: negative
- Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Ingestion
Result: negative

Bismuth Subnitrate Formulation

Version 5.6 Revision Date: 30.09.2023 SDS Number: 657117-00020 Date of last issue: 04.04.2023
Date of first issue: 02.05.2016

Carcinogenicity

Not classified based on available information.

Components:**Petrolatum:**

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Zinc oxide:

Species : Mouse
Application Route : Ingestion
Exposure time : 1 Years
Result : negative
Remarks : Based on data from similar materials

Benzyl alcohol:

Species : Mouse
Application Route : Ingestion
Exposure time : 103 weeks
Method : OECD Test Guideline 451
Result : negative

2,6-Di-tert-butyl-p-cresol:

Species : Rat
Application Route : Ingestion
Exposure time : 22 Months
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Petrolatum:

Bismuth Subnitrate Formulation

Version 5.6 Revision Date: 30.09.2023 SDS Number: 657117-00020 Date of last issue: 04.04.2023
Date of first issue: 02.05.2016

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Skin contact
Result: negative
Remarks: Based on data from similar materials

Zinc oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: inhalation (dust/mist/fume)
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Benzyl alcohol:

Effects on fertility : Test Type: Fertility/early embryonic development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: Ingestion
Result: negative

2,6-Di-tert-butyl-p-cresol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT-single exposure

Not classified based on available information.

Bismuth Subnitrate Formulation

Version 5.6 Revision Date: 30.09.2023 SDS Number: 657117-00020 Date of last issue: 04.04.2023
Date of first issue: 02.05.2016

STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Components:**Bismuth hydroxide nitrate oxide:**

Target Organs : Central nervous system
Assessment : Causes damage to organs through prolonged or repeated exposure.

Zinc oxide:

Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

2,6-Di-tert-butyl-p-cresol:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Repeated dose toxicity**Components:****Petrolatum:**

Species : Rat
NOAEL : 5.000 mg/kg
Application Route : Ingestion
Exposure time : 2 y

Zinc oxide:

Species : Rat, male
NOAEL : 0,0015 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 3 Months
Method : OECD Test Guideline 413

Benzyl alcohol:

Species : Rat
NOAEL : 1,072 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 28 Days
Method : OECD Test Guideline 412

2,6-Di-tert-butyl-p-cresol:

Species : Rat
NOAEL : 25 mg/kg
Application Route : Ingestion
Exposure time : 22 Months

Aspiration toxicity

Not classified based on available information.

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04.04.2023
5.6	30.09.2023	657117-00020	Date of first issue: 02.05.2016

Experience with human exposure

Product:

Ingestion : Symptoms: The absorption of this product into the body may lead to the formation of methaemoglobine that, in sufficient concentration, causes cyanosis., May cause, Neurological disorders, Blood disorders, blood effects, central nervous system effects, Methaemoglobinemia

Components:

Bismuth hydroxide nitrate oxide:

Ingestion : Target Organs: Blood
Symptoms: Methaemoglobinemia
Target Organs: Central nervous system
Symptoms: Neurological disorders

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Bismuth hydroxide nitrate oxide:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 137 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 137 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Petrolatum:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10.000 mg/l
Exposure time: 48 h

Bismuth Subnitrate Formulation

Version 5.6 Revision Date: 30.09.2023 SDS Number: 657117-00020 Date of last issue: 04.04.2023
 Date of first issue: 02.05.2016

Test substance: Water Accommodated Fraction
 Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
 Exposure time: 72 h
 Test substance: Water Accommodated Fraction
 Method: OECD Test Guideline 201
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
 Exposure time: 21 d
 Test substance: Water Accommodated Fraction
 Remarks: Based on data from similar materials

Zinc oxide:

Toxicity to fish : LC50 : > 0,1 - 1 mg/l
 Exposure time: 96 h
 Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0,136 mg/l
 Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (green algae)): > 0,01 - 0,1 mg/l
 Exposure time: 72 h
 Remarks: Based on data from similar materials

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic toxicity) : NOEC (Jordanella floridae (flagfish)): > 0,01 - 0,1 mg/l
 Exposure time: 14 Weeks
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): > 0,01 - 0,1 mg/l
 Exposure time: 7 d
 Remarks: Based on data from similar materials

M-Factor (Chronic aquatic toxicity) : 1

Benzyl alcohol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 460 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 230 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 770 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04.04.2023
5.6	30.09.2023	657117-00020	Date of first issue: 02.05.2016

- NOEC (Pseudokirchneriella subcapitata (green algae)): 310 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 51 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
- 2,6-Di-tert-butyl-p-cresol:**
- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 0,57 mg/l
Exposure time: 96 h
Method: Directive 67/548/EEC, Annex V, C.1.
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,48 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0,24 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOEC (Pseudokirchneriella subcapitata (green algae)): 0,24 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- M-Factor (Acute aquatic toxicity) : 1
- Toxicity to fish (Chronic toxicity) : NOEC (Oryzias latipes (Japanese medaka)): 0,053 mg/l
Exposure time: 30 d
Method: OECD Test Guideline 210
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0,316 mg/l
Exposure time: 21 d
- M-Factor (Chronic aquatic toxicity) : 1
- Toxicity to microorganisms : EC50: > 10.000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Persistence and degradability**Components:****Petrolatum:**

- Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Bismuth Subnitrate Formulation

Version 5.6 Revision Date: 30.09.2023 SDS Number: 657117-00020 Date of last issue: 04.04.2023
Date of first issue: 02.05.2016

Benzyl alcohol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 92 - 96 %
Exposure time: 14 d

2,6-Di-tert-butyl-p-cresol:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 4,5 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Bioaccumulative potential**Components:****Zinc oxide:**

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 78 - 2.060

Benzyl alcohol:

Partition coefficient: n-octanol/water : log Pow: 1,05

2,6-Di-tert-butyl-p-cresol:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 330 - 1.800

Partition coefficient: n-octanol/water : log Pow: 5,1

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04.04.2023
5.6	30.09.2023	657117-00020	Date of first issue: 02.05.2016

(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 956
Packing instruction (passenger aircraft) : 956
Environmentally hazardous : yes

IMDG-Code

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Argentina. Carcinogenic Substances and Agents Registry. : Not applicable

Control of precursors and essential chemicals for the preparation of drugs. : Not applicable

The ingredients of this product are reported in the following inventories:

AICS : not determined

DSL : not determined

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04.04.2023
5.6	30.09.2023	657117-00020	Date of first issue: 02.05.2016

IECSC : not determined

SECTION 16. OTHER INFORMATION

Revision Date : 30.09.2023
Date format : dd.mm.yyyy

Further information

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
AR OEL : Argentina. Occupational Exposure Limits

ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
AR OEL / CMP : TLV (Threshold Limit Value)
AR OEL / CMP - CPT : STEL (Short Term Limit Value)

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04.04.2023
5.6	30.09.2023	657117-00020	Date of first issue: 02.05.2016

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AR / Z8