

## **Bismuth Subnitrate Formulation**

Version **Revision Date:** SDS Number: Date of last issue: 30.09.2023 28.09.2024 657117-00021 Date of first issue: 02.05.2016 6.0

#### **SECTION 1. IDENTIFICATION**

Product name Bismuth Subnitrate Formulation

Manufacturer or supplier's details

Company MSD

Address Talcahuano 750, 6th floor, Ciudad Autonoma

Buenos Aires, Argentina C1013AAP

Telephone 908-740-4000

Emergency telephone 1-908-423-6000

EHSDATASTEWARD@msd.com E-mail address

Recommended use of the chemical and restrictions on use

Recommended use Veterinary product Restrictions on use : Not applicable

#### **SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification** 

Skin sensitization : Category 1

repeated exposure

Specific target organ toxicity - : Category 1 (Central nervous system)

Short-term (acute) aquatic

hazard

Category 2

Long-term (chronic) aquatic

hazard

Category 2

**GHS** label elements

Hazard pictograms







Signal Word Danger

Hazard Statements H317 May cause an allergic skin reaction.

H372 Causes damage to organs (Central nervous system)

through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention:



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 6.0 28.09.2024 657117-00021 Date of first issue: 02.05.2016

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing should not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water. P314 Get medical advice/ attention if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

#### Other hazards which do not result in classification

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Bismuth hydroxide nitrate oxide	1304-85-4	>= 50 -< 70
Petrolatum	8009-03-8	>= 20 -< 30
Zinc oxide	1314-13-2	>= 5 -< 10
Benzyl alcohol	100-51-6	>= 1 -< 5
2,6-Di-tert-butyl-p-cresol	128-37-0	>= 0,1 -< 0,25

#### **SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention.

Wash clothing before reuse.

Thoroughly clean shoes before reuse. Flush eyes with water as a precaution.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur.



## **Bismuth Subnitrate Formulation**

Version **Revision Date:** SDS Number: Date of last issue: 30.09.2023 28.09.2024 657117-00021 Date of first issue: 02.05.2016 6.0

Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delaved

May cause an allergic skin reaction.

Causes damage to organs through prolonged or repeated

exposure.

Protection of first-aiders First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment

when the potential for exposure exists (see section 8).

Treat symptomatically and supportively. Notes to physician

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Nitrogen oxides (NOx)

Metal oxides Carbon oxides

Specific extinguishing meth-

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec: :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions Avoid release to the environment.

> Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 6.0 28.09.2024 657117-00021 Date of first issue: 02.05.2016

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe dust, fume, gas, mist, vapors or spray.

Do not swallow.

Avoid contact with eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Self-reactive substances and mixtures

Organic peroxides

Explosives Gases

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Petrolatum	8009-03-8	CMP (Mist)	5 mg/m³	AR OEL
		CMP - CPT (Mist)	10 mg/m³	AR OEL
		TWA (Inhalable particulate matter)	5 mg/m³	ACGIH
Zinc oxide	1314-13-2	CMP (Fumes)	5 mg/m³	AR OEL
		CMP (Dust)	10 mg/m <sup>3</sup>	AR OEL
		CMP - CPT (Fumes)	10 mg/m³	AR OEL



# **Bismuth Subnitrate Formulation**

Version	Revision Date:	SDS Number:	Date of last issue: 30.09.2023
6.0	28.09.2024	657117-00021	Date of first issue: 02.05.2016

		TWA (Respirable particulate matter)	2 mg/m³	ACGIH		
		STEL (Respirable particulate matter)	10 mg/m³	ACGIH		
2,6-Di-tert-butyl-p-cresol	128-37-0	CMP (Va- pour and aerosol, in- halable frac- tion)	2 mg/m³	AR OEL		
	Further infor	Further information: A4 - Not classifiable as a human carcinogen				
		TWA (Inhalable fraction and vapor)	2 mg/m³	ACGIH		

**Engineering measures** : Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or

exposure assessment demonstrates exposures outside the

recommended guidelines, use respiratory protection.

Filter type

Hand protection

Combined particulates and organic vapor type

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke.

Contaminated work clothing should not be allowed out of the

workplace.

Wash contaminated clothing before re-use.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**



# **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 6.0 28.09.2024 657117-00021 Date of first issue: 02.05.2016

Appearance : paste

Color : white

Odor : Petroleum

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Not classified as a flammability hazard

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : No data available

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

: Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 6.0 28.09.2024 657117-00021 Date of first issue: 02.05.2016

Particle size : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reac- : Can react with strong oxidizing agents.

tions

Conditions to avoid : None known.
Incompatible materials : Oxidizing agents

Hazardous decomposition : No hazardous decomposition products are known.

products

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of : Skin contact

exposure Ingestion
Eye contact

**Acute toxicity** 

Not classified based on available information.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: > 5.000 mg/kg

Method: Calculation method

#### **Components:**

#### Bismuth hydroxide nitrate oxide:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 423

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5,07 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 436

Remarks: Based on data from similar materials

Petrolatum:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Zinc oxide:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg



# **Bismuth Subnitrate Formulation**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.09.2023

 6.0
 28.09.2024
 657117-00021
 Date of first issue: 02.05.2016

Acute inhalation toxicity : LC50 (Rat): > 5,7 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Benzyl alcohol:

Acute oral toxicity : LD50 (Rat): 1.200 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,4 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

2,6-Di-tert-butyl-p-cresol:

Acute oral toxicity : LD50 (Rat): > 6.000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Not classified based on available information.

**Components:** 

Bismuth hydroxide nitrate oxide:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 439

Result : No skin irritation

Petrolatum:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Zinc oxide:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation



# **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 6.0 28.09.2024 657117-00021 Date of first issue: 02.05.2016

Benzyl alcohol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

2,6-Di-tert-butyl-p-cresol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

**Components:** 

Bismuth hydroxide nitrate oxide:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Petrolatum:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Zinc oxide:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Benzyl alcohol:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Method : OECD Test Guideline 405

2,6-Di-tert-butyl-p-cresol:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.



# **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 6.0 28.09.2024 657117-00021 Date of first issue: 02.05.2016

#### Components:

#### Bismuth hydroxide nitrate oxide:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Petrolatum:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Remarks : Based on data from similar materials

Zinc oxide:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Benzyl alcohol:

Test Type : Human repeat insult patch test (HRIPT)

Routes of exposure : Skin contact Species : Humans Result : positive

Assessment : Probability or evidence of low to moderate skin sensitization

rate in humans

2,6-Di-tert-butyl-p-cresol:

Test Type : Human repeat insult patch test (HRIPT)

Routes of exposure : Skin contact Species : Humans Result : negative

## Germ cell mutagenicity

Not classified based on available information.

# **Components:**

## Bismuth hydroxide nitrate oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative



# **Bismuth Subnitrate Formulation**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.09.2023

 6.0
 28.09.2024
 657117-00021
 Date of first issue: 02.05.2016

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Petrolatum:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Zinc oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: equivocal

Test Type: Chromosome aberration test in vitro

Result: equivocal

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (dust/mist/fume)

Method: OECD Test Guideline 474

Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: inhalation (dust/mist/fume)

Result: positive

Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

Benzyl alcohol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 6.0 28.09.2024 657117-00021 Date of first issue: 02.05.2016

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

2,6-Di-tert-butyl-p-cresol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: Ingestion

Result: negative

## Carcinogenicity

Not classified based on available information.

#### **Components:**

#### Petrolatum:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

#### Zinc oxide:

Species : Mouse
Application Route : Ingestion
Exposure time : 1 Years
Result : negative

Remarks : Based on data from similar materials

# Benzyl alcohol:

Species: MouseApplication Route: IngestionExposure time: 103 weeks

Method : OECD Test Guideline 451

Result : negative

#### 2,6-Di-tert-butyl-p-cresol:

Species : Rat Application Route : Ingestion



# **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 6.0 28.09.2024 657117-00021 Date of first issue: 02.05.2016

Exposure time : 22 Months
Result : negative

# Reproductive toxicity

Not classified based on available information.

#### **Components:**

## Bismuth hydroxide nitrate oxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

Petrolatum:

Effects on fertility: Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Skin contact

Result: negative

Remarks: Based on data from similar materials

Zinc oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: inhalation (dust/mist/fume)

Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

Benzyl alcohol:

Effects on fertility : Test Type: Fertility/early embryonic development

Species: Rat



# **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 6.0 28.09.2024 657117-00021 Date of first issue: 02.05.2016

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development: Test Type: Embryo-fetal development

Species: Mouse

**Application Route: Ingestion** 

Result: negative

2,6-Di-tert-butyl-p-cresol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

**Components:** 

Bismuth hydroxide nitrate oxide:

Target Organs : Central nervous system

Assessment : Causes damage to organs through prolonged or repeated

exposure.

Zinc oxide:

Assessment : No significant health effects observed in animals at concentra-

tions of 0.2 mg/l/6h/d or less.

2,6-Di-tert-butyl-p-cresol:

Assessment : No significant health effects observed in animals at concentra-

tions of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

Petrolatum:

Species : Rat

NOAEL : 5.000 mg/kg
Application Route : Ingestion
Exposure time : 2 y

Zinc oxide:



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 28.09.2024 657117-00021 Date of first issue: 02.05.2016 6.0

Rat. male Species NOAEL 0,0015 mg/l

Application Route inhalation (dust/mist/fume)

Exposure time 3 Months

Method **OECD Test Guideline 413** 

Benzyl alcohol:

Species Rat 1,072 mg/l NOAEL

Application Route inhalation (dust/mist/fume)

Exposure time 28 Days

Method **OECD Test Guideline 412** 

2,6-Di-tert-butyl-p-cresol:

Species Rat NOAEL 25 mg/kg Application Route Ingestion Exposure time 22 Months

**Aspiration toxicity** 

Not classified based on available information.

**Experience with human exposure** 

**Product:** 

Ingestion Symptoms: The absorption of this product into the body may

> lead to the formation of methaemoglobine that, in sufficient concentration, causes cyanosis., May cause, Neurological disorders, Blood disorders, blood effects, central nervous sys-

tem effects, Methaemoglobinemia

Components:

Bismuth hydroxide nitrate oxide:

Ingestion Target Organs: Blood

> Symptoms: Methaemoglobinemia Target Organs: Central nervous system Symptoms: Neurological disorders

**SECTION 12. ECOLOGICAL INFORMATION** 

**Ecotoxicity** 

**Components:** 

Bismuth hydroxide nitrate oxide:

LL50 (Danio rerio (zebra fish)): > 137 mg/l Toxicity to fish

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 137 mg/l

Exposure time: 48 h



# **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 6.0 28.09.2024 657117-00021 Date of first issue: 02.05.2016

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 137

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): >

137 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Petrolatum:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

NOEL (Pseudokirchneriella subcapitata (green algae)): >=

100 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 10 mg/l

Exposure time: 21 d

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Zinc oxide:

Toxicity to fish : LC50 : > 0,1 - 1 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): 0,136

mg/l

Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (green algae)): > 0,01

- 0,1 mg/l

Exposure time: 72 h

Remarks: Based on data from similar materials

M-Factor (Acute aquatic tox- : 1



# **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 6.0 28.09.2024 657117-00021 Date of first issue: 02.05.2016

icity)

Toxicity to fish (Chronic tox-

icity)

NOEC (Jordanella floridae (flagfish)): > 0,01 - 0,1 mg/l

Exposure time: 14 Weeks

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Ceriodaphnia dubia (water flea)): > 0,01 - 0,1 mg/l

Exposure time: 7 d

Remarks: Based on data from similar materials

M-Factor (Chronic aquatic

toxicity)

: 1

Benzyl alcohol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 460 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 230 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 770

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 310

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 51 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

2,6-Di-tert-butyl-p-cresol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 0,57 mg/l

Exposure time: 96 h

Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0,48 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0,24

1119/1

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,24

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox-

icity)

17 / 21



# **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 28.09.2024 657117-00021 Date of first issue: 02.05.2016 6.0

Toxicity to fish (Chronic tox-

icity)

NOEC (Oryzias latipes (Japanese medaka)): 0,053 mg/l

Exposure time: 30 d

Method: OECD Test Guideline 210

Toxicity to daphnia and other: aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0,316 mg/l

Exposure time: 21 d

M-Factor (Chronic aquatic

toxicity)

Toxicity to microorganisms

: EC50: > 10.000 mg/l Exposure time: 3 h

Method: OECD Test Guideline 209

#### Persistence and degradability

#### Components:

#### Petrolatum:

Biodegradability Result: Not readily biodegradable.

: 1

Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Benzyl alcohol:

Result: Readily biodegradable. Biodegradability

Biodegradation: 92 - 96 % Exposure time: 14 d

2,6-Di-tert-butyl-p-cresol:

Biodegradability Result: Not readily biodegradable.

> Biodegradation: 4,5 % Exposure time: 28 d

Method: OECD Test Guideline 301C

# **Bioaccumulative potential**

#### Components:

Zinc oxide:

Bioaccumulation Species: Oncorhynchus mykiss (rainbow trout)

Bioconcentration factor (BCF): 78 - 2.060

Benzyl alcohol:

Bioaccumulation

Partition coefficient: n-

log Pow: 1,05

octanol/water

2,6-Di-tert-butyl-p-cresol:

Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): 330 - 1.800

Partition coefficient: nlog Pow: 5,1



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 6.0 28.09.2024 657117-00021 Date of first issue: 02.05.2016

octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS** 

**Disposal methods** 

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

**SECTION 14. TRANSPORT INFORMATION** 

International Regulations

**UNRTDG** 

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

**IATA-DGR** 

UN/ID No. : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo : 956

aircraft)

Packing instruction (passen- :

ger aircraft)

Environmentally hazardous : yes

IMDG-Code

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

956

(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A,

EmS Code : F-A, S-F Marine pollutant : yes



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 6.0 28.09.2024 657117-00021 Date of first issue: 02.05.2016

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

# Safety, health and environmental regulations/legislation specific for the substance or mixture

Argentina. Carcinogenic Substances and Agents :

Registry.

: Not applicable

Not applicable

Control of precursors and essential chemicals for the

preparation of drugs.

The ingredients of this product are reported in the following inventories:

AICS : not determined

DSL : not determined

IECSC : not determined

## **SECTION 16. OTHER INFORMATION**

Revision Date : 28.09.2024 Date format : dd.mm.yyyy

**Further information** 

**Data Sheet** 

Sources of key data used to compile the Material Safety

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
AR OEL : Argentina. Occupational Exposure Limits

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit AR OEL / CMP : TLV (Threshold Limit Value) AR OEL / CMP - CPT : STEL (Short Term Limit Value)

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for



# **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 6.0 28.09.2024 657117-00021 Date of first issue: 02.05.2016

Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AR / Z8