

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version 5.6      Revision Date: 2023/09/30      SDS Number: 656836-00020      Date of last issue: 2023/04/04  
Date of first issue: 2016/05/02

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Bismuth Subnitrate Formulation

#### Manufacturer or supplier's details

Company : MSD

Address : No. 485 Jing Tai Road  
Pu Tuo District - Shanghai - China 200331

Telephone : +1-908-740-4000

Emergency telephone number : 86-571-87268110

E-mail address : EHSDATASTEWARD@msd.com

#### Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product

Restrictions on use : Not applicable

### 2. HAZARDS IDENTIFICATION

#### Emergency Overview

**Appearance** : paste  
**Colour** : white  
**Odour** : Petroleum

Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

#### GHS Classification

Specific target organ toxicity - repeated exposure : Category 1

Short-term (acute) aquatic hazard : Category 2

Long-term (chronic) aquatic hazard : Category 2

#### GHS label elements

Hazard pictograms :



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version 5.6      Revision Date: 2023/09/30      SDS Number: 656836-00020      Date of last issue: 2023/04/04  
Date of first issue: 2016/05/02

Signal word : Danger

Hazard statements : H372 Causes damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P273 Avoid release to the environment.

**Response:**  
P314 Get medical advice/ attention if you feel unwell.  
P391 Collect spillage.

**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

### Physical and chemical hazards

Not classified based on available information.

### Health hazards

Causes damage to organs through prolonged or repeated exposure.

### Environmental hazards

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

### Other hazards which do not result in classification

None known.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Bismuth hydroxide nitrate oxide	1304-85-4	>= 50 -< 70
Petrolatum	8009-03-8	>= 20 -< 30
Zinc oxide	1314-13-2	>= 2.5 -< 10
Benzyl alcohol	100-51-6	>= 1 -< 10
2,6-Di-tert-butyl-p-cresol	128-37-0	>= 0.1 -< 0.25

## 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
5.6	2023/09/30	656836-00020	Date of first issue: 2016/05/02

---

If inhaled	:	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	:	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention if symptoms occur.
In case of eye contact	:	Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed	:	If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	:	Causes damage to organs through prolonged or repeated exposure.
Protection of first-aiders	:	First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
Notes to physician	:	Treat symptomatically and supportively.

---

### 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical
Unsuitable extinguishing media	:	None known.
Specific hazards during fire-fighting	:	Exposure to combustion products may be a hazard to health.
Hazardous combustion products	:	Nitrogen oxides (NO <sub>x</sub> ) Metal oxides Carbon oxides
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

---

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
Environmental precautions	:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version 5.6      Revision Date: 2023/09/30      SDS Number: 656836-00020      Date of last issue: 2023/04/04  
Date of first issue: 2016/05/02

cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 7. HANDLING AND STORAGE

#### Handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.  
Local/Total ventilation : Use only with adequate ventilation.  
Advice on safe handling : Do not breathe dust, fume, gas, mist, vapours or spray.  
Do not swallow.  
Avoid contact with eyes.  
Avoid prolonged or repeated contact with skin.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Do not eat, drink or smoke when using this product.  
Take care to prevent spills, waste and minimize release to the environment.  
Avoidance of contact : Oxidizing agents

#### Storage

Conditions for safe storage : Keep in properly labelled containers.  
Store in accordance with the particular national regulations.  
Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Packaging material : Unsuitable material: None known.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Petrolatum	8009-03-8	TWA (Inhal-	5 mg/m3	ACGIH

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version 5.6      Revision Date: 2023/09/30      SDS Number: 656836-00020      Date of last issue: 2023/04/04  
Date of first issue: 2016/05/02

		able particulate matter)		
Zinc oxide	1314-13-2	PC-TWA	3 mg/m3	CN OEL
		PC-STEL	5 mg/m3	CN OEL
		TWA (Respirable particulate matter)	2 mg/m3	ACGIH
		STEL (Respirable particulate matter)	10 mg/m3	ACGIH
2,6-Di-tert-butyl-p-cresol	128-37-0	TWA (Inhalable fraction and vapor)	2 mg/m3	ACGIH

**Engineering measures** : Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

### Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapour type

Eye/face protection : Wear the following personal protective equipment:  
Safety glasses

Skin and body protection : Skin should be washed after contact.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : white

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
5.6	2023/09/30	656836-00020	Date of first issue: 2016/05/02

---

Odour	:	Petroleum
Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not classified as a flammability hazard
Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	No data available
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	No data available

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
5.6	2023/09/30	656836-00020	Date of first issue: 2016/05/02

### 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Can react with strong oxidizing agents.
Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

### 11. TOXICOLOGICAL INFORMATION

Exposure routes	:	Skin contact Ingestion Eye contact
-----------------	---	--

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
---------------------	---	--

Acute inhalation toxicity	:	Acute toxicity estimate: > 10 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
---------------------------	---	--

#### Components:

##### **Bismuth hydroxide nitrate oxide:**

Acute oral toxicity	:	LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 423 Remarks: Based on data from similar materials
---------------------	---	---

Acute inhalation toxicity	:	LC50 (Rat): > 5.07 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 436 Remarks: Based on data from similar materials
---------------------------	---	---

##### **Petrolatum:**

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401 Remarks: Based on data from similar materials
---------------------	---	---

Acute dermal toxicity	:	LD50 (Rat): > 2,000 mg/kg
-----------------------	---	---------------------------

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
5.6	2023/09/30	656836-00020	Date of first issue: 2016/05/02

---

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal toxicity

Remarks: Based on data from similar materials

### Zinc oxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.7 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

### Benzyl alcohol:

Acute oral toxicity : LD50 (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

### 2,6-Di-tert-butyl-p-cresol:

Acute oral toxicity : LD50 (Rat): > 6,000 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

### Skin corrosion/irritation

Not classified based on available information.

### Components:

#### Bismuth hydroxide nitrate oxide:

Species : reconstructed human epidermis (RhE)  
Method : OECD Test Guideline 439

Result : No skin irritation

#### Petrolatum:



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
5.6	2023/09/30	656836-00020	Date of first issue: 2016/05/02

---

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

### Zinc oxide:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

### Benzyl alcohol:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

### 2,6-Di-tert-butyl-p-cresol:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

### Serious eye damage/eye irritation

Not classified based on available information.

### Components:

#### Bismuth hydroxide nitrate oxide:

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

#### Petrolatum:

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

#### Zinc oxide:

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

#### Benzyl alcohol:

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days  
Method : OECD Test Guideline 405

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
5.6	2023/09/30	656836-00020	Date of first issue: 2016/05/02

---

### 2,6-Di-tert-butyl-p-cresol:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

### Components:

#### Bismuth hydroxide nitrate oxide:

Test Type	:	Local lymph node assay (LLNA)
Exposure routes	:	Skin contact
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	negative

#### Petrolatum:

Test Type	:	Buehler Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Result	:	negative
Remarks	:	Based on data from similar materials

#### Zinc oxide:

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

#### Benzyl alcohol:

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

### 2,6-Di-tert-butyl-p-cresol:

Test Type	:	Human repeat insult patch test (HRIPT)
Exposure routes	:	Skin contact

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
5.6	2023/09/30	656836-00020	Date of first issue: 2016/05/02

---

Species : Humans  
Result : negative

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### **Bismuth hydroxide nitrate oxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

#### **Petrolatum:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

#### **Zinc oxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: equivocal

Test Type: Chromosome aberration test in vitro  
Result: equivocal

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Method: OECD Test Guideline 474

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
5.6	2023/09/30	656836-00020	Date of first issue: 2016/05/02

---

Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: inhalation (dust/mist/fume)

Result: positive

Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)

Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

### **Benzyl alcohol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

### **2,6-Di-tert-butyl-p-cresol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Test Type: Chromosome aberration test in vitro  
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: Ingestion  
Result: negative

### **Carcinogenicity**

Not classified based on available information.

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version 5.6      Revision Date: 2023/09/30      SDS Number: 656836-00020      Date of last issue: 2023/04/04  
Date of first issue: 2016/05/02

---

### Components:

#### **Petrolatum:**

Species : Rat  
Application Route : Ingestion  
Exposure time : 2 Years  
Result : negative

#### **Zinc oxide:**

Species : Mouse  
Application Route : Ingestion  
Exposure time : 1 Years  
Result : negative  
Remarks : Based on data from similar materials

#### **Benzyl alcohol:**

Species : Mouse  
Application Route : Ingestion  
Exposure time : 103 weeks  
Method : OECD Test Guideline 451  
Result : negative

#### **2,6-Di-tert-butyl-p-cresol:**

Species : Rat  
Application Route : Ingestion  
Exposure time : 22 Months  
Result : negative

### **Reproductive toxicity**

Not classified based on available information.

### Components:

#### **Bismuth hydroxide nitrate oxide:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

#### **Petrolatum:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
5.6	2023/09/30	656836-00020	Date of first issue: 2016/05/02

---

test  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Skin contact  
Result: negative  
Remarks: Based on data from similar materials

### Zinc oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Method: OECD Test Guideline 414  
Result: negative  
Remarks: Based on data from similar materials

### Benzyl alcohol:

Effects on fertility : Test Type: Fertility/early embryonic development  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Mouse  
Application Route: Ingestion  
Result: negative

### 2,6-Di-tert-butyl-p-cresol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
5.6	2023/09/30	656836-00020	Date of first issue: 2016/05/02

---

### STOT - single exposure

Not classified based on available information.

### STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

### Components:

#### Bismuth hydroxide nitrate oxide:

Target Organs : Central nervous system  
Assessment : Causes damage to organs through prolonged or repeated exposure.

#### Zinc oxide:

Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

#### 2,6-Di-tert-butyl-p-cresol:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

### Repeated dose toxicity

### Components:

#### Petrolatum:

Species : Rat  
NOAEL : 5,000 mg/kg  
Application Route : Ingestion  
Exposure time : 2 yr

#### Zinc oxide:

Species : Rat, male  
NOAEL : 0.0015 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 3 Months  
Method : OECD Test Guideline 413

#### Benzyl alcohol:

Species : Rat  
NOAEL : 1.072 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 28 Days  
Method : OECD Test Guideline 412

#### 2,6-Di-tert-butyl-p-cresol:

Species : Rat  
NOAEL : 25 mg/kg

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
5.6	2023/09/30	656836-00020	Date of first issue: 2016/05/02

---

Application Route : Ingestion  
Exposure time : 22 Months

### Aspiration toxicity

Not classified based on available information.

### Experience with human exposure

#### Product:

Ingestion : Symptoms: The absorption of this product into the body may lead to the formation of methaemoglobine that, in sufficient concentration, causes cyanosis., May cause, Neurological disorders, Blood disorders, blood effects, central nervous system effects, Methaemoglobinemia

#### Components:

##### **Bismuth hydroxide nitrate oxide:**

Ingestion : Target Organs: Blood  
Symptoms: Methaemoglobinemia  
Target Organs: Central nervous system  
Symptoms: Neurological disorders

---

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### **Bismuth hydroxide nitrate oxide:**

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 137 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 137 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

---



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
5.6	2023/09/30	656836-00020	Date of first issue: 2016/05/02

---

### Petrolatum:

- Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l  
Exposure time: 21 d  
Test substance: Water Accommodated Fraction  
Remarks: Based on data from similar materials

### Zinc oxide:

- Toxicity to fish : LC50 : > 0.1 - 1 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.136 mg/l  
Exposure time: 72 h  
NOEC (Pseudokirchneriella subcapitata (green algae)): > 0.01 - 0.1 mg/l  
Exposure time: 72 h  
Remarks: Based on data from similar materials
- M-Factor (Acute aquatic toxicity) : 1
- Toxicity to fish (Chronic toxicity) : NOEC (Jordanella floridae (flagfish)): > 0.01 - 0.1 mg/l  
Exposure time: 14 Weeks  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): > 0.01 - 0.1 mg/l  
Exposure time: 7 d  
Remarks: Based on data from similar materials
- M-Factor (Chronic aquatic toxicity) : 1

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
5.6	2023/09/30	656836-00020	Date of first issue: 2016/05/02

---

toxicity)

### **Benzyl alcohol:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 460 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 230 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 770 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 310 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 51 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

### **2,6-Di-tert-butyl-p-cresol:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 0.57 mg/l  
Exposure time: 96 h  
Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.48 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0.24 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.24 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic toxicity) : NOEC (Oryzias latipes (Japanese medaka)): 0.053 mg/l  
Exposure time: 30 d  
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic) : NOEC (Daphnia magna (Water flea)): 0.316 mg/l  
Exposure time: 21 d

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
5.6	2023/09/30	656836-00020	Date of first issue: 2016/05/02

---

ic toxicity)  
M-Factor (Chronic aquatic toxicity) : 1  
Toxicity to microorganisms : EC50: > 10,000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

### Persistence and degradability

#### Components:

##### **Petrolatum:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 31 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

##### **Benzyl alcohol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 92 - 96 %  
Exposure time: 14 d

##### **2,6-Di-tert-butyl-p-cresol:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 4.5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301C

### Bioaccumulative potential

#### Components:

##### **Zinc oxide:**

Bioaccumulation : Species: *Oncorhynchus mykiss* (rainbow trout)  
Bioconcentration factor (BCF): 78 - 2,060

##### **Benzyl alcohol:**

Partition coefficient: n-octanol/water : log Pow: 1.05

##### **2,6-Di-tert-butyl-p-cresol:**

Bioaccumulation : Species: *Cyprinus carpio* (Carp)  
Bioconcentration factor (BCF): 330 - 1,800

Partition coefficient: n-octanol/water : log Pow: 5.1

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
5.6	2023/09/30	656836-00020	Date of first issue: 2016/05/02

### Mobility in soil

No data available

### Other adverse effects

No data available

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues	:	Do not dispose of waste into sewer. Dispose of in accordance with local regulations.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

## 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number	:	UN 3077
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc oxide, 2,6-Di-tert-butyl-p-cresol)
Class	:	9
Packing group	:	III
Labels	:	9
Environmentally hazardous	:	yes

#### IATA-DGR

UN/ID No.	:	UN 3077
Proper shipping name	:	Environmentally hazardous substance, solid, n.o.s. (Zinc oxide, 2,6-Di-tert-butyl-p-cresol)
Class	:	9
Packing group	:	III
Labels	:	Miscellaneous
Packing instruction (cargo aircraft)	:	956
Packing instruction (passenger aircraft)	:	956
Environmentally hazardous	:	yes

#### IMDG-Code

UN number	:	UN 3077
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc oxide, 2,6-Di-tert-butyl-p-cresol)
Class	:	9
Packing group	:	III
Labels	:	9
EmS Code	:	F-A, S-F
Marine pollutant	:	yes

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
5.6	2023/09/30	656836-00020	Date of first issue: 2016/05/02

---

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### GB 6944/12268

UN number	:	UN 3077
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc oxide, 2,6-Di-tert-butyl-p-cresol)
Class	:	9
Packing group	:	III
Labels	:	9
Marine pollutant	:	no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## 15. REGULATORY INFORMATION

### National regulatory information

#### Law on the Prevention and Control of Occupational Diseases

#### Yangtze River Protection Law

This product does not contain any dangerous chemicals prohibited for inland river transport.

#### The components of this product are reported in the following inventories:

AICS	:	not determined
DSL	:	not determined
IECSC	:	not determined

---

## 16. OTHER INFORMATION

Revision Date	:	2023/09/30
---------------	---	------------

### Further information

Sources of key data used to compile the Safety Data Sheet	:	Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <a href="http://echa.europa.eu/">http://echa.europa.eu/</a>
---	---	---

Date format	:	yyyy/mm/dd
-------------	---	------------

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CN OEL	:	Occupational exposure limits for hazardous agents in the

---

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
5.6	2023/09/30	656836-00020	Date of first issue: 2016/05/02

---

workplace - Chemical hazardous agents.

ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
CN OEL / PC-TWA	:	Permissible concentration - time weighted average
CN OEL / PC-STEEL	:	Permissible concentration - short term exposure limit

AllC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CN / EN