according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Bismuth Subnitrate Formulation

Manufacturer or supplier's details

Company : MSD

Address : No. 485 Jing Tai Road

Pu Tuo District - Shanghai - China 200331

Telephone : +1-908-740-4000

Emergency telephone number : 86-571-87268110

E-mail address : EHSDATASTEWARD@msd.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product Restrictions on use : Not applicable

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance : paste Colour : white Odour : Petroleum

May cause an allergic skin reaction. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

GHS Classification

Skin sensitisation : Category 1

Specific target organ toxicity - : Category 1

repeated exposure

Short-term (acute) aquatic

Category 2

hazard

Long-term (chronic) aquatic

: Category 2

hazard

GHS label elements

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

Hazard pictograms :







Signal word : Danger

Hazard statements : H317 May cause an allergic skin reaction.

H372 Causes damage to organs through prolonged or repeated

exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water. P314 Get medical advice/ attention if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Physical and chemical hazards

Not classified based on available information.

Health hazards

May cause an allergic skin reaction. Causes damage to organs through prolonged or repeated exposure.

Environmental hazards

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

Chemical name	CAS-No.	Concentration (% w/w)	
Bismuth hydroxide nitrate oxide	1304-85-4	>= 50 -< 70	
Petrolatum	8009-03-8	>= 20 -< 30	
Zinc oxide	1314-13-2	>= 2.5 -< 10	
Benzyl alcohol	100-51-6	>= 1 -< 10	
2,6-Di-tert-butyl-p-cresol	128-37-0	>= 0.1 -< 0.25	

4. FIRST AID MEASURES

General advice In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

n case of skin contact In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse. Flush eyes with water as a precaution. In case of eye contact

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting. If swallowed Get medical attention if symptoms occur.

Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

May cause an allergic skin reaction. Causes damage to organs through prolonged or repeated

exposure.

Protection of first-aiders First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire-

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod- :

ucts

Nitrogen oxides (NOx)

Metal oxides

Carbon oxides

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

7. HANDLING AND STORAGE

Handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation

Use only with adequate ventilation. Do not get on skin or clothing.

Advice on safe handling

Do not breathe dust, fume, gas, mist, vapours or spray.

Do not swallow.

Avoid contact with eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

practice, based on the results of the workplace exposure as-

sessment

Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Avoidance of contact : Oxidizing agents

Storage

Conditions for safe storage : Keep in properly labelled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Packaging material : Unsuitable material: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Petrolatum	8009-03-8	TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
Zinc oxide	1314-13-2	PC-TWA	3 mg/m3	CN OEL
		PC-STEL	5 mg/m3	CN OEL
		TWA (Respirable particulate matter)	2 mg/m3	ACGIH
		STEL (Respirable particulate matter)	10 mg/m3	ACGIH
2,6-Di-tert-butyl-p-cresol	128-37-0	TWA (Inhal- able fraction and vapor)	2 mg/m3	ACGIH

Engineering measures : Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapour type Eye/face protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the

end of workday.

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the work-

ing place.

When using do not eat, drink or smoke.

Contaminated work clothing should not be allowed out of the

workplace.

Wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : white

Odour : Petroleum

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Not classified as a flammability hazard

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower : No data available

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

flammability limit

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : No data available

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

: Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics

Particle size : No data available

10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard. Chemical stability : Stable under normal conditions.

Possibility of hazardous reac- :

tions

Can react with strong oxidizing agents.

Conditions to avoid : None known. Incompatible materials : Oxidizing agents

Hazardous decomposition :

products

: No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Exposure routes : Skin contact

Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Product:

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Components:

Bismuth hydroxide nitrate oxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 423

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.07 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 436

Remarks: Based on data from similar materials

Petrolatum:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Zinc oxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.7 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Benzyl alcohol:

Acute oral toxicity : LD50 (Rat): 1,200 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.4 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

tion toxicity

2,6-Di-tert-butyl-p-cresol:

Acute oral toxicity : LD50 (Rat): > 6,000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 439

Result : No skin irritation

Petrolatum:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Zinc oxide:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Benzyl alcohol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

2,6-Di-tert-butyl-p-cresol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

Components:

Bismuth hydroxide nitrate oxide:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Petrolatum:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Zinc oxide:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Benzyl alcohol:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Method : OECD Test Guideline 405

2,6-Di-tert-butyl-p-cresol:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Petrolatum:

Test Type : Buehler Test

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Remarks : Based on data from similar materials

Zinc oxide:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Benzyl alcohol:

Test Type : Human repeat insult patch test (HRIPT)

Exposure routes : Skin contact
Species : Humans
Result : positive

Assessment : Probability or evidence of low to moderate skin sensitisation

rate in humans

2,6-Di-tert-butyl-p-cresol:

Test Type : Human repeat insult patch test (HRIPT)

Exposure routes : Skin contact
Species : Humans
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Petrolatum:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Zinc oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: equivocal

Test Type: Chromosome aberration test in vitro

Result: equivocal

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (dust/mist/fume)

Method: OECD Test Guideline 474

Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: inhalation (dust/mist/fume)

Result: positive

Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity -

Assessment

: Weight of evidence does not support classification as a germ

cell mutagen.

Benzyl alcohol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay)

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

2,6-Di-tert-butyl-p-cresol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: Ingestion

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Petrolatum:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Zinc oxide:

Species: MouseApplication Route: IngestionExposure time: 1 YearsResult: negative

Remarks : Based on data from similar materials

Benzyl alcohol:

Species : Mouse
Application Route : Ingestion
Exposure time : 103 weeks

Method : OECD Test Guideline 451

Result : negative

2,6-Di-tert-butyl-p-cresol:

Species : Rat Application Route : Ingestion

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

Exposure time : 22 Months
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

Petrolatum:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Skin contact

Result: negative

Remarks: Based on data from similar materials

Zinc oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (dust/mist/fume)

Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

Benzyl alcohol:

Effects on fertility : Test Type: Fertility/early embryonic development

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Mouse

Application Route: Ingestion

Result: negative

2,6-Di-tert-butyl-p-cresol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion

Result: negative

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Components:

Bismuth hydroxide nitrate oxide:

Target Organs : Central nervous system

Assessment : Causes damage to organs through prolonged or repeated

exposure.

Zinc oxide:

Assessment : No significant health effects observed in animals at concentra-

tions of 0.2 mg/l/6h/d or less.

2,6-Di-tert-butyl-p-cresol:

Assessment : No significant health effects observed in animals at concentra-

tions of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

Petrolatum:

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

Species : Rat

NOAEL : 5,000 mg/kg
Application Route : Ingestion
Exposure time : 2 yr

Zinc oxide:

Species : Rat, male NOAEL : 0.0015 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 3 Months

Method : OECD Test Guideline 413

Benzyl alcohol:

Species : Rat NOAEL : 1.072 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 28 Days

Method : OECD Test Guideline 412

2,6-Di-tert-butyl-p-cresol:

Species : Rat

NOAEL : 25 mg/kg

Application Route : Ingestion

Exposure time : 22 Months

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Product:

Ingestion : Symptoms: The absorption of this product into the body may

lead to the formation of methaemoglobine that, in sufficient concentration, causes cyanosis., May cause, Neurological disorders, Blood disorders, blood effects, central nervous sys-

tem effects, Methaemoglobinemia

Components:

Bismuth hydroxide nitrate oxide:

Ingestion : Target Organs: Blood

Symptoms: Methaemoglobinemia Target Organs: Central nervous system Symptoms: Neurological disorders

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Bismuth hydroxide nitrate oxide:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 137 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 137 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 137

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): >

137 ma/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Petrolatum:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

NOEL (Pseudokirchneriella subcapitata (green algae)): >=

100 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

NOEC (Daphnia magna (Water flea)): 10 mg/l

Exposure time: 21 d

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

ic toxicity) Test substance: Water Accommodated Fraction

Remarks: Based on data from similar materials

Zinc oxide:

Toxicity to fish LC50 : > 0.1 - 1 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.136

mg/l

Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (green algae)): > 0.01

- 0.1 mg/l

Exposure time: 72 h

Remarks: Based on data from similar materials

M-Factor (Acute aquatic tox- :

icity)

Toxicity to fish (Chronic tox- : NOEC (Jordanella floridae (flagfish)): > 0.01 - 0.1 mg/l

Exposure time: 14 Weeks

Remarks: Based on data from similar materials

Toxicity to daphnia and other:

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Ceriodaphnia dubia (water flea)): > 0.01 - 0.1 mg/l

Exposure time: 7 d

Remarks: Based on data from similar materials

M-Factor (Chronic aquatic

toxicity)

: 1

Benzyl alcohol:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): 460 mg/l

Exposure time: 96 h

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 230 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 770

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 310

ma/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other: aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 51 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 656836-00022 6.0 2024/09/28 Date of first issue: 2016/05/02

П

2,6-Di-tert-butyl-p-cresol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 0.57 mg/l

Exposure time: 96 h

Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.48 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0.24

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.24

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox- : 1

Toxicity to fish (Chronic tox-

icity)

NOEC (Oryzias latipes (Japanese medaka)): 0.053 mg/l

Exposure time: 30 d

Method: OECD Test Guideline 210

Toxicity to daphnia and other: aguatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.316 mg/l

Exposure time: 21 d

M-Factor (Chronic aquatic

toxicity)

: 1

Toxicity to microorganisms

EC50: > 10,000 mg/l Exposure time: 3 h

Method: OECD Test Guideline 209

Persistence and degradability

Components:

Petrolatum:

Biodegradability Result: Not readily biodegradable.

> Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Benzyl alcohol:

Biodegradability Result: Readily biodegradable.

Biodegradation: 92 - 96 %

Exposure time: 14 d

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

П

2,6-Di-tert-butyl-p-cresol:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 4.5 % Exposure time: 28 d

Method: OECD Test Guideline 301C

Bioaccumulative potential

Components:

Zinc oxide:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)

Bioconcentration factor (BCF): 78 - 2,060

Benzyl alcohol:

Partition coefficient: n- : log Pow: 1.05

octanol/water

2,6-Di-tert-butyl-p-cresol:

Bioaccumulation : Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): 330 - 1,800

Partition coefficient: n-

octanol/water

log Pow: 5.1

Mobility in soil
No data available

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo : 956

aircraft)

Packing instruction (passen-

ger aircraft)

Environmentally hazardous : yes

IMDG-Code

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

956

(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

GB 6944/12268

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : 9
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

15. REGULATORY INFORMATION

National regulatory information

Law on the Prevention and Control of Occupational Diseases

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals This product is not listed in the cata-

logue of hazardous chemicals, but it meets the definition of hazardous chemicals and its principles of de-

termination.

dentification of Major Hazard Installations for Hazardous Chemicals (GB : Not listed

18218)

Hazardous Chemicals for Priority Management under : Not listed

SAWS

Regulations on Labour Protection in Workplaces where Toxic Substances are Used

Catalogue of Highly Toxic Chemicals : Not listed

Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import : Not listed

and Export

Regulation on the Administration of Precursor Chemicals

Catalogue and Classification of Precursor Chemicals : Not listed

Yangtze River Protection Law

This product does not contain any dangerous chemicals prohibited for inland river transport.

The components of this product are reported in the following inventories:

AICS not determined

DSL not determined

IECSC not determined

16. OTHER INFORMATION

Revision Date 2024/09/28

Further information

Sources of key data used to compile the Safety Data

Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CN OEL : Occupational exposure limits for hazardous agents in the

workplace - Chemical hazardous agents.

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

CN OEL / PC-TWA : Permissible concentration - time weighted average CN OEL / PC-STEL : Permissible concentration - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be

according to GB/T 16483 and GB/T 17519



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 6.0 2024/09/28 656836-00022 Date of first issue: 2016/05/02

considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CN / EN