

Bismuth Subnitrate Formulation

Version 6.1 Revision Date: 2023/09/30 SDS Number: 656839-00021 Date of last issue: 2023/04/04
Date of first issue: 2016/05/02

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Bismuth Subnitrate Formulation

Manufacturer or supplier's details

Company : MSD
Address : 126 E. Lincoln Avenue
Rahway, New Jersey U.S.A. 07065
Telephone : 908-740-4000
Emergency telephone number : 1-908-423-6000
E-mail address : EHSDATASTEWARD@msd.com

Recommended use of the chemical and restrictions on use



Recommended use : Veterinary product
Restrictions on use : Not applicable

2. HAZARDS IDENTIFICATION**GHS Classification**

Specific target organ toxicity - repeated exposure : Category 1 (Central nervous system)

Long-term (chronic) aquatic hazard : Category 2

GHS label elements

Hazard pictograms :  

Signal word : Danger

Hazard statements : H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P273 Avoid release to the environment.

Bismuth Subnitrate Formulation

Version 6.1 Revision Date: 2023/09/30 SDS Number: 656839-00021 Date of last issue: 2023/04/04
Date of first issue: 2016/05/02

Response:

P314 Get medical advice/ attention if you feel unwell.
P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Bismuth hydroxide nitrate oxide	1304-85-4	≥ 60 - ≤ 100
Petrolatum	8009-03-8	≥ 10 - < 30
Zinc oxide	1314-13-2	≥ 2.5 - < 10
Benzyl alcohol	100-51-6	< 10
2,6-Di-tert-butyl-p-cresol	128-37-0	≥ 0.025 - < 0.25

4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
6.1	2023/09/30	656839-00021	Date of first issue: 2016/05/02

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Nitrogen oxides (NO_x)
Metal oxides
Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
-

7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not breathe dust, fume, gas, mist, vapours or spray.

Bismuth Subnitrate Formulation

Version 6.1 Revision Date: 2023/09/30 SDS Number: 656839-00021 Date of last issue: 2023/04/04
 Date of first issue: 2016/05/02

Do not swallow.
 Avoid contact with eyes.
 Avoid prolonged or repeated contact with skin.
 Wash skin thoroughly after handling.
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
 Do not eat, drink or smoke when using this product.
 Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labelled containers.
 Store in accordance with the particular national regulations.
 Materials to avoid : Do not store with the following product types:
 Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Petrolatum	8009-03-8	NAB (Mist)	5 mg/m ³	ID OEL
		PSD (Mist)	10 mg/m ³	ID OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Zinc oxide	1314-13-2	NAB (Respirable particulate matter)	2 mg/m ³	ID OEL
	Further information: Not classified as carcinogenic to humans. Not enough data to classify these materials as carcinogenic to humans or animals			
		PSD (Respirable particulate matter)	10 mg/m ³	ID OEL
	Further information: Not classified as carcinogenic to humans. Not enough data to classify these materials as carcinogenic to humans or animals			
		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
		STEL (Respirable particulate matter)	10 mg/m ³	ACGIH
2,6-Di-tert-butyl-p-cresol	128-37-0	TWA (Inhalable fraction)	2 mg/m ³	ACGIH

Bismuth Subnitrate Formulation

Version 6.1	Revision Date: 2023/09/30	SDS Number: 656839-00021	Date of last issue: 2023/04/04 Date of first issue: 2016/05/02
----------------	------------------------------	-----------------------------	---

		and vapor)		
--	--	------------	--	--

Engineering measures : Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapour type
Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : white

Odour : Petroleum

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
6.1	2023/09/30	656839-00021	Date of first issue: 2016/05/02

Flammability (solid, gas)	:	Not classified as a flammability hazard
Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	No data available
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	No data available

10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Can react with strong oxidizing agents.
Conditions to avoid	:	None known.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of	:	Skin contact
---------------------------------	---	--------------

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
6.1	2023/09/30	656839-00021	Date of first issue: 2016/05/02

toxicity

Benzyl alcohol:

Acute oral toxicity : LD50 (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

2,6-Di-tert-butyl-p-cresol:

Acute oral toxicity : LD50 (Rat): > 6,000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439

Result : No skin irritation

Petrolatum:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Zinc oxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Benzyl alcohol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

2,6-Di-tert-butyl-p-cresol:

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
6.1	2023/09/30	656839-00021	Date of first issue: 2016/05/02

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation
Remarks	:	Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

Petrolatum:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

Zinc oxide:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405

Benzyl alcohol:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days
Method	:	OECD Test Guideline 405

2,6-Di-tert-butyl-p-cresol:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Test Type	:	Local lymph node assay (LLNA)
-----------	---	-------------------------------

Bismuth Subnitrate Formulation

Version 6.1 Revision Date: 2023/09/30 SDS Number: 656839-00021 Date of last issue: 2023/04/04
Date of first issue: 2016/05/02

Exposure routes : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

Petrolatum:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Zinc oxide:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

Benzyl alcohol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

2,6-Di-tert-butyl-p-cresol:

Test Type : Human repeat insult patch test (HRIPT)
Exposure routes : Skin contact
Species : Humans
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Bismuth Subnitrate Formulation

Version 6.1	Revision Date: 2023/09/30	SDS Number: 656839-00021	Date of last issue: 2023/04/04 Date of first issue: 2016/05/02
----------------	------------------------------	-----------------------------	---

Petrolatum:

- Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Result: negative
Remarks: Based on data from similar materials
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Zinc oxide:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
- Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: equivocal
- Test Type: Chromosome aberration test in vitro
Result: equivocal
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (dust/mist/fume)
Method: OECD Test Guideline 474
Result: negative
- Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: inhalation (dust/mist/fume)
Result: positive
- Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
- Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Benzyl alcohol:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
6.1	2023/09/30	656839-00021	Date of first issue: 2016/05/02

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

2,6-Di-tert-butyl-p-cresol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Ingestion
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Petrolatum:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Zinc oxide:

Species : Mouse
Application Route : Ingestion
Exposure time : 1 Years
Result : negative
Remarks : Based on data from similar materials

Benzyl alcohol:

Species : Mouse
Application Route : Ingestion
Exposure time : 103 weeks
Method : OECD Test Guideline 451
Result : negative

Bismuth Subnitrate Formulation

Version 6.1 Revision Date: 2023/09/30 SDS Number: 656839-00021 Date of last issue: 2023/04/04
Date of first issue: 2016/05/02

2,6-Di-tert-butyl-p-cresol:

Species : Rat
Application Route : Ingestion
Exposure time : 22 Months
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:**Bismuth hydroxide nitrate oxide:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Petrolatum:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Skin contact
Result: negative
Remarks: Based on data from similar materials

Zinc oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (dust/mist/fume)
Method: OECD Test Guideline 414
Result: negative

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
6.1	2023/09/30	656839-00021	Date of first issue: 2016/05/02

Remarks: Based on data from similar materials

Benzyl alcohol:

Effects on fertility : Test Type: Fertility/early embryonic development
 Species: Rat
 Application Route: Ingestion
 Result: negative
 Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
 Species: Mouse
 Application Route: Ingestion
 Result: negative

2,6-Di-tert-butyl-p-cresol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
 Species: Rat
 Application Route: Ingestion
 Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
 Species: Rat
 Application Route: Ingestion
 Result: negative

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Components:

Bismuth hydroxide nitrate oxide:

Target Organs : Central nervous system
 Assessment : Causes damage to organs through prolonged or repeated exposure.

Zinc oxide:

Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

2,6-Di-tert-butyl-p-cresol:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Bismuth Subnitrate Formulation

Version 6.1 Revision Date: 2023/09/30 SDS Number: 656839-00021 Date of last issue: 2023/04/04
Date of first issue: 2016/05/02

Repeated dose toxicity**Components:****Petrolatum:**

Species : Rat
NOAEL : 5,000 mg/kg
Application Route : Ingestion
Exposure time : 2 yr

Zinc oxide:

Species : Rat, male
NOAEL : 0.0015 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 3 Months
Method : OECD Test Guideline 413

Benzyl alcohol:

Species : Rat
NOAEL : 1.072 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 28 Days
Method : OECD Test Guideline 412

2,6-Di-tert-butyl-p-cresol:

Species : Rat
NOAEL : 25 mg/kg
Application Route : Ingestion
Exposure time : 22 Months

Aspiration toxicity

Not classified based on available information.

Experience with human exposure**Product:**

Ingestion : Symptoms: The absorption of this product into the body may lead to the formation of methaemoglobine that, in sufficient concentration, causes cyanosis., May cause, Neurological disorders, Blood disorders, blood effects, central nervous system effects, Methaemoglobinemia

Components:**Bismuth hydroxide nitrate oxide:**

Ingestion : Target Organs: Blood
Symptoms: Methaemoglobinemia
Target Organs: Central nervous system
Symptoms: Neurological disorders

Bismuth Subnitrate Formulation

Version 6.1 Revision Date: 2023/09/30 SDS Number: 656839-00021 Date of last issue: 2023/04/04
Date of first issue: 2016/05/02

12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Bismuth hydroxide nitrate oxide:**

- Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 137 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 137 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
- NOELR (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Petrolatum:

- Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
6.1	2023/09/30	656839-00021	Date of first issue: 2016/05/02

Remarks: Based on data from similar materials

Zinc oxide:

Toxicity to fish : LC50 : > 0.1 - 1 mg/l
 Exposure time: 96 h
 Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.136 mg/l
 Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (green algae)): > 0.01 - 0.1 mg/l
 Exposure time: 72 h
 Remarks: Based on data from similar materials

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic toxicity) : NOEC (Jordanella floridae (flagfish)): > 0.01 - 0.1 mg/l
 Exposure time: 14 Weeks
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): > 0.01 - 0.1 mg/l
 Exposure time: 7 d
 Remarks: Based on data from similar materials

M-Factor (Chronic aquatic toxicity) : 1

Benzyl alcohol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 460 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 230 mg/l
 Exposure time: 48 h
 Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 770 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 310 mg/l
 Exposure time: 72 h
 Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 51 mg/l
 Exposure time: 21 d
 Method: OECD Test Guideline 211

Bismuth Subnitrate Formulation

Version 6.1 Revision Date: 2023/09/30 SDS Number: 656839-00021 Date of last issue: 2023/04/04
Date of first issue: 2016/05/02

2,6-Di-tert-butyl-p-cresol:

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 0.57 mg/l
Exposure time: 96 h
Method: Directive 67/548/EEC, Annex V, C.1.
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.48 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0.24 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- NOEC (Pseudokirchneriella subcapitata (green algae)): 0.24 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- M-Factor (Acute aquatic toxicity) : 1
- Toxicity to fish (Chronic toxicity) : NOEC (Oryzias latipes (Japanese medaka)): 0.053 mg/l
Exposure time: 30 d
Method: OECD Test Guideline 210
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.316 mg/l
Exposure time: 21 d
- M-Factor (Chronic aquatic toxicity) : 1
- Toxicity to microorganisms : EC50: > 10,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Persistence and degradability**Components:****Petrolatum:**

- Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Benzyl alcohol:

- Biodegradability : Result: Readily biodegradable.
Biodegradation: 92 - 96 %
Exposure time: 14 d

2,6-Di-tert-butyl-p-cresol:

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
6.1	2023/09/30	656839-00021	Date of first issue: 2016/05/02

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 4.5 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301C

Bioaccumulative potential

Components:

Zinc oxide:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
 Bioconcentration factor (BCF): 78 - 2,060

Benzyl alcohol:

Partition coefficient: n-octanol/water : log Pow: 1.05

2,6-Di-tert-butyl-p-cresol:

Bioaccumulation : Species: Cyprinus carpio (Carp)
 Bioconcentration factor (BCF): 330 - 1,800

Partition coefficient: n-octanol/water : log Pow: 5.1

Mobility in soil

No data available

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
 Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
 If not otherwise specified: Dispose of as unused product.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
 (Zinc oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
 Packing group : III
 Labels : 9

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
6.1	2023/09/30	656839-00021	Date of first issue: 2016/05/02

Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3077
 Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
 (Zinc oxide, 2,6-Di-tert-butyl-p-cresol)
 Class : 9
 Packing group : III
 Labels : Miscellaneous
 Packing instruction (cargo aircraft) : 956
 Packing instruction (passenger aircraft) : 956
 Environmentally hazardous : yes

IMDG-Code

UN number : UN 3077
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
 N.O.S.
 (Zinc oxide, 2,6-Di-tert-butyl-p-cresol)
 Class : 9
 Packing group : III
 Labels : 9
 EmS Code : F-A, S-F
 Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Minister of Industry Regulation No. 23/M-IND/PER/4/2013 concerning the Revision of Minister of Industry Regulation No. 87/M-IND/PER/9/2009 concerning Globally Harmonized System of Classification and Labelling of Chemicals.

Regulation of the Minister of Health No. 472 of 1996 on the Safeguarding of Substances Hazardous to Health

Hazardous substances that must be registered : Not applicable

Government Regulation No. 74 of 2001 on the Management of Hazardous and Toxic Substances

Hazardous substances approved for use : Not applicable

Prohibited substances : Not applicable

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
6.1	2023/09/30	656839-00021	Date of first issue: 2016/05/02

Restricted substances : Not applicable

Regulation of the Ministry of Trade No. 7 of 2022 on Distribution and Control of Hazardous Materials

Type of hazardous materials subject to distribution and control, Annex I : Not applicable

Type of hazardous materials subject to distribution and control, Annex II : Not applicable

The components of this product are reported in the following inventories:

AICS	: not determined
DSL	: not determined
IECSC	: not determined

16. OTHER INFORMATION

Revision Date : 2023/09/30

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ID OEL	: Indonesia. Occupational Exposure Limits

ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
ID OEL / NAB	: Long term exposure limit
ID OEL / PSD	: Short term exposure limit

AllC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemi-

Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 2023/04/04
6.1	2023/09/30	656839-00021	Date of first issue: 2016/05/02

cal Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

ID / EN