according to the Globally Harmonized System



### **Bismuth Subnitrate Formulation**

Revision Date: Date of last issue: 04.04.2023 Version SDS Number: 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

#### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name Bismuth Subnitrate Formulation

Manufacturer or supplier's details

Company : MSD

Address Briahnager - Off Pune Nagar Road

Wagholi - Pune - India 412 207

+1-908-740-4000 Telephone

Emergency telephone number: +1-908-423-6000

E-mail address : EHSDATASTEWARD@msd.com

Recommended use of the chemical and restrictions on use

Veterinary product Recommended use Not applicable Restrictions on use

### 2. HAZARDS IDENTIFICATION

#### Manufacture, Storage and Import of Hazardous Chemicals Rules 1989

### Classification

Not classified as hazardous according to criteria laid down in Part I of Schedule-1.

**GHS Classification** 

repeated exposure

Specific target organ toxicity - : Category 1 (Central nervous system)

Short-term (acute) aquatic

hazard

Category 2

Long-term (chronic) aquatic

hazard

Category 2

**GHS** label elements

Hazard pictograms

Signal word

Hazard statements H372 Causes damage to organs (Central nervous system)

through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

according to the Globally Harmonized System



## **Bismuth Subnitrate Formulation**

**Revision Date:** Date of last issue: 04.04.2023 Version SDS Number: 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

Precautionary statements Prevention:

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

Response:

P319 Get medical help if you feel unwell.

P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

#### Other hazards which do not result in classification

None known.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Mixture

### Components

Chemical name	CAS-No.	Concentration (%
		w/w)
Bismuth hydroxide nitrate oxide	1304-85-4	>= 50 - < 70
Petrolatum	8009-03-8	>= 20 - < 30
Zinc oxide	1314-13-2	>= 5 - < 10
Benzyl alcohol	100-51-6	>= 1 - < 5
2,6-Di-tert-butyl-p-cresol	128-37-0	>= 0.1 - < 0.25

### 4. FIRST AID MEASURES

General advice In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of contact, immediately flush skin with soap and plenty In case of skin contact

of water.

Get medical attention if symptoms occur. Flush eyes with water as a precaution. In case of eye contact

Get medical attention if irritation develops and persists.

If swallowed If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

Protection of first-aiders

Causes damage to organs through prolonged or repeated

exposure.

First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment

according to the Globally Harmonized System



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical None known.

Unsuitable extinguishing

media

Specific hazards during fire-

fighting

Hazardous combustion prod-

ucts

Exposure to combustion products may be a hazard to health.

Nitrogen oxides (NOx)

Metal oxides Carbon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

### 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

according to the Globally Harmonized System



### **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not breathe dust, fume, gas, mist, vapours or spray.

Do not swallow.

Avoid contact with eyes.

Avoid prolonged or repeated contact with skin.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labelled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of	Control parame- ters / Permissible	Basis
		exposure)	concentration	
Petrolatum	8009-03-8	TWA (Mist)	5 mg/m3	IN OEL
		STEL (Mist)	10 mg/m3	IN OEL
		TWA (Inhal-	5 mg/m3	ACGIH
		able particu-		
		late matter)		
Zinc oxide	1314-13-2	TWA (Total	10 mg/m3	IN OEL
		dust)		
		TWA	5 mg/m3	IN OEL
		(Fumes)		
		STEL	10 mg/m3	IN OEL
		(Fumes)		
		TWA (Res-	2 mg/m3	ACGIH
		pirable par-		
		ticulate mat-		
		ter)		
		STEL (Res-	10 mg/m3	ACGIH
		pirable par-		
		ticulate mat-		
		ter)		1.000
2,6-Di-tert-butyl-p-cresol	128-37-0	TWA (Inhal-	2 mg/m3	ACGIH
		able fraction		
		and vapor)		

**Engineering measures** : Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

according to the Globally Harmonized System



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection.

Filter type Hand protection Combined particulates and organic vapour type

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the

end of workday.

Eye protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working

place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : white

Odour : Petroleum

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Not classified as a flammability hazard

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

according to the Globally Harmonized System



## **Bismuth Subnitrate Formulation**

Version **Revision Date:** SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

Vapour pressure No data available

Relative vapour density No data available

Relative density No data available

Density No data available

Solubility(ies)

Water solubility No data available

Partition coefficient: n-

octanol/water

Not applicable

Auto-ignition temperature No data available

Decomposition temperature No data available

Viscosity

Viscosity, kinematic No data available

Explosive properties Not explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

Particle size No data available

### 10. STABILITY AND REACTIVITY

Reactivity Not classified as a reactivity hazard. Chemical stability Stable under normal conditions. Possibility of hazardous reac- : Can react with strong oxidizing agents.

tions

Conditions to avoid None known. Incompatible materials Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

### 11. TOXICOLOGICAL INFORMATION

Information on likely routes of: Skin contact

exposure Ingestion

Eye contact

### Acute toxicity

Not classified based on available information.

**Product:** 

Acute oral toxicity Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute toxicity estimate: > 10 mg/l Acute inhalation toxicity

according to the Globally Harmonized System



### **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

### **Components:**

Bismuth hydroxide nitrate oxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 423

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.07 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 436

Remarks: Based on data from similar materials

Petrolatum:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Zinc oxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.7 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Benzyl alcohol:

Acute oral toxicity : LD50 (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

2,6-Di-tert-butyl-p-cresol:

according to the Globally Harmonized System



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

Acute oral toxicity : LD50 (Rat): > 6,000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

#### Skin corrosion/irritation

Not classified based on available information.

### **Components:**

### Bismuth hydroxide nitrate oxide:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 439

Result : No skin irritation

Petrolatum:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Zinc oxide:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Benzyl alcohol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

2,6-Di-tert-butyl-p-cresol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

### Serious eye damage/eye irritation

Not classified based on available information.

### **Components:**

### Bismuth hydroxide nitrate oxide:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

according to the Globally Harmonized System



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

Petrolatum:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

Remarks : Based on data from similar materials

Zinc oxide:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

Benzyl alcohol:

Species : Rabbit

Method : OECD Test Guideline 405

Result : Irritation to eyes, reversing within 21 days

2,6-Di-tert-butyl-p-cresol:

Species : Rabbit

Method : OECD Test Guideline 405

Result : No eye irritation

Remarks : Based on data from similar materials

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

### Respiratory sensitisation

Not classified based on available information.

### **Components:**

### Bismuth hydroxide nitrate oxide:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Petrolatum:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Remarks : Based on data from similar materials

Zinc oxide:

Test Type : Maximisation Test Exposure routes : Skin contact Species : Guinea pig

according to the Globally Harmonized System



### **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

Method : OECD Test Guideline 406

Result : negative

Benzyl alcohol:

Test Type : Maximisation Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

2,6-Di-tert-butyl-p-cresol:

Test Type : Human repeat insult patch test (HRIPT)

Exposure routes : Skin contact Species : Humans : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Petrolatum:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Zinc oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

according to the Globally Harmonized System



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: equivocal

Test Type: Chromosome aberration test in vitro

Result: equivocal

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (dust/mist/fume)

Method: OECD Test Guideline 474

Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: inhalation (dust/mist/fume)

Result: positive

Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

Benzyl alcohol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

2,6-Di-tert-butyl-p-cresol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

according to the Globally Harmonized System



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

**Application Route: Ingestion** 

Result: negative

### Carcinogenicity

Not classified based on available information.

### **Components:**

#### Petrolatum:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

#### Zinc oxide:

Species : Mouse
Application Route : Ingestion
Exposure time : 1 Years
Result : negative

Remarks : Based on data from similar materials

# Benzyl alcohol:

Species : Mouse
Application Route : Ingestion
Exposure time : 103 weeks

Method : OECD Test Guideline 451

Result : negative

### 2,6-Di-tert-butyl-p-cresol:

Species : Rat
Application Route : Ingestion
Exposure time : 22 Months
Result : negative

### Reproductive toxicity

Not classified based on available information.

### **Components:**

### Bismuth hydroxide nitrate oxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

according to the Globally Harmonized System



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

Result: negative

Petrolatum:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Skin contact

Result: negative

Remarks: Based on data from similar materials

Zinc oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (dust/mist/fume)

Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

Benzyl alcohol:

Effects on fertility : Test Type: Fertility/early embryonic development

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Mouse

Application Route: Ingestion

Result: negative

2,6-Di-tert-butyl-p-cresol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion

according to the Globally Harmonized System



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

Result: negative

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

**Components:** 

Bismuth hydroxide nitrate oxide:

Target Organs : Central nervous system

Assessment : Causes damage to organs through prolonged or repeated

exposure.

Zinc oxide:

Assessment : No significant health effects observed in animals at concentra-

tions of 0.2 mg/l/6h/d or less.

2,6-Di-tert-butyl-p-cresol:

Assessment : No significant health effects observed in animals at concentra-

tions of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

Petrolatum:

Species : Rat

NOAEL : 5,000 mg/kg
Application Route : Ingestion
Exposure time : 2 yr

Zinc oxide:

Species : Rat, male NOAEL : 0.0015 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 3 Months

Method : OECD Test Guideline 413

Benzyl alcohol:

Species : Rat NOAEL : 1.072 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 28 Days

Method : OECD Test Guideline 412

2,6-Di-tert-butyl-p-cresol:

Species : Rat NOAEL : 25 mg/kg

according to the Globally Harmonized System



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

Application Route : Ingestion Exposure time : 22 Months

### **Aspiration toxicity**

Not classified based on available information.

### Experience with human exposure

**Product:** 

Ingestion : Symptoms: The absorption of this product into the body may

lead to the formation of methaemoglobine that, in sufficient concentration, causes cyanosis., May cause, Neurological disorders, Blood disorders, blood effects, central nervous sys-

tem effects, Methaemoglobinemia

**Components:** 

Bismuth hydroxide nitrate oxide:

Ingestion : Target Organs: Blood

Symptoms: Methaemoglobinemia Target Organs: Central nervous system Symptoms: Neurological disorders

### 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

### **Components:**

### Bismuth hydroxide nitrate oxide:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 137 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 137 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 137

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): >

137 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

#### Petrolatum:

according to the Globally Harmonized System



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

NOEL (Pseudokirchneriella subcapitata (green algae)): >=

100 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

NOEC: 10 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Zinc oxide:

Toxicity to fish : LC50: > 0.1 - 1 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.136

mg/l

Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (green algae)): >

0.01 - 0.1 mg/l Exposure time: 72 h

Remarks: Based on data from similar materials

M-Factor (Acute aquatic tox-

icity)

: 1

Toxicity to fish (Chronic tox-

icity)

NOEC: > 0.01 - 0.1 mg/l

NOEC: > 0.01 - 0.1 mg/l

Exposure time: 14 Weeks

Species: Jordanella floridae (flagfish)

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

Exposure time: 7 d

ic toxicity)

Species: Ceriodaphnia dubia (water flea)

Remarks: Based on data from similar materials

M-Factor (Chronic aquatic

toxicity)

1

according to the Globally Harmonized System



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

Benzyl alcohol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 460 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 230 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 770

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 310

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC: 51 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

2,6-Di-tert-butyl-p-cresol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 0.57 mg/l

Exposure time: 96 h

Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.48 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 ( Pseudokirchneriella subcapitata (green algae)): >

0.24 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.24

mq/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox- :

icity)

: 1

Toxicity to microorganisms : EC50: > 10,000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Toxicity to fish (Chronic tox-

icity)

NOEC: 0.053 mg/l

Exposure time: 30 d Species: Oryzias latipes (Japanese medaka)

Method: OECD Test Guideline 210

according to the Globally Harmonized System



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC: 0.316 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

M-Factor (Chronic aquatic

toxicity)

: 1

### Persistence and degradability

### **Components:**

Petrolatum:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Benzyl alcohol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 92 - 96 % Exposure time: 14 d

2,6-Di-tert-butyl-p-cresol:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 4.5 % Exposure time: 28 d

Method: OECD Test Guideline 301C

Bioaccumulative potential

**Components:** 

Zinc oxide:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)

Bioconcentration factor (BCF): 78 - 2,060

Benzyl alcohol:

Partition coefficient: n-

octanol/water

log Pow: 1.05

2,6-Di-tert-butyl-p-cresol:

Bioaccumulation : Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): 330 - 1,800

Partition coefficient: n-

octanol/water

log Pow: 5.1

according to the Globally Harmonized System



### **Bismuth Subnitrate Formulation**

**Revision Date:** Version SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

### Mobility in soil

No data available

### Other adverse effects

No data available

#### 13. DISPOSAL CONSIDERATIONS

**Disposal methods** 

Waste from residues Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

#### 14. TRANSPORT INFORMATION

### International Regulations

**UNRTDG** 

**UN** number UN 3077

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)

Class 9 Packing group Ш Labels 9 Environmentally hazardous yes

**IATA-DGR** 

UN/ID No. UN 3077

Proper shipping name Environmentally hazardous substance, solid, n.o.s.

(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)

Class 9 Ш Packing group

Miscellaneous Labels

Packing instruction (cargo

aircraft)

956

Packing instruction (passen-

956

ger aircraft)

Environmentally hazardous yes

**IMDG-Code** 

**UN** number UN 3077

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)

Class 9 Packing group Ш Labels 9 **EmS Code** F-A, S-F Marine pollutant yes

#### Transport in bulk according to IMO instruments

Not applicable for product as supplied.

according to the Globally Harmonized System



## **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

The components of this product are reported in the following inventories:

**AICS** not determined

DSL not determined

**IECSC** not determined

#### 16. OTHER INFORMATION

**Revision Date** 30.09.2023

**Further information** 

Sources of key data used to

: Internal technical data, data from raw material SDSs, OECD compile the Safety Data eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/

Sheet

Date format dd.mm.yyyy

Full text of other abbreviations

**ACGIH** USA. ACGIH Threshold Limit Values (TLV)

India. Permissible levels of certain chemical substances in IN OEL

work environment.

ACGIH / TWA 8-hour, time-weighted average Short-term exposure limit ACGIH / STEL

Time-Weighted Average Concentration (TWA) (8 hrs.) IN OEL / TWA

IN OEL / STEL Short-term exposure Limit STEL (15 min)

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Or-

according to the Globally Harmonized System



### **Bismuth Subnitrate Formulation**

Version Revision Date: SDS Number: Date of last issue: 04.04.2023 5.6 30.09.2023 657129-00020 Date of first issue: 02.05.2016

ganisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose): MARPOL - International Convention for the Prevention of Pollution from Ships: n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

IN / EN