

Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

1. PRODUCT AND COMPANY IDENTIFICATION

Chemical product name : Bismuth Subnitrate Formulation

Supplier's company name, address and phone number

Company name of supplier : MSD

Address : Kumagaya, Saitama Prefecture , Xicheng 810 MSD Co., Ltd.

Menuma factory

Telephone : 048-588-8411

E-mail address : EHSDATASTEWARD@msd.com

Emergency telephone number : +1-908-423-6000

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product Restrictions on use : Not applicable

2. HAZARDS IDENTIFICATION

GHS classification of chemical product

Skin sensitisation : Category 1

Specific target organ toxicity - :

repeated exposure

Category 1 (Central nervous system)

Short-term (acute) aquatic

hazard

Category 2

Long-term (chronic) aquatic

hazard

Category 2

GHS label elements

Hazard pictograms

(!



Signal word : Danger

Hazard statements : H317 May cause an allergic skin reaction.

H372 Causes damage to organs (Central nervous system)

through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

Precautionary statements : Prevention:

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water. P314 Get medical advice/ attention if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

P391 Collect spillage.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)	ENCS No.
Bismuth hydroxide nitrate oxide	1304-85-4	>= 60 - < 70	1-97
Petrolatum	8009-03-8	>= 20 - < 30	-
Zinc oxide	1314-13-2	5	1-561
Benzyl alcohol	100-51-6	>= 1 - < 10	3-1011
2,6-Di-tert-butyl-p-cresol	128-37-0	>= 0.1 - < 1	3-540, 9-1805

4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

In case of skin contact : In case of contact, immediately flush skin with soap and plenty

of water

Remove contaminated clothing and shoes.

Get medical attention.
Wash clothing before reuse.

Thoroughly clean shoes before reuse.
In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delaved

: May cause an allergic skin reaction.

Causes damage to organs through prolonged or repeated

exposure.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire-

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Nitrogen oxides (NOx)

Metal oxides Carbon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

O.

Evacuate area.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

7. HANDLING AND STORAGE

Handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe dust, fume, gas, mist, vapours or spray.

Do not swallow.

Avoid contact with eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Avoidance of contact : Oxidizing agents

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working

place.

When using do not eat, drink or smoke.

Contaminated work clothing should not be allowed out of the

workplace.

Wash contaminated clothing before re-use.

Storage

Conditions for safe storage : Keep in properly labelled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents



Bismuth Subnitrate Formulation

Version **Revision Date:** SDS Number: Date of last issue: 2024/04/06 2024/09/28 656842-00022 Date of first issue: 2016/05/02 13.0

Packaging material : Unsuitable material: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Threshold limit value and permissible exposure limits for each component in the work environment

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Concentration standard / Permissible concentration	Basis
Petrolatum	8009-03-8	OEL-M (Mist)	3 mg/m3	JP OEL JSOH
	Further inform	nation: Group 1: o	arcinogenic to huma	ns
		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH
Zinc oxide	1314-13-2	8h-OEL-M (As respirato- ry particles)	0.1 mg/m3	JP ISHL OEL 577-2(2)
		TWA (Respirable particulate matter)	2 mg/m3	ACGIH
		STEL (Respirable particulate matter)	10 mg/m3	ACGIH
Benzyl alcohol	100-51-6	OEL-C	25 mg/m3	JP OEL JSOH
		Further information: Skin sensitizing agent; Group 2 substances which probably induce allergic reactions in humans.		
2,6-Di-tert-butyl-p-cresol	128-37-0	8h-OEL-M	10 mg/m3	JP ISHL OEL 577-2(2)
		TWA (Inhal- able fraction and vapor)	2 mg/m3	ACGIH

Engineering measures Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection. Combined particulates and organic vapour type

Filter type

Hand protection

Material Chemical-resistant gloves



Bismuth Subnitrate Formulation

SDS Number: Date of last issue: 2024/04/06 Version Revision Date: 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

Remarks Choose gloves to protect hands against chemicals depending

> on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the

end of workday.

Impermeable protective gloves

Eye protection Wear the following personal protective equipment:

Safety glasses

Select appropriate protective clothing based on chemical Skin and body protection

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state paste

Colour white

Odour Petroleum

Odour Threshold No data available

Melting point/freezing point No data available

Boiling point, initial boiling point and boiling range

No data available

Flammability (solid, gas) Not classified as a flammability hazard

Flammability (liquids) No data available

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit / Lower flammability limit No data available

Flash point Not applicable

Decomposition temperature No data available

pΗ No data available

No data available Evaporation rate

Auto-ignition temperature No data available



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

Viscosity

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

Not applicable

Vapour pressure : No data available

Density and / or relative density

Relative density : No data available

Density : No data available

Relative vapour density : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics

Particle size : No data available

10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reac- : Can react with strong oxidizing agents.

tions

Conditions to avoid : None known. Incompatible materials : Oxidizing agents

Hazardous decomposition : No hazardous decomposition products are known.

products

11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Skin contact

exposure Ingestion

Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

Components:

Bismuth hydroxide nitrate oxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 423

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.07 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: OECD Test Guideline 436

Remarks: Based on data from similar materials

Petrolatum:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Zinc oxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.7 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Benzyl alcohol:

Acute oral toxicity : LD50 (Rat): 1,200 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.4 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

2,6-Di-tert-butyl-p-cresol:

Acute oral toxicity : LD50 (Rat): > 6,000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 439

Result : No skin irritation

Petrolatum:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Zinc oxide:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Benzyl alcohol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

2,6-Di-tert-butyl-p-cresol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

Components:

Bismuth hydroxide nitrate oxide:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Petrolatum:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Zinc oxide:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Benzyl alcohol:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Method : OECD Test Guideline 405

2,6-Di-tert-butyl-p-cresol:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Petrolatum:

Test Type : Buehler Test Exposure routes : Skin contact



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

Species : Guinea pig Result : negative

Remarks : Based on data from similar materials

Zinc oxide:

Test Type : Maximisation Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Benzyl alcohol:

Test Type : Human repeat insult patch test (HRIPT)

Exposure routes : Skin contact
Species : Humans
Result : positive

Assessment : Probability or evidence of low to moderate skin sensitisation

rate in humans

2,6-Di-tert-butyl-p-cresol:

Test Type : Human repeat insult patch test (HRIPT)

Exposure routes : Skin contact
Species : Humans
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Petrolatum:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Remarks: Based on data from similar materials



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay)
Species: Mouse

Application Route: Intraperitoneal injection Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Zinc oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: equivocal

Test Type: Chromosome aberration test in vitro

Result: equivocal

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (dust/mist/fume)

Method: OECD Test Guideline 474

Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: inhalation (dust/mist/fume)

Result: positive

Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

Benzyl alcohol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

П

2,6-Di-tert-butyl-p-cresol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

Application Route: Ingestion

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Petrolatum:

Species: RatApplication Route: IngestionExposure time: 2 YearsResult: negative

Zinc oxide:

Species : Mouse
Application Route : Ingestion
Exposure time : 1 Years
Result : negative

Remarks : Based on data from similar materials

Benzyl alcohol:

Species : Mouse
Application Route : Ingestion
Exposure time : 103 weeks

Method : OECD Test Guideline 451

Result : negative

2,6-Di-tert-butyl-p-cresol:

Species : Rat
Application Route : Ingestion
Exposure time : 22 Months
Result : negative



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

Reproductive toxicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

Petrolatum:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Skin contact

Result: negative

Remarks: Based on data from similar materials

Zinc oxide:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (dust/mist/fume)

Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

Benzyl alcohol:

Effects on fertility : Test Type: Fertility/early embryonic development

Species: Rat

Application Route: Ingestion



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Mouse

Application Route: Ingestion

Result: negative

2,6-Di-tert-butyl-p-cresol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion

Result: negative

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Components:

Bismuth hydroxide nitrate oxide:

Target Organs : Central nervous system

Assessment : Causes damage to organs through prolonged or repeated

exposure.

Zinc oxide:

Assessment : No significant health effects observed in animals at concentra-

tions of 0.2 mg/l/6h/d or less.

2,6-Di-tert-butyl-p-cresol:

Assessment : No significant health effects observed in animals at concentra-

tions of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

Petrolatum:

Species : Rat

NOAEL : 5,000 mg/kg
Application Route : Ingestion
Exposure time : 2 yr



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

Zinc oxide:

Species : Rat, male NOAEL : 0.0015 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 3 Months

Method : OECD Test Guideline 413

Benzyl alcohol:

Species : Rat NOAEL : 1.072 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 28 Days

Method : OECD Test Guideline 412

2,6-Di-tert-butyl-p-cresol:

Species : Rat

NOAEL : 25 mg/kg

Application Route : Ingestion

Exposure time : 22 Months

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Product:

Ingestion : Symptoms: The absorption of this product into the body may

lead to the formation of methaemoglobine that, in sufficient concentration, causes cyanosis., May cause, Neurological disorders, Blood disorders, blood effects, central nervous sys-

tem effects, Methaemoglobinemia

Components:

Bismuth hydroxide nitrate oxide:

Ingestion : Target Organs: Blood

Symptoms: Methaemoglobinemia

Target Organs: Central nervous system Symptoms: Neurological disorders

12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Bismuth hydroxide nitrate oxide:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 137 mg/l



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 137 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 137

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): >

137 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Petrolatum:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

NOEL (Pseudokirchneriella subcapitata (green algae)): >=

100 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 10 mg/l

Exposure time: 21 d

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Zinc oxide:

Toxicity to fish : LC50 : > 0.1 - 1 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.136



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

plants mg/l

Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (green algae)): > 0.01

- 0.1 mg/l

Exposure time: 72 h

Remarks: Based on data from similar materials

M-Factor (Acute aquatic tox-

icity

Toxicity to fish (Chronic tox-

icity)

NOEC (Jordanella floridae (flagfish)): > 0.01 - 0.1 mg/l

Exposure time: 14 Weeks

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Ceriodaphnia dubia (water flea)): > 0.01 - 0.1 mg/l

Exposure time: 7 d

Remarks: Based on data from similar materials

M-Factor (Chronic aquatic

toxicity)

: 1

1

Benzyl alcohol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 460 mg/l

Exposure time: 96 h

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 230 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 770

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 310

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 51 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

2,6-Di-tert-butyl-p-cresol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 0.57 mg/l

Exposure time: 96 h

Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.48 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0.24

plants m

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.24

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox- :

icity)

Toxicity to fish (Chronic tox-

icity)

NOEC (Oryzias latipes (Japanese medaka)): 0.053 mg/l

NOEC (Daphnia magna (Water flea)): 0.316 mg/l

Exposure time: 30 d

Exposure time: 21 d

Method: OECD Test Guideline 210

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

M-Factor (Chronic aquatic

toxicity)

Toxicity to microorganisms : EC50: > 10,000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Persistence and degradability

Components:

Petrolatum:

Biodegradability : Result: Not readily biodegradable.

: 1

Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Benzyl alcohol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 92 - 96 % Exposure time: 14 d

2,6-Di-tert-butyl-p-cresol:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 4.5 % Exposure time: 28 d

Method: OECD Test Guideline 301C



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

Bioaccumulative potential

Components:

Zinc oxide:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)

Bioconcentration factor (BCF): 78 - 2,060

Benzyl alcohol:

Partition coefficient: n-

octanol/water

log Pow: 1.05

2,6-Di-tert-butyl-p-cresol:

Bioaccumulation : Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): 330 - 1,800

Partition coefficient: n-

octanol/water

: log Pow: 5.1

Mobility in soil

No data available

Hazardous to the ozone layer

Not applicable

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

UN/ID No. : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo

aircraft)

956

Packing instruction (passen: 956

ger aircraft)

Environmentally hazardous : yes

IMDG-Code

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

Refer to section 15 for specific national regulation.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

ERG Code : 171

15. REGULATORY INFORMATION

Related Regulations

Fire Service Law

Not applicable to dangerous materials / designated flammables.

Chemical Substance Control Law

Priority Assessment Chemical Substance

1 Horky Accessificate Chemical Capetanes	
Chemical name	Number
2,6-Di-tert-butyl-4-methylphenol	64

Industrial Safety and Health Law

Harmful Substances Prohibited from Manufacture

Not applicable



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

Harmful Substances Required Permission for Manufacture

Not applicable

Substances Prevented From Impairment of Health

Not applicable

Circular concerning Information on Chemicals having Mutagenicity - Annex 2: Information on Existing Chemicals having Mutagenicity

Not applicable

Circular concerning Information on Chemicals having Mutagenicity - Annex 1: Information on Notified Substances having Mutagenicity

Not applicable

Substances Subject to be Notified Names

Article 57-2 (Enforcement Order Table 9)

Chemical name	Concentration (%)	Remarks
Bismuth(III) hydroxide nitrate oxide	>=60 - <70	From April 1st, 2025
Petrolatum	>=20 - <30	From April 1st, 2026
Zinc oxide	>=1 - <10	-
Benzyl alcohol	>=1 - <10	-
2,6-Di-tert-butyl-4-cresol	>=0.1 - <1	-

Substances Subject to be Indicated Names

Article 57 (Enforcement Order Article 18)

Chemical name	Remarks
Bismuth(III) hydroxide nitrate oxide	From April 1st, 2025
Petrolatum	From April 1st, 2026
Zinc oxide	-
benzyl alcohol	-

Skin and Eye Damage Substances for PPE Requirements (ISHL MO Art. 594-2)

Chemical name	
benzvl alcohol	

Carcinogenic Substances (Article 577-2 of the Occupational Health and Safety Regulations)

Not applicable

Ordinance on Prevention of Hazards Due to Specified Chemical Substances

Not applicable

Ordinance on Prevention of Lead Poisoning

Not applicable

Ordinance on Prevention of Tetraalkyl Lead Poisoning

Not applicable

Ordinance on Prevention of Organic Solvent Poisoning

Not applicable

Enforcement Order of the Industrial Safety and Health Law - Attached table 1 (Dangerous Substances)

Not applicable



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

Poisonous and Deleterious Substances Control Law

Not applicable

Act on Confirmation, etc. of Release Amounts of Specific Chemical Substances in the Environment and Promotion of Improvements to the Management Thereof

Class I Designated Chemical Substances

Chemical name	Administration number	Concentration (%)
Zinc compounds, soluble / Zinc	1	4.0

High Pressure Gas Safety Act

Not applicable

Explosive Control Law

Not applicable

Vessel Safety Law

Miscellaneous dangerous substances and articles (Article 2 and 3 of rules on shipping and storage of dangerous goods and its Attached Table 1)

Aviation Law

Miscellaneous dangerous substances and articles (Article 194 of The Enforcement Rules of Aviation Law and its Attached Table 1)

Marine Pollution and Sea Disaster Prevention etc Law

Bulk transportation : Not classified as noxious liquid substance

Pack transportation : Classified as marine pollutant

Narcotics and Psychotropics Control Act

Narcotic or Psychotropic Raw Material (Export / Import Permission)

Not applicable

Specific Narcotic or Psychotropic Raw Material (Export / Import permission)

Not applicable

Waste Disposal and Public Cleansing Law

Industrial waste

The components of this product are reported in the following inventories:

AICS : not determined

DSL : not determined

IECSC : not determined

16. OTHER INFORMATION

In this SDS, if the concentration of substances subject to notification under the Industrial Safety and Health Law is indicated as a range, it includes cases where it is a trade secret.

Further information

Sources of key data used to compile the Safety Data

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

Sheet cy, http://echa.europa.eu/

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

JP ISHL OEL 577-2(2) : Concentration standard (Value set by the Minister of Health,

Labour and Welfare stipulated under the Ministerial Ordinance

Article 577-2(2))

JP OEL JSOH : Japan Society for Occupational Health. Recom-

mendation of Occupational Exposure Limits

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

JP ISHL OEL 577-2(2) / 8h- : 8-hour Occupational Exposure Limit-Mean

OEL-M

JP OEL JSOH / OEL-M : Occupational Exposure Limit-Mean JP OEL JSOH / OEL-C : Occupational Exposure Limit-Ceiling

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System



Bismuth Subnitrate Formulation

Version Revision Date: SDS Number: Date of last issue: 2024/04/06 13.0 2024/09/28 656842-00022 Date of first issue: 2016/05/02

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

JP / EN