

# **Cephalonium Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 3.4 30.11.2023 26977-00024 Date of first issue: 31.10.2014

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Cephalonium Formulation

Other means of identification : Cepravin Dry Cow (A003322)

Manufacturer or supplier's details

Company : MSD

Address : 50 Tuas West Drive

Singapore - Singapore 638408

Telephone : +1-908-740-4000

Emergency telephone number : 65 6697 2111 (24/7/365)

E-mail address : EHSDATASTEWARD@msd.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product Restrictions on use : Not applicable

#### 2. HAZARDS IDENTIFICATION

**GHS Classification** 

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

**GHS** label elements

Hazard pictograms :

Signal word : Danger

Hazard statements : H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Precautionary statements : Prevention:

P261 Avoid breathing mist or vapours.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves.



# **Cephalonium Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 3.4 30.11.2023 26977-00024 Date of first issue: 31.10.2014

P284 Wear respiratory protection.

#### Response:

P302 + P352 IF ON SKIN: Wash with plenty of water. P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

P342 + P311 If experiencing respiratory symptoms: Call a

POISON CENTER/ doctor.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

## Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

## Other hazards which do not result in classification

None known.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
White mineral oil (petroleum)	8042-47-5	>= 90 -<= 100
Cefalonium	5575-21-3	>= 2.5 -< 10
Hydroxyaluminum distearate	300-92-5	>= 1 -< 10

#### 4. FIRST AID MEASURES

In case of eye contact

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse. Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur.



# Cephalonium Formulation

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 3.4 30.11.2023 26977-00024 Date of first issue: 31.10.2014

Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reac-

tive airways dysfunction syndrome).

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

### 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical None known.

Unsuitable extinguishing

media

Specific hazards during fire-

fighting

Hazardous combustion prod-

ucts

: Carbon oxides

Nitrogen oxides (NOx)

Sulphur oxides Metal oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

Exposure to combustion products may be a hazard to health.

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can



# **Cephalonium Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 3.4 30.11.2023 26977-00024 Date of first issue: 31.10.2014

be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbant

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation. Advice on safe handling : Do not get on skin or clothing.

Avoid breathing mist or vapours.

Do not swallow.

Avoid contact with eyes.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Keep container tightly closed.

Already sensitised individuals, and those susceptible

to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respira-

tory irritants or sensitisers.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labelled containers.

Keep tightly closed.

Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis	
White mineral oil (petroleum)	8042-47-5	PEL (long term) (Mist)	5 mg/m3	SG OEL	
		PEL (short term) (Mist)	10 mg/m3	SG OEL	
		TWA (Inhal- able particu- late matter)	5 mg/m3	ACGIH	
Cefalonium	5575-21-3	TWA	2000 μg/m3 (OEB 1)	Internal	
	Further information: RSEN				



# **Cephalonium Formulation**

SDS Number: Date of last issue: 30.09.2023 Version Revision Date: 3.4 30.11.2023 26977-00024 Date of first issue: 31.10.2014

Hydroxyaluminum distearate	300-92-5	PEL (long term)	10 mg/m3	SG OEL
		TWA (Inhal- able particu- late matter)	10 mg/m3	ACGIH
		TWA (Respirable particulate matter)	3 mg/m3	ACGIH
		TWA (Respirable particulate matter)	1 mg/m3 (Aluminium)	ACGIH

**Engineering measures** Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection. Combined particulates and organic vapour type

Filter type

Material

Hand protection

Chemical-resistant gloves

Remarks Choose gloves to protect hands against chemicals depending

> on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the

end of workday.

Wear the following personal protective equipment: Eye protection

Safety glasses

Skin and body protection Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

If exposure to chemical is likely during typical use, provide Hygiene measures

eye flushing systems and safety showers close to the work-

ing place.

When using do not eat, drink or smoke.

Contaminated work clothing should not be allowed out of the

workplace.

Wash contaminated clothing before re-use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** suspension



# **Cephalonium Formulation**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.09.2023

 3.4
 30.11.2023
 26977-00024
 Date of first issue: 31.10.2014

Colour : off-white

Odour : odourless

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : No data available

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.



# **Cephalonium Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 3.4 30.11.2023 26977-00024 Date of first issue: 31.10.2014

Molecular weight : No data available

Particle size : No data available

### 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard. Chemical stability : Stable under normal conditions.

None known.

Possibility of hazardous reac-

tions

Conditions to avoid : None known.

Incompatible materials : None. Hazardous decomposition : No haz

products

No hazardous decomposition products are known.

### 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure

Skin contact Ingestion Eye contact

# Acute toxicity

Not classified based on available information.

#### **Components:**

### White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Cefalonium:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Hydroxyaluminum distearate:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg

Method: OECD Test Guideline 423

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.15 mg/l



# **Cephalonium Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 3.4 30.11.2023 26977-00024 Date of first issue: 31.10.2014

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

### Skin corrosion/irritation

Not classified based on available information.

### **Components:**

### White mineral oil (petroleum):

Species : Rabbit

Result : No skin irritation

## Hydroxyaluminum distearate:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 431

Remarks : Based on data from similar materials

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 439

Remarks : Based on data from similar materials

Result : No skin irritation

## Serious eye damage/eye irritation

Not classified based on available information.

## **Components:**

## White mineral oil (petroleum):

Species : Rabbit

Result : No eye irritation

## Hydroxyaluminum distearate:

Species : Bovine cornea

Method : OECD Test Guideline 437

Remarks : Based on data from similar materials

Result : No eye irritation

## Respiratory or skin sensitisation

### Skin sensitisation

May cause an allergic skin reaction.

## Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.



# **Cephalonium Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 3.4 30.11.2023 26977-00024 Date of first issue: 31.10.2014

### Components:

White mineral oil (petroleum):

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Cefalonium:

Exposure routes : Skin contact

Assessment : Probability or evidence of skin sensitisation in humans

Exposure routes : Inhalation

Assessment : May cause sensitisation by inhalation.

Hydroxyaluminum distearate:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

**Components:** 

White mineral oil (petroleum):

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Cefalonium:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Chromosome aberration test in vitro

Result: positive



# **Cephalonium Formulation**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.09.2023

 3.4
 30.11.2023
 26977-00024
 Date of first issue: 31.10.2014

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

**Application Route: Ingestion** 

Result: negative

Test Type: Unscheduled DNA synthesis (UDS) test with

mammalian liver cells in vivo

Species: Rat

Application Route: Ingestion

Result: negative

Hydroxyaluminum distearate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

**Components:** 

White mineral oil (petroleum):

Species : Rat
Application Route : Ingestion
Exposure time : 24 Months
Result : negative

Reproductive toxicity

Not classified based on available information.

**Components:** 

White mineral oil (petroleum):

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: Skin contact

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion

Result: negative



# **Cephalonium Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 3.4 30.11.2023 26977-00024 Date of first issue: 31.10.2014

Cefalonium:

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

**Application Route: Ingestion** 

Result: negative

Hydroxyaluminum distearate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Method: OECD Test Guideline 416

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Method: OECD Test Guideline 416

Result: negative

Remarks: Based on data from similar materials

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

**Components:** 

White mineral oil (petroleum):

Species : Rat
LOAEL : 160 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat LOAEL : >= 1 mg/l

Application Route : inhalation (dust/mist/fume)

Exposure time : 4 Weeks

Method : OECD Test Guideline 412

**Aspiration toxicity** 

Not classified based on available information.



# **Cephalonium Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 3.4 30.11.2023 26977-00024 Date of first issue: 31.10.2014

#### 12. ECOLOGICAL INFORMATION

## **Ecotoxicity**

### **Components:**

White mineral oil (petroleum):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (green algae)): 100

mg/

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l

Exposure time: 28 d

Toxicity to daphnia and other : aquatic invertebrates (Chron-

aquatic invertebrat

ic toxicity)

NOEC (Daphnia magna (Water flea)): 1,000 mg/l

Exposure time: 21 d

Cefalonium:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: No toxicity at the limit of solubility

Toxicity to algae/aquatic

plants

NOEC (Anabaena flos-aquae (cyanobacterium)): 0.213 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

ErC50 (Anabaena flos-aquae (cyanobacterium)): 0.315 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox-

Toxicity to microorganisms

city)

)

EC50: > 1,000 mg/l

1

Exposure time: 3 h

Method: OECD Test Guideline 209



# **Cephalonium Formulation**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.09.2023

 3.4
 30.11.2023
 26977-00024
 Date of first issue: 31.10.2014

NOEC: 0.48 mg/l Exposure time: 3 h

Method: OECD Test Guideline 209

Hydroxyaluminum distearate:

**Ecotoxicology Assessment** 

Chronic aquatic toxicity : No toxicity at the limit of solubility

Persistence and degradability

**Components:** 

White mineral oil (petroleum):

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 31 % Exposure time: 28 d

Cefalonium:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 32 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Hydroxyaluminum distearate:

Biodegradability : Result: Readily biodegradable.

Remarks: Based on data from similar materials

**Bioaccumulative potential** 

Components:

Cefalonium:

Partition coefficient: n- : log Pow: 0.188

octanol/water

Hydroxyaluminum distearate:

Partition coefficient: n- : log Pow: 15.088 octanol/water : Remarks: Calculation

Mobility in soil
No data available

Other adverse effects

No data available



# **Cephalonium Formulation**

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 3.4 30.11.2023 26977-00024 Date of first issue: 31.10.2014

#### 13. DISPOSAL CONSIDERATIONS

**Disposal methods** 

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

### 14. TRANSPORT INFORMATION

### International Regulations

**UNRTDG** 

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo : Not applicable

aircraft)

Packing instruction (passen- : No

ger aircraft)

Not applicable

**IMDG-Code** 

UN number Not applicable Proper shipping name Not applicable Class Not applicable Subsidiary risk Not applicable Not applicable Packing group Labels Not applicable **EmS Code** Not applicable Not applicable Marine pollutant

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Special precautions for user

Not applicable



# Cephalonium Formulation

Version Revision Date: SDS Number: Date of last issue: 30.09.2023 3.4 30.11.2023 26977-00024 Date of first issue: 31.10.2014

### 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Workplace Safety and Health Act and Workplace Safety and Health (General Provisions) Regulations: This product is subjected to the SDS, labelling, PEL and other requirements in the Act/Regulations.

Environmental Protection and Management Act and

Environmental Protection and Management (Hazard-

ous Substances) Regulations

Fire Safety (Petroleum and Flammable Materials)

Regulations

Not applicable

Not applicable

The components of this product are reported in the following inventories:

AICS : not determined

DSL : not determined

IECSC : not determined

#### 16. OTHER INFORMATION

Revision Date : 30.11.2023

**Further information** 

Sources of key data used to compile the Safety Data

Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

SG OEL : Singapore. Workplace Safety and Health (General Provisions)

Regulations - First Schedule Permissible Exposure Limits of

Toxic Substances.

ACGIH / TWA : 8-hour, time-weighted average

SG OEL / PEL (long term) : Permissible Exposure Level (PEL) Long Term SG OEL / PEL (short term) : Permissible Exposure Level (PEL) Short Term

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with



# Cephalonium Formulation

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 30.09.2023

 3.4
 30.11.2023
 26977-00024
 Date of first issue: 31.10.2014

x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods: vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

SG / EN