

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Dichlofenthion Formulation

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Veterinary product

Recommended restrictions on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : MSD
Kilsheelan
Clonmel Tipperary, IE

Telephone : 353-51-601000

E-mail address of person responsible for the SDS : EHSDATASTEWARD@msd.com

1.4 Emergency telephone number

1-908-423-6000

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Germ cell mutagenicity, Category 2	H341: Suspected of causing genetic defects.
Carcinogenicity, Category 1A	H350: May cause cancer if swallowed.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure, Category 1	H370: Causes damage to organs.
Specific target organ toxicity - single exposure, Category 3	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006




Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Category 1
Long-term (chronic) aquatic hazard, Category 1 H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms : 

Signal word : Danger

Hazard statements : H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H341 Suspected of causing genetic defects.
H350 May cause cancer if swallowed.
H361d Suspected of damaging the unborn child.
H370 Causes damage to organs.
H373 May cause damage to organs through prolonged or repeated exposure.
H410 Very toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH071 Corrosive to the respiratory tract.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.
P391 Collect spillage.

Hazardous components which must be listed on the label:

Tar, wood
Rosin
Tar, coal
Ethylbenzene
Dichlofenthion (ISO)
Sodium hydroxide
Phenol

Additional Labelling

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Restricted to professional users.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Tar, wood	91722-33-7 294-436-0	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1B; H317 Aquatic Chronic 3; H412	>= 10 - < 20
Rosin	8050-09-7 232-475-7 650-015-00-7	Skin Sens. 1; H317	>= 10 - < 20
Tar, coal	8007-45-2 232-361-7 648-081-00-7	Acute Tox. 4; H302 Eye Dam. 1; H318 Skin Sens. 1; H317 Muta. 2; H341 Carc. 1A; H350 STOT SE 1; H370 (Nervous system) STOT SE 3; H335 STOT RE 2; H373 (Respiratory Tract) Aquatic Chronic 2; H411 Acute toxicity estimate Acute oral toxicity: 1,700 mg/kg	>= 10 - < 20

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Ethylbenzene	100-41-4 202-849-4 601-023-00-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	$\geq 2.5 - < 10$
		Acute toxicity estimate	
		Acute inhalation toxicity (vapour): 17.8 mg/l	
Xylene	1330-20-7 215-535-7 601-022-00-9	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	$\geq 2.5 - < 10$
		Acute toxicity estimate	
		Acute inhalation toxicity (vapour): 11 mg/l Acute dermal toxicity: 1,100 mg/kg	
Dichlofenthion (ISO)	97-17-6 202-564-5 015-068-00-7	Acute Tox. 3; H301 Acute Tox. 4; H332 Acute Tox. 3; H311 Repr. 2; H361d STOT RE 1; H372 (Nervous system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410	$\geq 3 - < 10$
		M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	
Sodium hydroxide	1310-73-2 215-185-5 011-002-00-6	Met. Corr. 1; H290 Skin Corr. 1A; H314 Eye Dam. 1; H318 EUH014, EUH071	$\geq 2 - < 3$

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

		<hr/> specific concentration limit Skin Corr. 1A; H314 >= 5 % Skin Corr. 1B; H314 2 - < 5 % Skin Irrit. 2; H315 0.5 - < 2 % Eye Irrit. 2; H319 0.5 - < 2 % EUH071 >= 2 %	
Phenol	108-95-2 203-632-7 604-001-00-2	Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Muta. 2; H341 STOT RE 2; H373 (Central nervous system, Kidney, Liver, Skin) Aquatic Chronic 2; H411 EUH071 <hr/> specific concentration limit Skin Corr. 1B; H314 >= 3 % Skin Irrit. 2; H315 1 - < 3 % Eye Irrit. 2; H319 1 - < 3 % EUH071 >= 3 % <hr/> Acute toxicity estimate Acute oral toxicity: 140 - 290 mg/kg Acute inhalation toxicity (dust/mist): > 0.9 mg/l Acute dermal toxicity: 300 mg/kg	>= 1 - < 2.5
m-Cresol	108-39-4 203-577-9 604-004-00-9	Acute Tox. 3; H301 Acute Tox. 3; H311 Skin Corr. 1B; H314	>= 1 - < 2.5

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

		Eye Dam. 1; H318 Aquatic Chronic 3; H412 EUH071	
		Acute toxicity estimate Acute oral toxicity: 121 mg/kg Acute dermal toxicity: 301 mg/kg	
p-Cresol	106-44-5 203-398-6 604-004-00-9	Acute Tox. 3; H301 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Aquatic Chronic 3; H412 EUH071	>= 1 - < 2.5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention immediately.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention immediately.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 01.10.2022
4.0	04.04.2023	1560319-00015	Date of first issue: 14.04.2017

If swallowed : If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control centre immediately.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes digestive tract burns.

Harmful if swallowed.
May be fatal if swallowed and enters airways.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
Suspected of causing genetic defects.
May cause cancer if swallowed.
Suspected of damaging the unborn child.
Causes damage to organs.
May cause damage to organs through prolonged or repeated exposure.
Corrosive to the respiratory tract.
Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Metal oxides
Nitrogen oxides (NO_x)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 01.10.2022
4.0	04.04.2023	1560319-00015	Date of first issue: 14.04.2017

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
-

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

- Environmental precautions : Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 01.10.2022
4.0	04.04.2023	1560319-00015	Date of first issue: 14.04.2017

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.
- Advice on safe handling : Do not get on skin or clothing.
Do not breathe vapours.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Already sensitised individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitisers.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.
The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.
- Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Flammable solids
Pyrophoric liquids
Pyrophoric solids

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases
Explosives
Gases
Very acutely toxic substances and mixtures

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Rosin	8050-09-7	OELV - 8 hrs (TWA)	0.05 mg/m ³ (airborne total resin acid)	IE OEL
		Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis		
		OELV - 15 min (STEL)	0.15 mg/m ³ (airborne total resin acid)	IE OEL
		Further information: Chemical agents which following exposure may cause sensitisation of the respiratory tract and lead to asthma, rhinitis or extrinsic allergic alveolitis		
Ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m ³	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	200 ppm 884 mg/m ³	2000/39/EC
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		OELV - 8 hrs (TWA)	100 ppm 442 mg/m ³	IE OEL
		Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body		
		OELV - 15 min (STEL)	200 ppm 884 mg/m ³	IE OEL
		Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body		
Xylene	1330-20-7	OELV - 8 hrs (TWA)	50 ppm 221 mg/m ³	IE OEL
		Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body		
		OELV - 15 min (STEL)	100 ppm 442 mg/m ³	IE OEL
		Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
 Date of first issue: 14.04.2017

		TWA	50 ppm 221 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
Dichlofenthion (ISO)	97-17-6	TWA	20 µg/m ³ (OEB 3)	Internal
	Further information: Skin			
		Wipe limit	200 µg/100 cm ²	Internal
Sodium hydroxide	1310-73-2	OELV - 15 min (STEL)	2 mg/m ³	IE OEL
Phenol	108-95-2	TWA	2 ppm 8 mg/m ³	2009/161/EU
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	4 ppm 16 mg/m ³	2009/161/EU
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		OELV - 15 min (STEL)	4 ppm 16 mg/m ³	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
		OELV - 8 hrs (TWA)	2 ppm 8 mg/m ³	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
m-Cresol	108-39-4	OELV - 8 hrs (TWA)	5 ppm 22 mg/m ³	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			
p-Cresol	106-44-5	OELV - 8 hrs (TWA)	5 ppm 22 mg/m ³	IE OEL
	Further information: Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Sodium hydroxide	Consumers	Inhalation	Long-term local effects	1 mg/m ³
	Workers	Inhalation	Long-term local effects	1 mg/m ³
Tar, wood	Workers	Inhalation		70.53 mg/m ³
	Consumers	Inhalation		355.56 mg/m ³
	Consumers	Ingestion		10 mg/kg bw/day
Phenol	Workers	Inhalation	Long-term systemic effects	8 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version
4.0

Revision Date:
04.04.2023

SDS Number:
1560319-00015

Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

	Workers	Inhalation	Acute local effects	16 mg/m ³
	Workers	Skin contact	Long-term systemic effects	1.23 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1.32 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	0.4 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0.4 mg/kg bw/day
m-Cresol	Workers	Inhalation	Long-term systemic effects	3.5 mg/m ³
	Workers	Inhalation	Acute systemic effects	343 mg/m ³
	Workers	Skin contact	Long-term systemic effects	0.5 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	1.47 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.75 mg/m ³
	Consumers	Inhalation	Acute systemic effects	222 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	0.25 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	0.74 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0.25 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	0.74 mg/kg bw/day
p-Cresol	Workers	Inhalation	Long-term systemic effects	3.5 mg/m ³
	Workers	Inhalation	Acute systemic effects	7 mg/m ³
	Workers	Skin contact	Long-term systemic effects	0.5 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	1 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.75 mg/m ³
	Consumers	Inhalation	Acute systemic effects	1.5 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	0.25 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	0.5 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0.25 mg/kg bw/day
Xylene	Workers	Inhalation	Long-term systemic effects	221 mg/m ³
	Workers	Inhalation	Acute systemic effects	442 mg/m ³
	Workers	Inhalation	Long-term local effects	221 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

	Workers	Inhalation	Acute local effects	442 mg/m ³
	Workers	Skin contact	Long-term systemic effects	212 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	65.3 mg/m ³
	Consumers	Inhalation	Acute systemic effects	260 mg/m ³
	Consumers	Inhalation	Long-term local effects	65.3 mg/m ³
	Consumers	Inhalation	Acute local effects	260 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	12.5 mg/kg bw/day
Ethylbenzene	Workers	Inhalation	Long-term systemic effects	77 mg/m ³
	Workers	Inhalation	Acute local effects	293 mg/m ³
	Workers	Skin contact	Long-term systemic effects	180 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	15 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	1.6 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Tar, wood	Fresh water	0.003 mg/l
	Marine water	0.0003 mg/l
	Fresh water sediment	0.006 mg/kg dry weight (d.w.)
	Marine sediment	0.0006 mg/kg dry weight (d.w.)
	Soil	0.002 mg/kg dry weight (d.w.)
Phenol	Fresh water	0.0077 mg/l
	Marine water	0.00077 mg/l
	Intermittent use/release	0.031 mg/l
	Sewage treatment plant	2.1 mg/l
	Fresh water sediment	0.0915 mg/kg
	Marine sediment	0.00915 mg/kg
m-Cresol	Soil	0.136 mg/kg
	Fresh water	0.1 mg/l
	Marine water	0.01 mg/l
	Intermittent use/release	0.076 mg/l
	Sewage treatment plant	1.14 mg/l
	Fresh water sediment	0.71 mg/kg
p-Cresol	Marine sediment	0.071 mg/kg
	Soil	0.0831 mg/kg
	Fresh water	0.1 mg/l
	Marine water	0.01 mg/l
	Intermittent use/release	0.044 mg/l
	Sewage treatment plant	1.65 mg/l
	Fresh water sediment	0.85 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

	Marine sediment	0.085 mg/kg
	Soil	0.111 mg/kg
Xylene	Fresh water	0.327 mg/l
	Intermittent use/release	0.327 mg/l
	Marine water	0.327 mg/l
	Sewage treatment plant	6.58 mg/l
	Fresh water sediment	12.46 mg/kg dry weight (d.w.)
	Marine sediment	12.46 mg/kg dry weight (d.w.)
	Soil	2.31 mg/kg dry weight (d.w.)
Ethylbenzene	Fresh water	0.1 mg/l
	Freshwater - intermittent	0.1 mg/l
	Marine water	0.01 mg/l
	Sewage treatment plant	9.6 mg/l
	Fresh water sediment	13.7 mg/kg dry weight (d.w.)
	Marine sediment	1.37 mg/kg dry weight (d.w.)
	Soil	2.68 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	20 mg/kg food

8.2 Exposure controls

Engineering measures

Use appropriate engineering controls and manufacturing technologies to control airborne concentrations (e.g., drip-less quick connections).

All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment.

Containment technologies suitable for controlling compounds are required to control at source and to prevent migration of the compound to uncontrolled areas (e.g., open-face containment devices).

Minimize open handling.

Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Eye/face protection : Wear safety glasses with side shields or goggles.
If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles.
Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or aerosols.

Hand protection

Material : Chemical-resistant gloves

Remarks : Consider double gloving. Take note that the product is flammable, which may impact the selection of hand protection.

Skin and body protection : Work uniform or laboratory coat.
Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 01.10.2022
4.0	04.04.2023	1560319-00015	Date of first issue: 14.04.2017

Respiratory protection	:	Use appropriate degowning techniques to remove potentially contaminated clothing. If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection. Equipment should conform to I.S. EN 14387
Filter type	:	Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	viscous liquid
Colour	:	dark, brown
Odour	:	strong
Odour Threshold	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Not applicable
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	30 °C
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	Not applicable
Viscosity	:	
Viscosity, kinematic	:	No data available
Solubility(ies)	:	
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Vapour pressure	:	No data available
Relative density	:	No data available
Density	:	1,009 - 1,051 g/cm ³ (20 °C)
Relative vapour density	:	No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 01.10.2022
4.0	04.04.2023	1560319-00015	Date of first issue: 14.04.2017

Particle characteristics
Particle size : Not applicable

9.2 Other information

Explosives : Not explosive
Oxidizing properties : The substance or mixture is not classified as oxidizing.
Evaporation rate : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Flammable liquid and vapour.
Vapours may form explosive mixture with air.
Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 1,713 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

Tar, wood:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity

Rosin:

Acute oral toxicity : LD50 (Rat): 2,800 mg/kg
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Tar, coal:

Acute oral toxicity : LD50 (Rat): 1,700 mg/kg
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg
Acute inhalation toxicity : LC50 (Rat): 17.8 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Xylene:

Acute oral toxicity : LD50 (Rat): 3,523 mg/kg
Method: Directive 67/548/EEC, Annex V, B.1.
Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement
Remarks: Based on national or regional regulation.
Acute dermal toxicity : Acute toxicity estimate: 1,100 mg/kg
Method: Expert judgement
Remarks: Based on national or regional regulation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Dichlofenthion (ISO):

Acute oral toxicity : LD50 (Rat): 172 mg/kg
LD50 (Rat): 270 mg/kg
Acute inhalation toxicity : LC50 (Rat): 1.75 mg/l
Acute dermal toxicity : LD50 (Rat): 355 mg/kg
LD50 (Rabbit): 6,000 mg/kg

Sodium hydroxide:

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Phenol:

Acute oral toxicity : LD50 (Rat): 650 mg/kg
Method: OECD Test Guideline 401
Acute toxicity estimate (Humans): 140 - 290 mg/kg
Method: Expert judgement
Acute inhalation toxicity : LC0 (Rat): 0.9 mg/l
Exposure time: 8 h
Test atmosphere: dust/mist
Assessment: Corrosive to the respiratory tract.
Acute toxicity estimate (Humans): > 0.9 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgement
Acute dermal toxicity : LD50 (Rabbit): 660 mg/kg
Method: OECD Test Guideline 402
Acute toxicity estimate (Humans): 300 mg/kg
Method: Expert judgement

m-Cresol:

Acute oral toxicity : LD50 (Rat): 121 mg/kg
Remarks: Based on data from similar materials
Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.
Acute dermal toxicity : LD50 (Rabbit): 301 mg/kg
Remarks: Based on data from similar materials

p-Cresol:

Acute oral toxicity : LD50 (Rat): 172 - 250 mg/kg
Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Acute dermal toxicity : LD50 (Rabbit): 213 - 426 mg/kg

Skin corrosion/irritation

Causes severe burns.

Components:

Tar, wood:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 431

Result : Skin irritation

Rosin:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Tar, coal:

Species : Rabbit
Result : Mild skin irritation

Xylene:

Species : Rabbit
Result : Skin irritation

Dichlofenthion (ISO):

Result : Mild skin irritation
Remarks : Based on data from similar materials

Sodium hydroxide:

Result : Corrosive after 3 minutes or less of exposure

Phenol:

Species : Rabbit
Result : Corrosive after 3 minutes to 1 hour of exposure

m-Cresol:

Species : Rabbit
Result : Corrosive after 3 minutes to 1 hour of exposure

p-Cresol:

Species : Rabbit
Result : Corrosive after 3 minutes to 1 hour of exposure

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

Tar, wood:

Result : Irritation to eyes, reversing within 7 days

Rosin:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Tar, coal:

Species : Human
Result : Irreversible effects on the eye

Xylene:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Sodium hydroxide:

Result : Irreversible effects on the eye
Remarks : Based on skin corrosivity.

Phenol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irreversible effects on the eye

m-Cresol:

Species : Rabbit
Result : Irreversible effects on the eye

p-Cresol:

Species : Rabbit
Result : Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

Tar, wood:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : positive

Assessment : Probability or evidence of low to moderate skin sensitisation rate in humans

Rosin:

Assessment : Probability or evidence of skin sensitisation in humans
Remarks : Based on national or regional regulation.

Tar, coal:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : positive
Remarks : Based on data from similar materials

Assessment : Probability or evidence of skin sensitisation in humans

Xylene:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Result : negative

Dichlofenthion (ISO):

Exposure routes : Dermal
Assessment : Does not cause skin sensitisation.
Result : Weak sensitizer
Remarks : Based on data from similar materials

Sodium hydroxide:

Test Type : Human repeat insult patch test (HRIPT)
Exposure routes : Skin contact
Result : negative

Phenol:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative

p-Cresol:

Test Type : Draize Test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Germ cell mutagenicity

Suspected of causing genetic defects.

Components:

Tar, wood:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Rosin:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Tar, coal:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: positive
Remarks: Based on data from similar materials

Germ cell mutagenicity- Assessment : Positive result(s) from in vivo non-mammalian somatic cell mutagenicity tests, supported by positive results from in vitro mutagenicity assays.
Remarks: Based on national or regional regulation.

Ethylbenzene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with mammalian liver cells in vivo

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Species: Mouse
Application Route: Inhalation
Method: OECD Test Guideline 486
Result: negative

Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-
malian cells
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Skin contact
Result: negative

Phenol:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: positive
Remarks: Annex VI From 1272/2008

Germ cell mutagenicity- As-
sessment : Positive result(s) from in vivo mammalian somatic cell muta-
genicity tests.

m-Cresol:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive

Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow
cytogenetic test, chromosomal analysis)
Species: Mouse

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Application Route: Ingestion
Method: OECD Test Guideline 475
Result: negative

p-Cresol:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 478
Result: negative

Carcinogenicity

May cause cancer if swallowed.

Components:

Tar, coal:

Species : Mouse
Application Route : Ingestion
Exposure time : 2 Years
Result : positive

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (oral)
Remarks: Based on national or regional regulation.

Ethylbenzene:

Species : Rat
Application Route : inhalation (vapour)
Exposure time : 104 weeks
Result : positive
Remarks : The mechanism or mode of action may not be relevant in humans.

Xylene:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Phenol:

Species : Mouse
Application Route : Ingestion
Exposure time : 103 weeks

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Method : OECD Test Guideline 451
Result : negative

m-Cresol:

Species : Mouse, males
Application Route : Ingestion
Exposure time : 105 weeks
Result : equivocal
Remarks : Based on data from similar materials

Species : Mouse, female
Application Route : Ingestion
Exposure time : 106 - 107 weeks
Result : positive
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

p-Cresol:

Species : Mouse
Application Route : Ingestion
Exposure time : 106 - 107 weeks
Result : negative
Remarks : Based on data from similar materials

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

Rosin:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Ethylbenzene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 414
Result: negative

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Result: negative

Dichlofenthion (ISO):

Effects on foetal development : Test Type: Development
Species: Mouse
Application Route: Intraperitoneal
Developmental Toxicity: LOAEL: 80 mg/kg body weight
Result: Reduced foetal weight, Embryotoxic effects.
Remarks: Based on data from similar materials

Test Type: Development
Species: Rat
Application Route: Intraperitoneal
Developmental Toxicity: LOAEL: 10 mg/kg body weight
Result: Reduced foetal weight, Embryotoxic effects., No teratogenic effects
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Suspected of damaging the unborn child.

Phenol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

m-Cresol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Species: Rat
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Prenatal development toxicity study (teratogenicity)
Species: Rat
Application Route: Ingestion
Result: negative

p-Cresol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT - single exposure

May cause respiratory irritation.
Causes damage to organs.
Corrosive to the respiratory tract.

Components:

Tar, coal:

Exposure routes : Ingestion
Target Organs : Nervous system
Assessment : Shown to produce significant health effects in animals at concentrations of 300 mg/kg bw or less.

Xylene:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:

Tar, coal:

Target Organs : Respiratory Tract
Assessment : Shown to produce significant health effects in animals at concentrations of >0.02 to 0.2 mg/l/6h/d.

Exposure routes : inhalation (dust/mist/fume)
Target Organs : Respiratory Tract
Assessment : Shown to produce significant health effects in animals at concentrations of >0.02 to 0.2 mg/l/6h/d.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Ethylbenzene:

Exposure routes : inhalation (vapour)
Target Organs : Auditory system
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Xylene:

Exposure routes : inhalation (vapour)
Target Organs : Auditory system
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Dichlofenthion (ISO):

Target Organs : Nervous system
Assessment : Causes damage to organs through prolonged or repeated exposure.
Remarks : Based on human experience.

Phenol:

Target Organs : Central nervous system, Kidney, Liver, Skin
Assessment : May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

Rosin:

Species : Rat, male
NOAEL : 335 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

Ethylbenzene:

Species : Rat
LOAEL : 0.868 mg/l
Application Route : inhalation (vapour)
Exposure time : 13 Weeks

Species : Rat
NOAEL : 75 mg/kg
LOAEL : 250 mg/kg
Application Route : Ingestion
Method : OECD Test Guideline 408

Xylene:

Species : Rat
LOAEL : > 0.2 - 1 mg/l
Application Route : inhalation (vapour)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Exposure time : 13 Weeks
Remarks : Based on data from similar materials

Species : Rat
LOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Dichlofenthion (ISO):

Species : Rat
NOAEL : 0.75 mg/kg
Application Route : Oral
Exposure time : 90 d

Species : Dog
NOAEL : 0.75 mg/kg
Application Route : Oral
Exposure time : 90 d

Phenol:

Species : Rat
LOAEL : 300 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

Species : Rat
NOAEL : ≥ 0.1 mg/l
Application Route : inhalation (vapour)
Exposure time : 74 Days

Species : Rabbit
LOAEL : 260 mg/kg
Application Route : Skin contact
Exposure time : 18 Days

m-Cresol:

Species : Rat
NOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks
Method : OECD Test Guideline 408

p-Cresol:

Species : Rat
NOAEL : 50 mg/kg
LOAEL : 175 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Components:

Ethylbenzene:

|| The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Xylene:

|| The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Experience with human exposure

Components:

Dichlofenthion (ISO):

|| Skin contact : Symptoms: irritating, central nervous system effects, sweating
Remarks: Can be absorbed through skin.
May cause sensitisation by skin contact.

|| Eye contact : Symptoms: constriction of pupils, central nervous system effects

|| Ingestion : Symptoms: Nausea, Diarrhoea, Vomiting, sweating, Lachrymation, constriction of pupils, Central nervous system depression, Gastrointestinal disturbance, bronchospasm, central nervous system effects, Oedema

SECTION 12: Ecological information

12.1 Toxicity

Components:

Tar, wood:

|| Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 28 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 17 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

EC10 (Desmodesmus subspicatus (green algae)): 14 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Rosin:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 1 - 10 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 911 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Raphidocelis subcapitata (freshwater green alga)): > 1,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

NOELR (Raphidocelis subcapitata (freshwater green alga)): 1,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): > 10,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Tar, coal:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 250 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 2.8 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): 36 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOELR (Desmodesmus subspicatus (green algae)): 5 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Ethylbenzene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.8 - 2.4 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 3.6 mg/l
Exposure time: 96 h

NOEC (Pseudokirchneriella subcapitata (green algae)): 3.4 mg/l
Exposure time: 96 h

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 96 mg/l
Exposure time: 24 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.96 mg/l
Exposure time: 7 d
Species: Ceriodaphnia dubia (water flea)

Xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13.5 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): 10 mg/l
Exposure time: 72 h

Toxicity to microorganisms : NOEC : > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC: > 0.1 - < 1 mg/l
Exposure time: 35 d
Species: Danio rerio (zebra fish)
Method: OECD Test Guideline 210
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL10: > 1 - 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Dichlofenthion (ISO):

Toxicity to fish : LC50 (No species specified): 0.64 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

LC50 (Lepomis macrochirus (Bluegill sunfish)): 1.23 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.0011 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

M-Factor (Acute aquatic toxicity) : 100

M-Factor (Chronic aquatic toxicity) : 100

Phenol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 24.9 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 3.1 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 61.1 mg/l
Exposure time: 96 h

Toxicity to microorganisms : IC50 (Nitrosomonas sp.): 21 mg/l
Exposure time: 24 h

Toxicity to fish (Chronic toxicity) : NOEC: 0.077 mg/l
Exposure time: 60 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Exposure time: 16 d
Species: Daphnia magna (Water flea)

m-Cresol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 8.6 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia pulex (Water flea)): > 99.5 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Toxicity to fish (Chronic toxicity) : NOEC: 1.35 mg/l
Exposure time: 32 d
Species: Pimephales promelas (fathead minnow)
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Remarks: Based on data from similar materials

p-Cresol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 7.4 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 7.7 mg/l
Exposure time: 48 h
Method: DIN 38412

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 7.8 mg/l
Exposure time: 48 h
EC10 (Desmodesmus subspicatus (green algae)): 2.3 mg/l
Exposure time: 48 h

Toxicity to microorganisms : IC50 (Nitrosomonas sp.): 260 mg/l
Exposure time: 24 h

Toxicity to fish (Chronic toxicity) : NOEC: 1.35 mg/l
Exposure time: 32 d
Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Components:

Tar, wood:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 47 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Rosin:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 71 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Ethylbenzene:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 - 80 %
Exposure time: 28 d

Xylene:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 70 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Phenol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 62 %
Exposure time: 10 d
Method: OECD Test Guideline 301C

m-Cresol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

p-Cresol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Exposure time: 8 d

12.3 Bioaccumulative potential

Components:

Tar, wood:

Partition coefficient: n-octanol/water : log Pow: 0.2 - 2.02

Rosin:

Partition coefficient: n-octanol/water : log Pow: > 3 - 6.2
Method: OECD Test Guideline 117

Tar, coal:

Partition coefficient: n-octanol/water : Remarks: No data available

Ethylbenzene:

Partition coefficient: n-octanol/water : log Pow: 3.6

Xylene:

Partition coefficient: n-octanol/water : log Pow: 3.16
Remarks: Calculation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

||

Dichlofenthion (ISO):

|| Partition coefficient: n-octanol/water : log Pow: 5.14

Phenol:

|| Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): 17.5
Method: OECD Test Guideline 305

|| Partition coefficient: n-octanol/water : log Pow: 1.47

m-Cresol:

|| Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 17 - 20

|| Partition coefficient: n-octanol/water : log Pow: 1.96

p-Cresol:

|| Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 17 - 20
Remarks: Based on data from similar materials

|| Partition coefficient: n-octanol/water : log Pow: 1.94

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities. Do not dispose of waste into sewer.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number or ID number

ADN	:	UN 2920
ADR	:	UN 2920
RID	:	UN 2920
IMDG	:	UN 2920
IATA	:	UN 2920

14.2 UN proper shipping name

ADN	:	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Sodium hydroxide, Ethylbenzene)
ADR	:	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Sodium hydroxide, Ethylbenzene)
RID	:	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Sodium hydroxide, Ethylbenzene)
IMDG	:	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Sodium hydroxide, Ethylbenzene, Dichlofenthion (ISO))
IATA	:	Corrosive liquid, flammable, n.o.s. (Sodium hydroxide, Ethylbenzene)

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 8	3
ADR	: 8	3
RID	: 8	3
IMDG	: 8	3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

IATA : 8 3

14.4 Packing group

ADN

Packing group : II
Classification Code : CF1
Hazard Identification Number : 83
Labels : 8 (3)

ADR

Packing group : II
Classification Code : CF1
Hazard Identification Number : 83
Labels : 8 (3)
Tunnel restriction code : (D/E)

RID

Packing group : II
Classification Code : CF1
Hazard Identification Number : 83
Labels : 8 (3)

IMDG

Packing group : II
Labels : 8 (3)
EmS Code : F-E, S-C

IATA (Cargo)

Packing instruction (cargo aircraft) : 855
Packing instruction (LQ) : Y840
Packing group : II
Labels : Corrosive, Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 851
Packing instruction (LQ) : Y840
Packing group : II
Labels : Corrosive, Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : If you intend to use this product as tattoo ink, please contact your vendor.

Tar, coal (Number on list 28)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
H3	STOT SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE	50 t	200 t
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.			
E1	ENVIRONMENTAL HAZARDS	100 t	200 t
P5c	FLAMMABLE LIQUIDS	5,000 t	50,000 t

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

AICS : not determined

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 01.10.2022
4.0	04.04.2023	1560319-00015	Date of first issue: 14.04.2017

DSL : not determined

IECSC : not determined

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H290 : May be corrosive to metals.
H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H304 : May be fatal if swallowed and enters airways.
H311 : Toxic in contact with skin.
H312 : Harmful in contact with skin.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H331 : Toxic if inhaled.
H332 : Harmful if inhaled.
H335 : May cause respiratory irritation.
H341 : Suspected of causing genetic defects.
H350 : May cause cancer if swallowed.
H361d : Suspected of damaging the unborn child.
H370 : Causes damage to organs.
H372 : Causes damage to organs through prolonged or repeated exposure.
H373 : May cause damage to organs through prolonged or repeated exposure.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.
EUH014 : Reacts violently with water.
EUH071 : Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Carc. : Carcinogenicity
Eye Dam. : Serious eye damage

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version 4.0 Revision Date: 04.04.2023 SDS Number: 1560319-00015 Date of last issue: 01.10.2022
Date of first issue: 14.04.2017

Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Met. Corr.	:	Corrosive to metals
Muta.	:	Germ cell mutagenicity
Repr.	:	Reproductive toxicity
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2009/161/EU	:	Europe. COMMISSION DIRECTIVE 2009/161/EU establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC
IE OEL	:	Ireland. List of Chemical Agents and Occupational Exposure Limit Values - Schedule 1
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2009/161/EU / TWA	:	Limit Value - eight hours
2009/161/EU / STEL	:	Short term exposure limit
IE OEL / OELV - 8 hrs (TWA)	:	Occupational exposure limit value (8-hour reference period)
IE OEL / OELV - 15 min (STEL)	:	Occupational exposure limit value (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet;

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Dichlofenthion Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 01.10.2022
4.0	04.04.2023	1560319-00015	Date of first issue: 14.04.2017

SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Flam. Liq. 3	H226
Acute Tox. 4	H302
Skin Corr. 1B	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Muta. 2	H341
Carc. 1A	H350
Repr. 2	H361d
STOT SE 1	H370
STOT SE 3	H335
STOT RE 2	H373
Asp. Tox. 1	H304
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Based on product data or assessment
Calculation method
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

IE / EN