

Flumethrin (1%) Formulation

Version 4.1	Revision Date: 30.09.2023		S Number: 19087-00015	Date of last issue: 04.04.2023 Date of first issue: 25.02.2019
SECTION	1. IDENTIFICATION			
Produ	uct name	:	Flumethrin (1%)	Formulation
Manu	facturer or supplier's	s deta	ils	
Comp	bany	:	MSD	
Addre	ess	:		, 6th floor, Ciudad Autonoma rgentina C1013AAP
Telep	hone	:	908-740-4000	
Emer	gency telephone	:	1-908-423-6000	
E-ma	il address	:	EHSDATASTEV	VARD@msd.com
Reco	mmended use of the	chem	ical and restriction	ons on use
	mmended use ictions on use	:	Veterinary produ Not applicable	ıct

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification		
Flammable liquids	:	Category 3
Acute toxicity (Oral)	:	Category 4
Acute toxicity (Dermal)	:	Category 3
Skin corrosion/irritation	:	Category 2
Serious eye damage/eye irritation	:	Category 2A
Reproductive toxicity	:	Category 1B
Specific target organ toxicity - single exposure (Oral)	:	Category 2
Specific target organ toxicity - repeated exposure	:	Category 2 (Auditory system)
Specific target organ toxicity - repeated exposure (Oral)	:	Category 2
Aspiration hazard	:	Category 1
Short-term (acute) aquatic hazard	:	Category 3



Version 4.1	Revision Date: 30.09.2023	SDS Number: 4019087-00015	Date of last issue: 04.04.2023 Date of first issue: 25.02.2019
Long [.] hazar	-term (chronic) aquatic rd	: Category 3	
GHS	label elements		
	rd pictograms		
Signa	al Word	: Danger	
Haza	rd Statements	H302 Harmful H304 May be H311 Toxic in H315 Causes H319 Causes H360D May da H371 May cau H373 May cau peated expose H373 May cau prolonged or r	fatal if swallowed and enters airways. contact with skin.
Preca	autionary Statements	P202 Do not h and understoc P210 Keep av and other ignit P260 Do not b P264 Wash sk P270 Do not e P273 Avoid re	vay from heat, hot surfaces, sparks, open flames tion sources. No smoking. oreathe mist or vapors. kin thoroughly after handling. eat, drink or smoke when using this product. elease to the environment. otective gloves/ protective clothing/ eye protec-
		CENTER/ doc P302 + P352 ter.Call a POIS P303 + P361 ly all contamin P305 + P351 for several min easy to do. Co P308 + P311 CENTER/ doc P331 Do NOT	 + P312 IF ON SKIN: Wash with plenty of wa- SON CENTER/ doctor if you feel unwell. + P353 IF ON SKIN (or hair): Take off immediate bated clothing. Rinse skin with water. + P338 IF IN EYES: Rinse cautiously with water butes. Remove contact lenses, if present and portinue rinsing. IF exposed or concerned: Call a POISON



Version 4.1	Revision Date: 30.09.2023	SDS Number: 4019087-00015	Date of last issue: 04.04.2023 Date of first issue: 25.02.2019			
		tention.	f eye irritation persists: Get medical advice/ at- Fake off immediately all contaminated clothing fore reuse.			
		Storage: P405 Store locked up.				
		Disposal:	incu up.			
		P501 Dispose disposal plant.	of contents/ container to an approved waste			
Othe	r hazards which do ı	not result in classifica	ition			
Vapo	rs may form explosive	e mixture with air.				

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Paraffin oil	8012-95-1	>= 50 -< 70
Xylene	1330-20-7	>= 10 -< 20
Flumethrin	69770-45-2	>= 1 -< 2,5
Toluene	108-88-3	>= 0,25 -< 1

SECTION 4. FIRST AID MEASURES

General advice	:	In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
If inhaled	:	If inhaled, remove to fresh air. Get medical attention.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
In case of eye contact	:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention.
If swallowed	:	If swallowed, DO NOT induce vomiting. If vomiting occurs have person lean forward. Call a physician or poison control center immediately. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, both acute and delayed	:	



Version 4.1	Revision Date: 30.09.2023		S Number: 19087-00015	Date of last issue: 04.04.2023 Date of first issue: 25.02.2019			
	tection of first-aiders es to physician	:	Causes serious eye irritation. May damage the unborn child. May cause damage to organs if swallowed. May cause damage to organs through prolonged or repeated exposure. First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8). Treat symptomatically and supportively.				
SECTIO	N 5. FIRE-FIGHTING ME	ASU	RES				
Suit	table extinguishing media	:	Water spray Alcohol-resistant Carbon dioxide (C Dry chemical				
Uns	suitable extinguishing	:	High volume wate	er jet			
Spe	aia ecific hazards during fire ting		fire. Flash back possik Vapors may form	d water stream as it may scatter and spread ble over considerable distance. explosive mixtures with air. bustion products may be a hazard to health.			
Haz	zardous combustion prod-	:	Carbon oxides				
Spe ods	ecific extinguishing meth-	:	cumstances and t Use water spray t	measures that are appropriate to local cir- the surrounding environment. to cool unopened containers. ged containers from fire area if it is safe to do			
	ecial protective equipment fire-fighters	:	In the event of fire	e, wear self-contained breathing apparatus. tective equipment.			
SECTIO	N 6. ACCIDENTAL RELE	ASE	MEASURES				
tive	sonal precautions, protec- equipment and emer- icy procedures	:	Follow safe handl	es of ignition. tective equipment. ing advice (see section 7) and personal tent recommendations (see section 8).			
Env	vironmental precautions			he environment. akage or spillage if safe to do so. g over a wide area (e.g., by containment or			

 Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

 Methods and materials for containment and cleaning up
 : Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapors/mists with a water spray

jet.



Version	Revision Date:	SDS Number:	Date of last issue: 04.04.2023
4.1	30.09.2023	4019087-00015	Date of first issue: 25.02.2019
		containment to can be pumped container. Clean up rema absorbent. Local or nation disposal of this employed in th determine whic Sections 13 an	, provide diking or other appropriate keep material from spreading. If diked material d, store recovered material in appropriate ining materials from spill with suitable al regulations may apply to releases and material, as well as those materials and items e cleanup of releases. You will need to ch regulations are applicable. d 15 of this SDS provide information regarding national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures	:	See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
Local/Total ventilation	:	If sufficient ventilation is unavailable, use with local exhaust ventilation. Use explosion-proof electrical, ventilating and lighting equip- ment.
Advice on safe handling	:	Do not get on skin or clothing. Do not breathe mist or vapors. Do not swallow. Do not get in eyes. Wash skin thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment Non-sparking tools should be used. Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product. Take care to prevent spills, waste and minimize release to the environment.
Conditions for safe storage	:	Keep in properly labeled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.
Materials to avoid	:	Do not store with the following product types: Strong oxidizing agents Self-reactive substances and mixtures Organic peroxides Flammable solids Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures Substances and mixtures which in contact with water emit flammable gases Explosives



Version	Revision Date:	SDS Number:	Date of last issue: 04.04.2023
4.1	30.09.2023	4019087-00015	Date of first issue: 25.02.2019

Gases

Very acutely toxic substances and mixtures

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

				.		
Components	CAS-No.	Value type (Form of	Control parame- ters / Permissible	Basis		
		exposure)	concentration			
Paraffin oil	8012-95-1	CMP (Mist)	5 mg/m³	AR OEL		
		CMP - CPT (Mist)	10 mg/m³	AR OEL		
		TWA (Inhalable particulate matter)	5 mg/m³	ACGIH		
Xylene	1330-20-7	CMP	100 ppm	AR OEL		
·	Further inform	ation: A4 - Not o	classifiable as a huma	n carcinogen		
		CMP - CPT	150 ppm	AR OEL		
	Further inform	ation: A4 - Not o	classifiable as a huma	n carcinogen		
		TWA	20 ppm	ACGIH		
Flumethrin	69770-45-2	TWA	45 µg/m3 (OEB 3)	Internal		
	Further inform	ation: Skin				
		Wipe limit	450 µg/100 cm ²	Internal		
Toluene	108-88-3	CMP	50 ppm	AR OEL		
	Further inform Skin	Further information: A4 - Not classifiable as a human carcinogen, Skin				
		TWA	20 ppm	ACGIH		

Ingredients with workplace control parameters

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentra- tion	Basis
Xylene	1330-20-7	methyl hippuric acids	Urine	End of shift	1.5 g/g creatinine	AR BEI
		Methylhippu ric acids	Urine	End of shift (As soon as possible after exposure ceases)	1.5 g/g creatinine	ACGIH BEI
Toluene	108-88-3	o-Cresol	Urine	End of shift	0,5 mg/l	AR BEI
		hippuric acid	Urine	End of shift	1.6 g/g creatinine	AR BEI
		toluene	Blood	Prior to last shift of work- week	0,05 mg/l	AR BEI



ersion 1			S Number: 19087-00015	Date of last issue: 04.04.2023 Date of first issue: 25.02.2019			
			Toluene	In blood	Prior to last shift of work- week	0,02 mg/l	ACGIH BEI
			Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0,03 mg/l	ACGIH BEI
			o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g creatinine	ACGIH BEI
g"	neering measures		 Use appropriate engineering controls and manufacturing technologies to control airborne concentrations (e.g., drij less quick connections). All engineering controls should be implemented by facilit design and operated in accordance with GMP principles protect products, workers, and the environment. Containment technologies suitable for controlling compo are required to control at source and to prevent migration the compound to uncontrolled areas (e.g., open-face containment devices). Minimize open handling. 				
			Use explosion-p equipment.	roof electrica	al, ventilating	and lighting	
Perso	onal protective equi	ipment					
Respi	iratory protection	:	If adequate loca exposure asses recommended g	sment demo	nstrates exp	osures outsid	
	ter type protection	:	Combined partic	culates and o	rganic vapo	r type	
Ma	aterial	:	Chemical-resista	ant gloves			
Re	emarks	:	Consider double flammable, whic protection.				5
Eye p	protection	:	Wear safety glas If the work envir mists or aerosol Wear a faceshie potential for dire aerosols.	onment or ac s, wear the a eld or other fu	ctivity involve oppropriate g Ill face prote	es dusty conc oggles. ction if there	is a
Skin a	and body protection	:	Work uniform or Additional body task being perfo disposable suits	oron, gauntle			



Version	Revision Date: 30.09.2023	SDS Number:	Date of last issue: 04.04.2023
4.1		4019087-00015	Date of first issue: 25.02.2019
Hygie	ne measures	contaminated c If exposure to c eye flushing sys working place. When using do Wash contamin The effective op engineering cor appropriate deg	hemical is likely during typical use, provide stems and safety showers close to the not eat, drink or smoke. hated clothing before re-use. beration of a facility should include review of htrols, proper personal protective equipment, gowning and decontamination procedures, ne monitoring, medical surveillance and the

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Aqueous solution
Color	:	light brown, yellow
Odor	:	No data available
Odor Threshold	:	No data available
рН	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	54 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	0,820 - 0,900 g/cm³
Solubility(ies) Water solubility	:	No data available



Flumethrin (1%) Formulation

Version 4.1	Revision Date: 30.09.2023		5 Number: 9087-00015	Date of last issue: 04.04.2023 Date of first issue: 25.02.2019
octar Autoi Deco Visco		:	Not applicable No data available No data available)
	scosity, kinematic	:	No data available	3
	zing properties cular weight	:	The substance o	r mixture is not classified as oxidizing.
Partic	cle size	:	Not applicable	

SECTION 10. STABILITY AND REACTIVITY

Reactivity Chemical stability Possibility of hazardous reac- tions	:	Not classified as a reactivity hazard. Stable under normal conditions. Flammable liquid and vapor. Vapors may form explosive mixture with air. Can react with strong oxidizing agents.
Conditions to avoid Incompatible materials Hazardous decomposition products	:	Heat, flames and sparks. Oxidizing agents No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	:	Inhalation Skin contact Ingestion Eye contact
Acute toxicity		
Harmful if swallowed. Toxic in contact with skin.		
Product:		
Acute oral toxicity	:	Acute toxicity estimate: 404,59 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 40 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: 402,36 mg/kg Method: Calculation method



Version 4.1	Revision Date: 30.09.2023	SDS Number 4019087-000	
Com	ponents:		
Para	ffin oil:		
Acute	e oral toxicity	: LD50 (Ra	t): > 5.000 mg/kg
Acute	e dermal toxicity		bbit): > 2.000 mg/kg ent: The substance or mixture has no acute dermal
Xyler	ne:		
-	e oral toxicity		t): 3.523 mg/kg Directive 67/548/EEC, Annex V, B.1.
Acute	e inhalation toxicity	Exposure	t): 27,571 mg/l time: 4 h sphere: vapor
Acute	e dermal toxicity	: LD50 (Ra	bbit): > 4.200 mg/kg
Flum	ethrin:		
Acute	e oral toxicity	: LD50 (Ra	t): > 20 mg/kg
		LD50 (Mo	use): > 20 mg/kg
Acute	e inhalation toxicity	: LC50 (Ra	t): > 2.934 mg/l
Acute	e dermal toxicity	: LD50 (Ra	t): > 5 mg/kg
Tolue	ene:		
Acute	e oral toxicity	: LD50 (Ra	t): > 5.000 mg/kg
Acute	e inhalation toxicity	Exposure	t): 28,1 mg/l time: 4 h sphere: vapor
Acute	e dermal toxicity	: LD50 (Ra	bbit): > 5.000 mg/kg
-	corrosion/irritation es skin irritation.		
Com	ponents:		
	ffin oil:		
Spec Resu		: Rabbit : No skin in	ritation
Xyler		D-LL'	
Spec Resu		: Rabbit : Skin irritat	ion



sion	Revision Date: 30.09.2023	SDS Number: 4019087-00015	Date of last issue: 04.04.2023 Date of first issue: 25.02.2019						
Flum	ethrin:								
Resu	t	: No skin irritation							
Tolue	ene:								
Speci	es	: Rabbit							
Metho		: Directive 67/548/	EEC, Annex V, B.4.						
Resu	t	: Skin irritation							
Serio	us eye damage/eye	irritation							
Cause	es serious eye irritati	on.							
<u>Com</u>	oonents:								
Paraf	fin oil:								
Speci		: Rabbit							
Resu	t	: No eye irritation							
Xyler	ie:								
Speci	es	: Rabbit							
Resu									
Flum	ethrin:								
Resu	t	: Mild eye irritation							
Tolue	ene:								
Speci		: Rabbit							
Resu		: No eye irritation							
Metho	od	: OECD Test Guid	eline 405						
Resp	iratory or skin sens	itization							
Skin	sensitization								
	assified based on av	ailable information							
	iratory sensitizatior								
-	assified based on av								
<u>Com</u>	oonents:								
Xyler	ie:								
Test ⁻		: Local lymph node	e assay (LLNA)						
	es of exposure	: Skin contact							
Speci		: Mouse							
Resu	t	: negative							
Tolue									
Test ⁻		: Maximization Tes	st						
	es of exposure	: Skin contact							
Speci		: Guinea pig							
	. .	. Dimesting 07/540/	Method : Directive 67/548/EEC, Annex V, B.6.						
		: Directive 67/548/ : negative	EEC, Annex V, B.6.						



.1	Revision Date: 30.09.2023	SDS Number: 4019087-00015	Date of last issue: 04.04.2023 Date of first issue: 25.02.2019
	cell mutagenicity assified based on ava	ailable information.	
<u>Comp</u>	oonents:		
Xylen Genot	e: toxicity in vitro	: Test Type: Ba Result: negat	acterial reverse mutation assay (AMES) ive
		Test Type: Cl Result: negat	nromosome aberration test in vitro ive
		Test Type: In Result: negat	vitro mammalian cell gene mutation test ive
		Test Type: In malian cells Result: negat	vitro sister chromatid exchange assay in mam- ive
Genot	toxicity in vivo	Species: Mou	oute: Skin contact
Flume	ethrin:		
Genot	toxicity in vitro		icrobial mutagenesis assay (Ames test) Salmonella typhimurium ocal
		Test system: Result: positiv	nromosomal aberration Chinese hamster ovary cells ve t classified due to inconclusive data.
			nromosomal aberration Human lymphocytes ive
		Test Type: in Test system: Result: negat	
	cell mutagenicity - ssment	: Weight of evic cell mutagen.	dence does not support classification as a germ
Tolue	ene:		
Genot	toxicity in vitro	: Test Type: In Result: negat	vitro mammalian cell gene mutation test ive
		Test Type: Ba Result: negat	acterial reverse mutation assay (AMES) ive



rsion I	Revision Date: 30.09.2023		S Number: 9087-00015	Date of last issue: 04.04.2023 Date of first issue: 25.02.2019				
Genotoxicity in vivo			cytogenetic test Species: Rat	agenicity (in vivo mammalian bone-marrow , chromosomal analysis) ite: Intraperitoneal injection				
			Test Type: Rodent dominant lethal test (germ cell) (in vivo) Species: Mouse Application Route: inhalation (vapor) Method: OECD Test Guideline 478 Result: negative					
	nogenicity assified based on avai	ilable ii	nformation.					
Comp	oonents:							
Xylen	ie:							
Speci	es	-	Rat					
	cation Route		Ingestion					
Resul	sure time t		103 weeks negative					
-								
	ethrin:		Det					
Speci Applic	es cation Route		Rat Oral					
	sure time		2 Years					
NOAE			0,5 mg/kg body	weight				
Resul	t	:	negative					
Carcir ment	nogenicity - Assess-		Weight of evide cinogen	nce does not support classification as a ca				
Tolue	ene:							
Speci		-	Rat					
	cation Route sure time		inhalation (vapo 103 weeks	or)				
Resul			negative					
Speci	es		Mouse					
Applic	cation Route	:	Skin contact					
	sure time		24 Months					
Resul	τ	:	negative					
-	oductive toxicity Jamage the unborn chi	ld.						
-	oonents:							
Xylen	ie:							
-	s on fertility		Species: Rat	-generation reproduction toxicity study				



/ersion I.1	Revision Date: 30.09.2023	-	0S Number: 19087-00015	Date of last issue: 04.04.2023 Date of first issue: 25.02.2019
			Result: negative	
Effects	on fetal development	:	Species: Rat	o-fetal development : inhalation (vapor)
Flume	thrin:			
Effects	on fetal development	:		: Oral oxicity: NOAEL: 0,36 mg/kg body weight oxicity observed., Reduced offspring weight
				: Oral oxicity: NOAEL: 0,5 mg/kg body weight oxicity observed., Skeletal malformations.,
			Test Type: Develor Species: Rabbit Application Route Developmental To Result: No teratog	: Oral oxicity: NOAEL: 1,7 mg/kg body weight
Reproc sessme	ductive toxicity - As- ent	:	May damage the	unborn child.
Toluer	ie:			
Effects	on fertility	:	Species: Rat	eneration reproduction toxicity study : inhalation (vapor) est Guideline 416
Effects	on fetal development	:	Species: Rat	o-fetal development : inhalation (vapor)
Reproc sessme	luctive toxicity - As- ent	:	Some evidence o animal experimen	f adverse effects on development, based on ts.
	single exposure use damage to organs	sifs	wallowed.	
	onents:			
Xylene Assess		:	May cause respira	atory irritation.



Version 4.1	Revision Date: 30.09.2023	SDS Number: 4019087-00015	Date of last issue: 04.04.2023 Date of first issue: 25.02.2019
Flum	nethrin:		
	es of exposure	: Oral	
Asse	essment	: Causes dama	ge to organs.
Tolu	ene:		
Asse	essment	: May cause dro	owsiness or dizziness.
STO	T-repeated exposure		
			or repeated exposure if swallowed. through prolonged or repeated exposure.
Com	ponents:		
Xyle	ne:		
	es of exposure	: inhalation (var	
	et Organs essment		m luce significant health effects in animals at con- >0.2 to 1 mg/l/6h/d.
			5
Flum	nethrin:		
	es of exposure	: Oral	re to ergone through prolonged or repeated
ASSE	essment	exposure.	ge to organs through prolonged or repeated
Tolu	ene:		
	es of exposure	: Inhalation	
	et Organs essment	: Central nervou	is system mage to organs through prolonged or repeated
//000	Someric	exposure.	mage to organis through protonged of repeated
Repe	eated dose toxicity		
Com	ponents:		
Para	ffin oil:		
Spec		: Rat, female	
LOA	EL ication Route	: 161 mg/kg : Ingestion	
	osure time	: 90 Days	
Xyle	ne:		
Spec		: Rat	
LÒA	EL	: > 0,2 - 1 mg/l	N N N N N N N N N N N N N N N N N N N
	ication Route	: inhalation (vap : 13 Weeks	por)
Rem			from similar materials
Spec	cies	: Rat	
LÒA	EL	: 150 mg/kg	
	ication Route	: Ingestion	
Expo	osure time	: 90 Days	



Version 4.1	Revision Date: 30.09.2023		DS Number: 19087-00015	Date of last issue: 04.04.2023 Date of first issue: 25.02.2019
Spec NOA Appli Expo Targe Symp Spec NOA Appli	EL cation Route sure time et Organs otoms ies EL cation Route		Dog 0,88 mg/kg Oral	n, Skin etite, Skin disorders
Targe	sure time et Organs otoms	:	13 Weeks digestive system decrease in app	n, Hair, Skin etite, Skin disorders
	ies	:	Rat 1,875 mg/l inhalation (vapo 6 Months	r)
		:	Rat 625 mg/kg Ingestion 13 Weeks	

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Paraffin oil:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Toluene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Experience with human exposure

Components:

Toluene:

Inhalation

: Target Organs: Central nervous system Symptoms: Neurological disorders



rsion	Revision Date: 30.09.2023		0S Number: 19087-00015	Date of last issue: 04.04.2023 Date of first issue: 25.02.2019
	12. ECOLOGICAL INFO	DRN		
Feete				
Ecoto	-			
	<u>onents:</u>			
Paraff Toxicit	in oil: ty to fish	:	Exposure time: 96 Test substance: V	nus maximus (turbot)): > 100 mg/l 5 h Vater Accommodated Fraction on data from similar materials
	ty to daphnia and other c invertebrates	:	Exposure time: 48 Test substance: V	sa (Calanoid copepod)): > 100 mg/l 3 h Vater Accommodated Fraction on data from similar materials
Toxicit plants	ty to algae/aquatic	:	Exposure time: 72 Test substance: V	na costatum (marine diatom)): > 100 mg/l 2 h Vater Accommodated Fraction on data from similar materials
			Exposure time: 72 Test substance: V	ema costatum (marine diatom)): > 1 mg/l 2 h Vater Accommodated Fraction on data from similar materials
Xylen	e:			
	ty to fish	:	LC50 (Oncorhync Exposure time: 96	hus mykiss (rainbow trout)): 13,5 mg/l 3 h
	ty to daphnia and other c invertebrates	:	Exposure time: 24 Method: OECD Te	
Toxicit plants	ty to algae/aquatic	:	EC50 (Skeletoner Exposure time: 72	na costatum (marine diatom)): 10 mg/l ? h
Toxicit icity)	ty to fish (Chronic tox-	:	Exposure time: 35 Method: OECD To	
	ty to daphnia and other c invertebrates (Chron- city)	:	Exposure time: 21 Method: OECD Te	
Toxicit	ty to microorganisms	:	NOEC: > 100 mg/ Exposure time: 3 Method: OECD To Remarks: Based	h



	Revision Date: 30.09.2023		DS Number: Date of last issue: 04.04.2023 Date of first issue: 25.02.2019	
Flume	ethrin:			
Toxicit icity)	ty to fish (Chronic tox-	:	NOEC (Danio rerio (zebra fish)): 0,046 mg/l Exposure time: 144 h	
M-Fac toxicity	tor (Chronic aquatic /)	:	1	
Tolue	ne:			
Toxicit	ty to fish	:	LC50 (Oncorhynchus kisutch (coho salmon)): 5,5 mg/l Exposure time: 96 h	
	y to daphnia and other cinvertebrates	:	EC50 (Ceriodaphnia dubia (water flea)): 3,78 mg/l Exposure time: 48 h	
Toxicit plants	ty to algae/aquatic	:	NOEC (Skeletonema costatum (marine diatom)): 10 mg Exposure time: 72 h	
Toxicit icity)	ty to fish (Chronic tox-	:	NOEC (Oncorhynchus kisutch (coho salmon)): 1,39 mg/ Exposure time: 40 d	
	ty to daphnia and other c invertebrates (Chron-	:	NOEC (Ceriodaphnia dubia (water flea)): 0,74 mg/l Exposure time: 7 d	
	ty to microorganisms	:	EC50 (Nitrosomonas sp.): 84 mg/l Exposure time: 24 h	
Persis	stence and degradabili	ty		
Comp	onents:			
	onents.			
Xylen				
Xylen		:	Result: Readily biodegradable. Biodegradation: > 70 % Exposure time: 28 d Method: OECD Test Guideline 301F Remarks: Based on data from similar materials	
Xylen Biodeg	e: gradability	:	Biodegradation: > 70 % Exposure time: 28 d Method: OECD Test Guideline 301F	
Xylend Biodeg	e: gradability	:	Biodegradation: > 70 % Exposure time: 28 d Method: OECD Test Guideline 301F	
Xylene Biodeg Tolue Biodeg	e: gradability ne:	:	Biodegradation: > 70 % Exposure time: 28 d Method: OECD Test Guideline 301F Remarks: Based on data from similar materials Result: Readily biodegradable. Biodegradation: 80 %	
Xylend Biodeg Tolue Biodeg Bioac	e: gradability ne: gradability	:	Biodegradation: > 70 % Exposure time: 28 d Method: OECD Test Guideline 301F Remarks: Based on data from similar materials Result: Readily biodegradable. Biodegradation: 80 %	
Xylend Biodeg Tolue Biodeg Bioac	e: gradability ne: gradability cumulative potential <u>onents:</u>	:	Biodegradation: > 70 % Exposure time: 28 d Method: OECD Test Guideline 301F Remarks: Based on data from similar materials Result: Readily biodegradable. Biodegradation: 80 %	
Xylend Biodeg Tolue Biodeg Bioacc Comp Paraff Partitio	e: gradability ne: gradability cumulative potential <u>onents:</u>	:	Biodegradation: > 70 % Exposure time: 28 d Method: OECD Test Guideline 301F Remarks: Based on data from similar materials Result: Readily biodegradable. Biodegradation: 80 %	
Xylend Biodeg Tolue Biodeg Bioacc Comp Paraff Partitio	e: gradability ne: gradability cumulative potential onents: in oil: on coefficient: n- ol/water		Biodegradation: > 70 % Exposure time: 28 d Method: OECD Test Guideline 301F Remarks: Based on data from similar materials Result: Readily biodegradable. Biodegradation: 80 % Exposure time: 20 d	



Version 4.1	Revision Date: 30.09.2023	SDS Number: 4019087-00015	Date of last issue: 04.04.2023 Date of first issue: 25.02.2019
Partiti	ethrin: ion coefficient: n- ol/water	: log Pow: 6,2	2
Tolue	ene:		
Bioac	cumulation	•	uciscus idus (Golden orfe) ration factor (BCF): 90
	ion coefficient: n- ol/water	: log Pow: 2,	73
Mobi	lity in soil		
No da	ata available		
Othe	r adverse effects		
No da	ata available		

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods		
Waste from residues	:	Do not dispose of waste into sewer. Dispose of in accordance with local regulations.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG UN number		UN 1992
•••••••	:	FLAMMABLE LIQUID, TOXIC, N.O.S.
Proper shipping name	•	(Xylene, Flumethrin)
Class	:	3
Subsidiary risk	:	6.1
Packing group	:	111
Labels	:	3 (6.1)
Environmentally hazardous	:	no
IATA-DGR		
UN/ID No.	:	UN 1992
Proper shipping name	:	Flammable liquid, toxic, n.o.s.
		(Xylene, Flumethrin)
Class	:	3
Subsidiary risk	:	6.1
Packing group	•	111
r doking group		
Labels	:	Flammable Liquids, Toxic
	:	



Versi 4.1	on Revision Date 30.09.2023		DS Number: 019087-00015	Date of last issue: 04.04.2023 Date of first issue: 25.02.2019
I	aircraft) Packing instruction (pa ger aircraft)	assen- :	355	
i	I MDG-Code UN number Proper shipping name	:	UN 1992 FLAMMABLE LIC (Xylene, Flumethi	QUID, TOXIC, N.O.S.
(Class	:	3)
5	Subsidiary risk	:	6.1	
I	Packing group	:	III	
l	Labels	:	3 (6.1)	
I	EmS Code	:	F-E, S-D	
1	Marine pollutant	:	no	

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Argentina. Carcinogenic Substances and Agents Registry.	:	Not applicable
Control of precursors and essential chemicals for the preparation of drugs.	:	Not applicable

The ingredients of this product are reported in the follow	wing inventories:
--	-------------------

AICS	:	not determined
DSL	:	not determined
IECSC	:	not determined

SECTION 16. OTHER INFORMATION

Revision Date	:	30.09.2023
Date format	:	dd.mm.yyyy

Further information

Sources of key data used to	:	Internal technical data, data from raw material SDSs, OECD
compile the Material Safety		eChem Portal search results and European Chemicals Agen-
Data Sheet		cy, http://echa.europa.eu/



Version	Revision Date:	SDS Number:	Date of last issue: 04.04.2023
4.1	30.09.2023	4019087-00015	Date of first issue: 25.02.2019

Full text of other abbreviations

ACGIH ACGIH BEI AR BEI AR OEL	:	USA. ACGIH Threshold Limit Values (TLV) ACGIH - Biological Exposure Indices (BEI) Argentina. Biological Exposure Indices Argentina. Occupational Exposure Limits
ACGIH / TWA AR OEL / CMP AR OEL / CMP - CPT	:	8-hour, time-weighted average TLV (Threshold Limit Value) STEL (Short Term Limit Value)

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AR / Z8